Univerza v Ljubljani

ViCOS Visual Cognitive Systems Lab

Machine perception
Image formation & Image processing 1

Matej Kristan



Laboratorij za Umetne Vizualne Spoznavne Sisteme,
Fakulteta za računalništvo in informatiko,
Univerza v Ljubljani

Machine perception

IMAGE FORMATION

Let’s design a camera!



- Idea 1: put an object in front of a film...

- Do we get a good image of the object?

Let’s design a camera!



- Add a barrier that blocks most of the rays
  - Significantly reduces blurring
  - The „hole“ is known as aperture

A pinhole camera

- 500 BC Mo Ti...
- ...1485 Leonardo da Vinci
- A simple standard camera model
  - A box with a small aperture
  - Works in practice





Effects of the aperture size

- Too large – multiple directions averaging, resulting in a blurred image.
- Too small – light starts diffracting, causing blurred image.
- In general small number of rays hit the film, which results in a dark image.
- How do we deal with this?



Vir: Forsyth & Ponce

Let’s add a lens...



- The lens focuses light to film
  - The rays that travel through the center do not refract.

Let’s add a lens...



- The lens focuses light to film
  - The rays that travel through the center do not refract.
  - Points at particular distance remain in-focus.
  - Points at other distances are blurred.

Focus and the depth-of-field

- Thin lens: Points at different depths get focused at different depths of image plane.

  (Real-world lens have a greater depth of field)



- Depth of field: distance between image planes at which the blurring effect is sufficiently small..

Focus and the depth-of-field

- Effects of aperture on the depth-of-field





- Small aperture increases the depth-of-field.
- But due to reduced illumination we have to increase the exposure time.

Field of view

- Field of view (FOV) $(2 \times \varphi)$ is an angular measure of space perceived by the camera.



$$\varphi = \tan^{-1}\left(\frac{d}{2f}\right)$$

- Larger focal length → Smaller field of view

Field of view

- Small *f* results in wide-angle image (Large field of view) ⟶
  - More 3D points project to the sensor.


28 mm lens, 65.5° × 46.4°


50 mm lens, 39.6° × 27.0°

- Large *f* results in a telescopic image (small FOV) ⟶
  - Smaller portion of 3D scene is projected to the sensor.


70 mm lens, 28.9° × 19.5°


210 mm lens, 9.8° × 6.5°

$$\varphi = \tan^{-1}\left(\frac{d}{2f}\right)$$

Field of view and focal length



Small FOV, large *f*
Camera far away from the car

Large FOV, small *f*
Camera close to the car

Sources: A. Efros, F. Durand

Chromatic aberration

- Different wave-lengths refract at different angle and focus at slightly different distances:



Close to image center

Close to image edge

Spherical aberration

- Spherical lenses do not focus the light perfectly.
- Rays close to lens edge focus closer than those at the center.







http://photographylife.com/what-is-spherical-aberration

Vignetting



Radial distortion



Without distortion

Barrel distortion

- Due to lens imperfections or fisheye.
- Most apparent at the edge of the image.

Digital image



- Instead of film, use matrix (array) of sensors.
- *Discretize* image into pixels.
- *Quantize* light into intensity levels.

Sensor: Camera

Electromagnetic spectrum



Visible light

Near-infrared light

Far-infrared light



Terahertz light

http://userweb.elec.gla.ac.uk/d/dpaul/terahertz.html

Visible light cams: CCD vs CMOS

Charge coupled device (CCD)



Complementary metal–oxide–semiconductor (CMOS)



- In both: Photons cause charge on each sensor „cell“.
- CCD reads out the charge (FIFO) serially and digitizes.
- CMOS performs digitization on each cell separately.
- CCD delivers a better images.
- CMOS is cheaper to produce and is thus wide-spread.

Color perception in digital cameras

Bayer sensor



Why twice as many greens compared to blue and red?

Luminance is mostly determined by the green values.

Human visual system much more sensitive to changes in intensity than in chroma (color).

Color perception in digital cameras

What you see

Your camera sees



Missing green!



De-mosaicking: The missing color channels at a pixel need to be interpolated!



Color perception : Foveon X3

- CMOS-based sensor.
- Based on the fact, that red, green and blue color penetrate the silicon at different depths.



http://www.foveon.com/article.php?a=67



http://en.wikipedia.org/wiki/Foveon_X3_sensor

Better image quality

Bayer-like



Foveon X3

From camera to perception



- How does a human perceive the bottles, plates, forks,..., using only brightness?
- How do we perceive depth?
- Can a computer program do that?

Machine perception

IMAGE PROCESSING 1

Binary images

- Only two possible gray levels
- Foreground vs. background

1	1	0	1	1	1	0	1
1	1	0	1	0	1	0	1
1	1	1	1	0	0	0	1
0	0	0	0	0	0	0	1
1	1	1	1	0	1	0	1
0	0	0	1	0	1	0	1
1	1	0	1	0	0	0	1
1	1	0	1	0	1	1	1



Usage: Machine vision



Fig. 3 Schematic diagram of marking inspection setup at Texas Instruments



Fig. 7 Binarized image

Fig. 9 Row sum for separating a row



R. Nagarajan et al. “A real time marking inspection scheme for semiconductor industries“, 2006

Source: Bastian Leibe

Usage : Text analysis



Hand written numbers

OCR on documents

Text in the wild: after detection

Source: Till Quack, Martin Renold

Source: Bastian Leibe

Usage: Medical imaging



Source: D. Kim et al., Cytometry 35(1), 1999



Task: Detect “round” cells

Generate hypotheses



Classify each region into a “round” and “not round”



Keep “round” regions



Localize, Describe, Classify

Localize: Sequence of processing steps

- Convert gray image to a binary image
  - Thresholding
- Clean binary image
  - Morphologic filtering
- Extract individual regions
  - Connected components





… then describe each localized region and classify

Machine perception

IMAGE THRESHOLDING



Thresholding

- Transform an image into a Binary Mask
- Various approaches
  - Apply a single threshold

$$F_T[i,j] = \begin{cases} 1, & \text{if } F[i,j] \geq T \\ 0, & \text{otherwise} \end{cases}$$

  - Apply two thresholds

$$F_T[i,j] = \begin{cases} 1, & \text{if } T_1 \leq F[i,j] \leq T_2 \\ 0, & \text{otherwise} \end{cases}$$

  - A general view: apply a classifier

$$F_T[i,j] = \begin{cases} 1, & \text{if } F[i,j] \in Z \\ 0, & \text{otherwise} \end{cases}$$

Object/background separation



Source: Bastian Leibe

A simple example: Bimodal histogram





Ideal case:
bright object on
dark background.





A more realistic noisy
image.

A not so simple example...

- What to do here?



Separate modes Overlapping modes Multiple modes

- Generally thresholding is a difficult problem
  - Domain knowledge helps a great deal.
  - E.g., the portion on letters on a page.
  - E.g., size of the structure we want to detect...

Source: Shapiro & Stockman

Global binarization [Otsu '79]

- Find a threshold *T*, that minimizes intensity variances within classes separated by *T*:

$$\sigma^2_{within}(T) = n_1(T)\sigma_1^2(T) + n_2(T)\sigma_2^2(T)$$

$$n_1(T) = \left|\{I_{(x,y)} < T\}\right|, n_2(T) = \left|\{I_{(x,y)} \geq T\}\right|$$



- This equals to maximization of between class variance $\sigma_{between}$:

$$\sigma^2_{between}(T) = \sigma^2 - \sigma^2_{within}(T)$$
$$= n_1(T)n_2(T)[\mu_1(T) - \mu_2(T)]^2$$

Otsu, N (1979), "A threshold selection method from gray-level histograms", IEEE SMC

Source: Bastian Leibe

Otsu's Algorithm

For threshold value *T*

1. Separate the pixels into two groups by intensity threshold *T*
2. For each group get an average intensity and calculate $\sigma^2_{between}$.

Select the T*, that maximizes the variance:

$$T^* = \arg\max_T [\sigma^2_{between}(T)]$$



Local binarization [Niblack'86]

- Estimate a local threshold in neighborhood W:

$$T_W = \mu_W + k \cdot \sigma_W$$

with $k \in [-1,1]$ set by user.

- Calculate the threshold separately for each pixel.





Niblack, W (1986), An introduction to Digital Image Processing, Prentice-Hall

Examples of thresholding



Original



Global (Otsu)



Local (Niblack)

Additional improvements

- The shade in documents is often smooth...

⇒*Try to model it by a polynomial!*



Figure 4: Face Dataset: We show the ROC curve for the full set SVM of 1434 support vectors (bold solid line), two reduced set methods of 10 and 100 reduced sets (both in dashed line). The dashed line of the 100 reduced set coincide almost entirely with the full set of support vectors. In addition, we show two element sets of 200 and 576 elements (both in solid line). Note that an element set of 576 elements is equivalent to a *single* support vector. Hence, the 576 element set is equivalent to the 10 reduced set in terms of classification power but uses much less memory.

Original



Fitted surface



Figure 4: Face Dataset: We show the ROC curve for the full set SVM of 1434 support vectors (bold solid line), two reduced set methods of 10 and 100 reduced sets (both in dashed line). The dashed line of the 100 reduced set coincide almost entirely with the full set of support vectors. In addition, we show two element sets of 200 and 576 elements (both in solid line). Note that an element set of 576 elements is equivalent to a *single* support vector. Hence, the 576 element set is equivalent to the 10 reduced set in terms of classification power but uses much less memory.

Shadow compensation



Figure 4: Face Dataset: We show the ROC curve for the full set SVM of 1434 support vectors (bold solid line), two reduced set methods of 10 and 100 reduced sets (both in dashed line). The dashed line of the 100 reduced set coincide almost entirely with the full set of support vectors. In addition, we show two element sets of 200 and 576 elements (both in solid line). Note that an element set of 576 elements is equivalent to a *single* support vector. Hence, the 576 element set is equivalent to the 10 reduced set in terms of classification power but uses much less memory.

Binarized result

Source: S. Lu & C. Tan, ICDAR'07

Comparison of results

Original image



Global (Otsu)



Local (Sauvola)

Polynomial + global



Vir: S. Lu & C. Tan, ICDAR'07

Machine perception

CLEANING THE IMAGE



Cleaning the binary image

- Thresholded image still includes noise



- Require post-processing to remove artefacts
- Morphological operators
  - Remove isolated points and small structures
  - Fill holes

Source: Bastian Leibe

Dilation: A sneak peak preview

- Dilate the regions of „white“ pixels
- Increases the size of the structures
- Fills holes in regions



Before dilation



After dilation

Erosion: A sneak peak preview

- Erode the regions of „white“ pixels
- Reduce the size of structures
- Remove bridges, branches, noise

Before erosion



After erosion

Central to morphology: Structuring element (SE)

- Can be any shape and content:



- Fit: All “1” pixels in SE cover “1” pixels in the image.
- Hit: Any “1” pixels in SE cover “1” pixels in the image.



Image curtesy: Brian Mac Namee

Fitting & Hitting

0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	1	1	0	0	0	0	0	0	0
0	0	1	B	1	1	1	0	C	1	0	0
0	1	1	1	1	1	1	1	0	0	0	0
0	1	1	1	1	1	1	1	0	0	0	0
0	0	1	1	1	1	1	1	0	0	0	0
0	0	1	1	1	1	1	1	1	0	0	0
0	0	1	1	1	1	1	A	1	1	1	0
0	0	0	0	0	1	1	1	1	1	1	0
0	0	0	0	0	0	0	0	0	0	0	0

0	1	0
1	1	1
0	1	0

Structuring Element

Fit / Hit?

A:

B:

C:

Fit : All “1” elements in SE are 1

Hit: Any “1” element in SE is 1

Erosion

- Erosion of image f by structuring element s is given by $g = f \ominus s$.
- The structuring element s is positioned with its origin at (x, y) and the new pixel value is determined using the rule:

$$g(x,y) = \begin{cases} 1 \text{ if } s \text{ fits } f \\ 0 \text{ otherwise} \end{cases}$$

s

0	1	0
1	1	1
0	1	0

SE placed on image at (2,2)

	0	1	2	3	4	5	6 …
0	0	0	0	0	0	0	0
1	0	0	0	1	1	0	0
2	0	0	1	1	1	1	0
3	0	1	1	1	1	1	1
4	0	1	1	1	1	1	1
5	0	0	1	1	1	1	1
…							

Fit: All “1” pixels in SE cover “1” pixels in the image.

Erosion Example



Fit :All 1 in SE covered in image

Processed Image With Eroded Pixels





Structuring Element

Erosion Example

Original Image



Processed Image With Eroded Pixels





Structuring Element

Fit :All 1 in SE covered in image

Dilation

- Dilation of image f by structuring element s is given by $g = f \oplus s$.
- The structuring element s is positioned with its origin at (x, y) and the new pixel value is determined using the rule:

$$g(x,y) = \begin{cases} 1 \text{ if } s \text{ hits } f \\ 0 \text{ otherwise} \end{cases}$$

s

0	1	0
1	1	1
0	1	0

SE placed on image at (2,2)

	0	1	2	3	4	5	6 …
0	0	0	0	0	0	0	0
1	0	0	0	1	1	0	0
2	0	0	1	1	1	1	0
3	0	1	1	1	1	1	1
4	0	1	1	1	1	1	1
5	0	0	1	1	1	1	1
…							

Hit: Any “1” pixels in SE cover “1” pixels in the image.

Dilation Example



Hit: Any 1 in SE covered in image

Dilation Example







Structuring Element

Hit: Any 1 in SE covered in image

Effects of erosion and dilation



Original



Dilation by a round structuring element.



Erosion by a round structuring element.

Source of images: http://homepages.inf.ed.ac.uk/rbf/HIPR2/

Combined operations: Opening

- Definition
  - Apply erosion then dilation

$$A \circ B = (A \ominus B) \oplus B$$



- Effect:

  ⇒ Removes small objects,
  preserves rough shape.

Image Source: R.C. Gonzales & R.E. Woods

Effects of opening

- Can filter out structures by selecting the size of structuring element.



Original



Thresholded



Opening by a small structuring element



Opening by a large structuring element

Source of images: http://homepages.inf.ed.ac.uk/rbf/HIPR2/

Effects of opening

- Choose the structure in image by choosing the shape of the structuring element.



Original image



Opening by a round structuring element

Source of images: http://homepages.inf.ed.ac.uk/rbf/HIPR2/

Combined operations: Closing

- Definition
  - Apply dilation then erosion

$$A \cdot B = (A \oplus B) \ominus B$$



- Effect

  ⇒ Fill holes, preserves the original shape.

Effects of closing

- Fill holes in thresholded image

  (*eg., reflections*)

Original



Thresholded



Closing by a round structuring element

The size of structuring element determines the maximal size of holes that will be filled.





Example: opening + closing

Image Source: R.C. Gonzales & R.E. Woods

Morphological operators in Matlab

- Main operations
  - Dilation (Matlab: `imdilate`)
  - Erosion (Matlab: `imerode`)
- Several important combinations
  - Opening (Matlab: `imopen`)
  - Closing (Matlab: `imclose`)
  - Boundary extraction
- Much more available (see help)



Examples of structuring elements:



Matlab:
>> help strel

Machine perception

LABELLING REGIONS



Connected components for labeling

- Goal: find separate connected regions



1	1	0	1	1	1	0	1
1	1	0	1	0	1	0	1
1	1	1	1	0	0	0	1
0	0	0	0	0	0	0	1
1	1	1	1	0	1	0	1
0	0	0	1	0	1	0	1
1	1	0	1	0	0	0	1
1	1	0	1	0	1	1	1

Binary image

1	1	0	1	1	1	0	2
1	1	0	1	0	1	0	2
1	1	1	1	0	0	0	2
0	0	0	0	0	0	0	2
3	3	3	3	0	4	0	2
0	0	0	3	0	4	0	2
5	5	0	3	0	0	0	2
5	5	0	3	0	2	2	2

connected components



Examples of connected components



connected components of 1's from thresholded image



connected components of cluster labels

Source: Pinar Duygulu

Connectivity

- Determines which pixels are considered neighbors.



4-neighborhood

8-neighborhood

Source: Chaitanya Chandra

Sequential connected components

- Process image from left to right, from top to bottom:

  1.) If the current pixel value is 1

  i.) If only one neighbor (left or top) is 1, copy its label.

  ii.) If both neighbors are 1 and have same label, copy that label.

  iii.) If they have different labels

  – Copy label from the left.

  – Update the table of equivalent labels.



  iv.) Otherwise form a new label.

- Relabel with the smallest equivalent labels.



{1, 2, 7}
{3}
{4}
{5, 6, 8}

Example SCC: 8-connectivity

(a)

0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	1	1	0	0	1	1	0	1	0
0	1	1	1	1	1	1	0	0	1	0	0	1	0
0	0	0	0	1	0	1	0	0	0	0	0	1	0
0	1	1	1	1	1	1	1	1	1	1	1	1	0
0	0	0	0	1	1	1	1	1	1	1	1	1	0
0	1	1	0	0	0	1	0	1	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0	0

0 Background

1 Foreground

(b) only background neighbors

0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	1	1	0	0	1	1	0	1	0
0	1	1	1	1	1	1	0	0	1	0	0	1	0
0	0	0	0	1	0	1	0	0	0	0	0	1	0
0	1	1	1	1	1	1	1	1	1	1	1	1	0
0	0	0	0	1	1	1	1	1	1	1	1	1	0
0	1	1	0	0	0	1	0	1	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0	0

new label (**2**)

0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	2	1	0	0	1	1	0	1	0
0	1	1	1	1	1	1	0	0	1	0	0	1	0
0	0	0	0	1	0	1	0	0	0	0	0	1	0
0	1	1	1	1	1	1	1	1	1	1	1	1	0
0	0	0	0	1	1	1	1	1	1	1	1	1	0
0	1	1	0	0	0	1	0	1	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0	0

Example SCC: 8-connectivity

(c) exactly one neighbor label

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	2	1	0	0	1	1	0	1	0	
0	1	1	1	1	1	1	0	0	1	0	0	1	0	
0	0	0	0	1	0	1	0	0	0	0	0	1	0	
0	1	1	1	1	1	1	1	1	1	1	1	1	0	
0	0	0	0	1	1	1	1	1	1	1	1	1	0	
0	1	1	0	0	0	1	0	1	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	

neighbor label is propagated

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	2	2	0	0	1	1	0	1	0	
0	1	1	1	1	1	1	0	0	1	0	0	1	0	
0	0	0	0	1	0	1	0	0	0	0	0	1	0	
0	1	1	1	1	1	1	1	1	1	1	1	1	0	
0	0	0	0	1	1	1	1	1	1	1	1	1	0	
0	1	1	0	0	0	1	0	1	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	

(d) two different neighbor labels

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	2	2	0	0	3	3	0	4	0	
0	5	5	5	1	1	1	0	0	1	0	0	1	0	
0	0	0	0	1	0	1	0	0	0	0	0	1	0	
0	1	1	1	1	1	1	1	1	1	1	1	1	0	
0	0	0	0	1	1	1	1	1	1	1	1	1	0	
0	1	1	0	0	0	1	0	1	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	

one of the labels (**2**) is propagated
(Update equivalency table {2,5})

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	2	2	0	0	3	3	0	4	0	
0	5	5	5	2	1	1	0	0	1	0	0	1	0	
0	0	0	0	1	0	1	0	0	0	0	0	1	0	
0	1	1	1	1	1	1	1	1	1	1	1	1	0	
0	0	0	0	1	1	1	1	1	1	1	1	1	0	
0	1	1	0	0	0	1	0	1	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	

Example SCC: 8-connectivity

First pass: label

0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	2	2	0	0	3	3	0	4	0
0	5	5	5	2	2	2	0	0	3	0	0	4	0
0	0	0	0	2	0	2	0	0	0	0	0	4	0
0	6	6	2	2	2	2	2	2	2	2	2	2	0
0	0	0	0	2	2	2	2	2	2	2	2	2	0
0	7	7	0	0	0	2	0	2	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0	0

Equivalency table



Second pass: apply equivalences

0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	2	2	0	0	3	3	0	2	0
0	2	2	2	2	2	2	0	0	3	0	0	2	0
0	0	0	0	2	0	2	0	0	0	0	0	2	0
0	2	2	2	2	2	2	2	2	2	2	2	2	0
0	0	0	0	2	2	2	2	2	2	2	2	2	0
0	7	7	0	0	0	2	0	2	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0	0	0	0



Machine perception

REGION DESCRIPTORS

Simple region descriptors

- A region can be detected using the connected components.
- How to describe it?
- Some examples:
  - Area A
  - Perimeter l
  - Compactness $c=l^2/(4\pi A)$
  - Circularity, roundness $1/c$
  - Centroid (center of mass)
  - Major and minor axes λ_1, λ_2
  - Eccentricity $||\lambda_1||/||\lambda_2||$
  - Minimal bounding box area $A_m = h\,b$
  - Rectangularity A/A_m

Matlab: *regionprops*





(Easy to come up with your own)

Require a level of invariance (App dependent)

- We seek a descriptor that maps:
  - Two images of the same object close-by in feature space.
  - Two images of different objects to points far between each other.



Task: Detect round cells





Classify each region







Summary: Binarization

- Pros
  - Fast, simple to store
  - Simple techniques
  - Works in constrained setups
- Cons
  - Difficult to get „clean“ shapes
  - Many real-world scenarios contain noise
  - Often too coarse representation
  - Not robust in changes of 3D view changes

Try and play with this at home:

- Task: “Automatically select only one of the coins”
  - Threshold, clean by morphology, find connected components, select a single connected component, overlay the input image with the selection.



Matlab code…

- a = imread('coins.jpg') ;
- figure(1) ; clf ; imagesc(a);
- a = rgb2gray(a) ;
- figure(1) ; clf ; imagesc(a); colormap gray ;
- I = a < 200 ; figure(1) ; clf ; imagesc(I); colormap gray ;
- se = strel('disk',4) ;
- I2 = imclose(I,se) ; figure(1) ; clf ; imagesc(I2); colormap gray ;
- [I3,num] = bwlabel(I2);
- figure(2); clf ; imagesc(I3)
- figure(3); clf ; imagesc(I3==1)
- a2= double(a).*double(I3==1) ;
- figure(4); clf ; imagesc(a2)

References

- R.C. Gonzales, R.E. Woods, *Digital Image Processing*. Prentice Hall, 2001
- Morfology – Spletni tutorial: http://homepages.inf.ed.ac.uk/rbf/HIPR2/
- David A. Forsyth, Jean Ponce, Computer Vision: A Modern Approach (2nd Edition), (prva izdaja dostopna na spletu)
- R. Szeliski,Computer Vision: Algorithms and Applications, 2010
- R. Hartley, A. Zisserman, Multiple View Geometry in Computer Vision, 2nd Edition, Cambridge University Press, 2004
- Rob Fegus, „Computer Vision“, lectures
- Bastian Leibe „Computer Vision“, lectures
- Kristen Grauman „Computer Vision“, Lectures
- Otsu, N., "A Threshold Selection Method from Gray-Level Histograms," *IEEE Transactions on Systems, Man, and Cybernetics*, Vol. 9, No. 1, 1979, pp. 62-66.