

# CUDA Implementation of Position Based Fluids

CSC417 Course Project

Qingyuan Qie, Changlin Su

Department of Computer Science  
University of Toronto

December 20, 2021

# Enforcing incompressibility

---

For particle  $i$  at position  $p_i$ , we compute the density of the fluid around particle  $i$  using the estimator:

$$\rho_{F(i)} = \sum_{j \in F(i)} m_j W_{poly6}(\mathbf{p}_i - \mathbf{p}_j, h)$$

# Enforcing incompressibility

---

For particle  $i$  at position  $\mathbf{p}_i$ , we compute the density of the fluid around particle  $i$  using the estimator:

$$\rho_i = \sum_{j \in F(i)} m_j W_{poly6}(\mathbf{p}_i - \mathbf{p}_j, h)$$

Then we have the constant density constraint:

$$C_i(\mathbf{p}) = \frac{\rho_i}{\rho_0} - 1$$

# Enforcing incompressibility

---

For particle  $i$  at position  $\mathbf{p}_i$ , we compute the density of the fluid around particle  $i$  using the estimator:

$$\rho_i = \sum_{j \in F(i)} m_j W_{poly6}(\mathbf{p}_i - \mathbf{p}_j, h)$$

Then we have the constant density constraint:

$$C_i(\mathbf{p}) = \frac{\rho_i}{\rho_0} - 1$$

And we want to compute a position correction  $\Delta\mathbf{p}$ , such that:

$$C(\mathbf{p} + \Delta\mathbf{p}) = 0$$

# Position Update from Solving Incompressibility

---

For particle  $i$  at position  $\mathbf{p}_i$ , we have,

$$\lambda_i = -\frac{C_i(\mathbf{p})}{\sum_k |\nabla_{\mathbf{p}_k} C_i|^2}$$

# Position Update from Solving Incompressibility

---

For particle  $i$  at position  $\mathbf{p}_i$ , we have,

$$\lambda_i = -\frac{C_i(\mathbf{p})}{\sum_k |\nabla_{\mathbf{p}_k} C_i|^2}$$

Then the position correction  $\Delta\mathbf{p}_i$  including affect from neighboring particles is,

$$\Delta\mathbf{p}_i = \frac{1}{\rho_0} \sum_j (\lambda_i + \lambda_j) \nabla W(\mathbf{p}_i - \mathbf{p}_j, h)$$

# Position Update from Solving Incompressibility

---

For particle  $i$  at position  $\mathbf{p}_i$ , we have,

$$\lambda_i = -\frac{C_i(\mathbf{p})}{\sum_k |\nabla_{\mathbf{p}_k} C_i|^2}$$

Then the position correction  $\Delta\mathbf{p}_i$  including affect from neighboring particles is,

$$\Delta\mathbf{p}_i = \frac{1}{\rho_0} \sum_j (\lambda_i + \lambda_j) \nabla W(\mathbf{p}_i - \mathbf{p}_j, h)$$

And the position update is,

$$\mathbf{p}_i^* = \mathbf{p}_i + \Delta\mathbf{p}_i$$

# Simulation Step

---

---

**Algorithm 1** simulation step

---

```
1: for all particles  $i$  do:                                ▶ Fluid advection
2:   apply forces  $\mathbf{v}_i = \mathbf{v}_i + \Delta t \mathbf{f}_{ext}$ 
3:   predict position  $\mathbf{x}_i^* = \mathbf{x}_i + \Delta t \mathbf{v}_i$ 
4: end for
5: for all particles  $i$  do:
6:   find neighboring particles  $F(\mathbf{x}_i^*)$ 
7: end for
8: while  $iter < solverIterations$  do:                    ▶ Iteratively solves
   incompressibility constraints
9:   for all particles  $i$  do:
10:    calculate  $\lambda_i$ 
11:   end for
12:   for all particles  $i$  do:
13:    calculate  $\Delta \mathbf{p}_i$ 
14:    perform collision detection and response
15:   end for
16:   for all particles  $i$  do:
17:    update position  $\mathbf{x}_i^* = \mathbf{x}_i^* + \Delta \mathbf{p}_i$ 
18:   end for
19: end while
20: for all particles  $i$  do:
21:   update velocity  $\mathbf{v}_i = \frac{1}{\Delta t} (\mathbf{x}_i^* - \mathbf{x}_i)$ 
22:   apply viscosity
23:   update position  $\mathbf{x}_i = \mathbf{x}_i^*$ 
24: end for
```

---



# Performance of Implementation




Figure: Performance Comparison between CPU and GPU, 2k particles

# Performance of CUDA Implementation

---

Particle Count	Time per Frame	Frame per Second(fps)
2k	0.006s	166fps
12k	0.01s	100fps
27k	0.021s	47.6fps
80k	0.064	15.6fps