Transformer-based Symbolic Music Generation

Independent Undergraduate Research Project
Python / PyTorch / MIDI / MidiTok / music21

422 MIDI arrangements | ~40M parameters | Four representation variants

I independently developed a symbolic music generation system to explore whether a Transformer trained on a small Touhou corpus could learn recognisable musical patterns, and whether changing the event representation would improve its outputs. The project grew from building a working generator into an investigation of musical position, harmonic annotation and the limits of automatic evaluation.

GitHub: Archmagos-Lama/text-to-midi-transformer

STARTING POINT

My practical goal was to generate music with some of the character of the source material. I was particularly interested in how a motif can return in a different register or harmonic setting while retaining internal movement: changes in note length, pauses and melodic direction. Matching the instruments or repeating a plausible accompaniment pattern would only address part of that goal.

I chose MIDI because it makes notes, timing and instruments accessible as discrete events. It also allows generated material to be inspected in a piano roll or replayed with different soundfonts. The model generates symbolic events; the final sound still depends on the playback instrument and synthesizer.

SCOPE OF THE INVESTIGATION

The experiments asked three related questions: how closely a small-corpus model could match reference music statistics; how explicit bar indices changed those distributions; and how harmonic-role annotations affected learning and generation. I kept the Transformer architecture broadly fixed while exploring these representation choices.

The resulting system supports both generation from a beginning-of-sequence token and continuation from a MIDI prompt. The quantitative comparison used unconditional samples. Prompt continuation remained a practical exploration rather than a separately validated experimental claim.

WORK COMPLETED INDEPENDENTLY

I prepared the data pipeline, implemented the PyTorch model and generation code, ran training and evaluation, and developed the BARPOS and HarmRole variants. MidiTok supplied the underlying REMI tokenizer, while music21 supplied tools for harmonic analysis. I also organised the scripts, saved model checkpoints and inspected generated outputs to identify where the measured results differed from the musical experience.

Building the Pipeline

From MIDI arrangements to an autoregressive event model

DATA AND EVENT REPRESENTATION

The corpus contained 422 Touhou MIDI arrangements. Training and validation material were prepared separately, with pitch-transposition augmentation used to expand the training examples. Transposition gives the model examples in different registers and keys, but does not provide new compositions or new large-scale forms.

I used REMI to encode bar boundaries, positions within bars, pitches, velocities, durations, tempo and instrument programs. Beginning- and end-of-sequence markers were added around pieces. The pipeline saved token tensors, tokenizer definitions and metadata so that training and MIDI reconstruction used the same event vocabulary.

TRANSFORMER IMPLEMENTATION AND TRAINING

The decoder-only Transformer used eight layers, eight attention heads and a 640-dimensional embedding, for approximately 40 million parameters. Learned position embeddings represented token positions within a 1,536-token context. The model learned next-token prediction with causal self-attention and cross-entropy loss.

The training configuration used a batch size of 12 and eight gradient-accumulation steps. Validation was evaluated every 500 iterations, and the training scripts saved both recent and best-validation checkpoints. I used the best checkpoint for sample generation rather than automatically selecting the final training step.

HarmRole v1 reached its recorded best validation loss at iteration 2,500; v2 reached its best at iteration 2,000. These observations describe the behaviour of those runs. They do not by themselves identify whether corpus size, optimisation, representation or model capacity caused the subsequent lack of improvement.

TESTING BAR-POSITION INFORMATION

Standard REMI uses the same Bar_None marker at every bar boundary. I replaced this marker with BARPOS_k, where k is the bar count modulo 128. This introduces an explicit cyclic bar index without requiring manual phrase or section annotations.

The baseline retained the same 741-entry vocabulary while continuing to use Bar_None. This made the baseline/BARPOS comparison more controlled than the harmonic-role comparisons. During generation, BARPOS tokens were predicted as part of the sequence and mapped back to Bar_None before MIDI decoding.

The hypothesis was that bar indices could help the model learn position-dependent patterns. They do not directly specify a phrase boundary, theme or section transition. I therefore assessed their effect through the available feature distributions, without treating the encoding as proof of learned musical form.

The HarmRole Experiment

An annotation idea, an unexpected distribution, and a revised representation

MAKING HARMONY EXPLICIT

After hearing repetitive or poorly organised samples, I explored whether explicit harmonic information could help. The first HarmRole version estimated a chord for each bar and placed a role label immediately after each pitch: root, third, fifth, seventh or non. These labels described the relation between a note and the estimated harmony.

Because the role followed the pitch, it was an auxiliary event in the autoregressive sequence. It did not force the preceding pitch to satisfy a chord rule. At generation time the model predicted its own labels, which remained in its context but were removed before MIDI decoding. Self-generated labels are therefore not an independent measure of harmonic correctness.

KEEPING PREPROCESSING PRACTICAL

Running harmonic analysis separately on every augmented MIDI would repeat much of the same work. I instead analysed the original files with music21, cached the bar-level chord maps, and shifted their pitch classes for each transposed version. Cache persistence also allowed analysis results to be reused after an interrupted run.

For the HarmRole variants, I disabled MidiTok chord extraction while retaining the separately computed role labels. This reduced duplicate preprocessing, but also changed the representation: the vocabulary became 578 entries for v1 and 579 for v2, compared with 741 for baseline and BARPOS. HarmRole also lengthened the sequence, reducing how much musical time fitted within the same token context.

WHAT THE LABELS REVEALED

Counting the training labels showed that **73.8% were non**. Root, third, fifth and seventh together accounted for the remaining 26.2%. The large residual category made the annotation worth investigating before interpreting the generation results.

A bar-level chord is a coarse description of music that can contain passing notes, ornaments and changing harmony within a bar. Chord-recognition error, alignment and transposition mapping can also affect these assignments. The count establishes what the pipeline labelled; it does not establish that 73.8% of the source music is musically inappropriate or explain the generation outcome on its own.

REVISION AND OUTCOME

In v2 I split non into scale and chromatic using the estimated key: 36.4% of training labels became scale and 37.4% became chromatic. This distinction is based on an automatically estimated major or minor scale, rather than a manually verified account of local modulation and modal harmony.

Version 2 achieved a lower raw validation loss than v1, 1.4375 versus 1.5050, while the musical statistics remained mixed. Changing the labels changes the prediction task, so this loss difference cannot independently demonstrate better music generation. The useful finding was the need to inspect how an annotation represents the domain before treating it as informative conditioning.

Results in Context

Measured distributions, generated examples and the remaining musical gap

QUANTITATIVE COMPARISON

I generated 50 samples per variant and compared eight features with reference MIDI: pitch-class entropy, pitch range, note density, average pitch, pitch standard deviation, average duration, rhythmic entropy and polyphony. The evaluator compared feature histograms using Jensen-Shannon distance.

BARPOS matched the reference more closely than baseline on some features, but did not outperform it consistently. HarmRole v1 and v2 also showed improvements on some measurements and regressions on others. These are descriptive results from the available runs, without a demonstrated statistically significant advantage.




Figure 1. BARPOS-generated MIDI versus reference feature distributions. Blue indicates reference samples and orange indicates generated samples. The original figure labels the histogram comparison as JS; the evaluation code returns Jensen-Shannon distance.

WHAT THE SAMPLES SOUNDED LIKE

Informal listening exposed a gap between plausible local patterns and coherent musical development. Outputs could imitate a rhythmic texture, instrument setting or chord pattern while repeating similar durations for too long. Motifs often lacked the internal rises, pauses and changes of pace that motivated the project.

I also tested continuation using the first 600 tokens of an existing MIDI as a prompt. The generated extensions did not reliably preserve the organisation of the source. This was an exploratory use case, not a formal listening study or evidence that continuation was better than unconditional generation.

WHAT THIS PROJECT ESTABLISHES

The project demonstrates an end-to-end implementation and a tested set of representation changes. It provides evidence that those changes affect generated statistics, and documents a harmonic-annotation refinement that did not yield consistent measured gains. The evaluation does not establish improved long-range structure or overall musical quality.

The limited corpus, absence of repeated training runs and representation differences restrict causal conclusions. A small piano-roll case analysis would be a practical next step for examining motif recurrence and rhythmic repetition in particular samples. No such case analysis is presented here as a completed experiment.