

EK-1: KAYNAKLAR

- Agarwal, A., et al. (2014). Taming the monster: A fast and simple algorithm for contextual bandits. *ICML*, 1638–1646.
- Cenikj, G., Strojnik, L., Angelski, R., Ogrinc, N., Koroušić Seljak, B., & Eftimov, T. (2023). From language models to large-scale food and biomedical knowledge graphs. *Scientific Reports*, 13, 7815. <https://doi.org/10.1038/s41598-023-34981-4>
- Chapelle, O., & Li, L. (2011). An empirical evaluation of Thompson sampling. *NeurIPS*, 24.
- Chen, L., et al. (2023). FrugalGPT: How to use large language models while reducing cost and improving performance. *arXiv:2305.05176*. <https://doi.org/10.48550/arXiv.2305.05176>
- Chen, M., Xu, Z., Weinberger, K. Q., Chapelle, O., & Kedem, D. (2012). Classifier cascade for minimizing feature evaluation cost. *AISTATS (PMLR)*, 218–226. <https://proceedings.mlr.press/v22/chen12c.html>
- Dagdelen, J., Dunn, A., Lee, S., Walker, N., Rosen, A. S., Ceder, G., Persson, K. A., & Jain, A. (2024). Structured information extraction from scientific text with large language models. *Nature Communications*, 15, 1418. <https://doi.org/10.1038/s41467-024-45563-x>
- Dettmers, T., et al. (2023). QLoRA: Efficient finetuning of quantized language models. *NeurIPS*, 36. <https://doi.org/10.48550/arXiv.2305.14314>
- Dooley, D.M., et al. (2018). FoodOn: A harmonized food ontology to increase global food traceability. *npj Science of Food*, 2(1), 1-10. <https://doi.org/10.1038/s41538-018-0032-6>
- EFSA (2015). The food classification and description system FoodEx2 (revision 2). *EFSA Supporting Publications*, 12(5), EN-804. <https://doi.org/10.2903/sp.efsa.2015.EN-804>
- Efron, B., & Tibshirani, R.J. (1993). *An Introduction to the Bootstrap*. Chapman & Hall/CRC. <https://doi.org/10.1201/9780429246593>
- EuroFIR AISBL. (2024). *European Food Information Resource (EuroFIR) food composition platform*. <https://www.eurofir.org>
- European Parliament and Council. (2011). *Regulation (EU) No 1169/2011 on the provision of food information to consumers*. EUR-Lex. <https://eur-lex.europa.eu/eli/reg/2011/1169/oj>
- FAO/INFOODS (2012). *FAO/INFOODS Guidelines for Food Matching*. Rome: FAO.
- Fedus, W., et al. (2022). Switch Transformers: Scaling to trillion parameter models. *JMLR*, 23(120), 1–39.
- Greenfield, H., & Southgate, D.A.T. (2003). *Food Composition Data: Production, Management and Use* (2nd ed.). Rome: FAO.
- Hestness, J., et al. (2017). Deep learning scaling is predictable, empirically. *arXiv:1712.00409*. <https://doi.org/10.48550/arXiv.1712.00409>
- Hooton, F., Menichetti, G., & Barabási, A.-L. (2020). Exploring food contents in scientific literature with FoodMine. *Scientific Reports*, 10, 16191. <https://doi.org/10.1038/s41598-020-73105-0>
- Hu, E.J., et al. (2022). LoRA: Low-rank adaptation of large language models. *ICLR*. <https://doi.org/10.48550/arXiv.2106.09685>
- Ispirova, G., Eftimov, T., & Koroušić Seljak, B. (2020). P-NUT: Predicting NUTrient content from short text descriptions. *Mathematics*, 8(10), 1811. <https://doi.org/10.3390/math8101811>
- Jankelow, A., Godneva, A., Rein, M., Samocha-Bonet, D., Weissglas-Volkov, D., Zohar, S., Shor, T., & Segal, E. (2026). NutriMatch: harmonizing food composition databases with large language models for enhanced nutritional prediction. *npj Digital Public Health*, 1, 1. <https://doi.org/10.1038/s44482-025-00001-7>
- Klensin, J.C., et al. (1989). *Identification of Food Components for INFOODS Data Interchange*. Tokyo: UNU Press.
- Lattimore, T., & Szepesvári, C. (2020). *Bandit Algorithms*. Cambridge University Press. <https://doi.org/10.1017/9781108571401>
- Lewis, P., et al. (2020). Retrieval-augmented generation for knowledge-intensive NLP tasks. *NeurIPS*, 33, 9459–9474. <https://doi.org/10.48550/arXiv.2005.11401>
- Li, L., et al. (2010). A contextual-bandit approach to personalized news article recommendation. *WWW*, 661–670. <https://doi.org/10.1145/1772690.1772758>
- Lin, T.-Y., et al. (2017). Focal loss for dense object detection. *ICCV*, 2980–2988. <https://doi.org/10.1109/ICCV.2017.324>
- MarketsandMarkets. (2025). *Personalized Nutrition Market — Global Forecast to 2030*. <https://www.marketsandmarkets.com/PressReleases/personalized-nutrition.asp>
- McHugh, M.L. (2012). Interrater reliability: The kappa statistic. *Biochemia Medica*, 22(3), 276-282. <https://doi.org/10.11613/BM.2012.031>
- Monarch, R.M. (2021). *Human-in-the-Loop Machine Learning*. Manning Publications.
- Møller, A., et al. (2008). LanguaL 2006 – the LanguaL thesaurus. *European Journal of Clinical Nutrition*, 62, S272–S275. <https://doi.org/10.1038/ejcn.2008.50>
- Mordor Intelligence. (2025). *Diet and Nutrition Apps Market — Size, Share & Growth Trends*. <https://www.mordorintelligence.com/industry-reports/diet-and-nutrition-apps-market>
- Ouyang, L., et al. (2022). Training language models to follow instructions with human feedback. *NeurIPS*, 35, 27730–

27744. <https://doi.org/10.48550/arXiv.2203.02155>

- Sanh, V., et al. (2019). DistilBERT: Smaller, faster, cheaper and lighter. *arXiv:1910.01108*. <https://doi.org/10.48550/arXiv.1910.01108>
- Schakel, S.F., Sievert, Y.A., & Buzzard, I.M. (1988). Sources of data for developing and maintaining a nutrient database. *Journal of the American Dietetic Association*, 88(10), 1268–1271. [https://doi.org/10.1016/S0002-8223\(21\)07997-9](https://doi.org/10.1016/S0002-8223(21)07997-9)
- Semantic Scholar. (2026). *Semantic Scholar Academic Graph API*. <https://www.semanticscholar.org/product/api>
- Settles, B. (2012). *Active Learning*. Morgan & Claypool Publishers. <https://doi.org/10.2200/S00429ED1V01Y201207AIM018>
- Seung, H.S., et al. (1992). Query by committee. *COLT*, 287–294. <https://doi.org/10.1145/130385.130417>
- Shazeer, N., et al. (2017). Outrageously large neural networks: The sparsely-gated MoE layer. *ICLR*. <https://doi.org/10.48550/arXiv.1701.06538>
- Shrout, P.E., & Fleiss, J.L. (1979). Intraclass correlations: Uses in assessing rater reliability. *Psychological Bulletin*, 86(2), 420–428. <https://doi.org/10.1037/0033-2909.86.2.420>
- Smock, B., et al. (2022). PubTables-1M: Towards comprehensive table extraction. *CVPR*, 4634–4642. <https://doi.org/10.1109/CVPR52688.2022.00459>
- Turc, I., et al. (2019). Well-read students learn better: On the importance of pre-training compact models. *arXiv:1908.08962*. <https://doi.org/10.48550/arXiv.1908.08962>
- TÜBİTAK MAM Gıda Enstitüsü (2014). *Türkiye'nin Ulusal Gıda Kompozisyon Veri Tabanı (TürKomp)*. TÜBİTAK Marmara Araştırma Merkezi. <https://mam.tubitak.gov.tr/turkiyenin-ulusal-gida-kompozisyon-veri-tabani/>
- TÜBİTAK ULAKBİM. (2026). *TRUBA Başvuru ve yüksek başarımlı hesaplama altyapısı*. <https://www.truba.gov.tr/>
- Viola, P., & Jones, M. (2001). Rapid object detection using a boosted cascade. *CVPR*, 1, 511–518. <https://doi.org/10.1109/CVPR.2001.990517>
- Youn, J., Li, F., Simmons, G., Kim, S., & Tagkopoulos, I. (2024). FoodAtlas: Automated knowledge extraction of food and chemicals from literature. *Computers in Biology and Medicine*, 109072. <https://doi.org/10.1016/j.compbiomed.2024.109072>
- Yue, M., et al. (2024). Large language model cascades with mixture of thought representations for cost-efficient reasoning. *ICLR*. <https://doi.org/10.48550/arXiv.2310.03094>