



ArcCorp Backend API Documentation

Base URL (Production)

arduino

CopyEdit

<https://arccorpbrowserprodtrack-production.up.railway.app/api/>



Authentication Flow

Your login system uses a 2-step verification with email codes:

- 1 Client calls `/users/login?email=<email>` → API sends verification code to the provided email.
 - 2 Client calls `/users/login?email=<email>&code=<code>` → API returns JWT on successful code verification.
-

◆ GET `/users/login`

→ Send Verification Code

Endpoint:

pgsql

CopyEdit

GET `/users/login?email=<user_email>`

Description:

- Starts the login process by generating and emailing a verification code.
- If user exists: generates a new code.
- If not: creates a pending user with code.

Query Parameters:

Name	Type	Required	Description
email	string	Yes	User email address.

Response 200 OK:

```

json
CopyEdit
{
  "jwtAuthKey": null,
  "sucessful": true,
  "message": "Verification code sent to aakgur@gmail.com. If you don't see the email, please check your spam or junk folder."
}

```

→ Validate Code & Retrieve JWT

Endpoint:

```

php-template
CopyEdit
GET /users/login?email=<user_email>&code=<verification_code>

```

Description:

- Verifies code for email.
- Returns JWT if correct.

Query Parameters:

Name	Type	Required	Description
email	string	Yes	User email address.
code	string	Yes	Verification code from email.

Response 200 OK (success):

json

CopyEdit

```
{
  "jwtAuthKey": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "sucessful": true,
  "message": "Login successful"
}
```

Response 401 Unauthorized (wrong code):

json

CopyEdit

```
{
  "jwtAuthKey": null,
  "sucessful": false,
  "message": "Invalid code"
}
```

◆ GET /users/test_online

Endpoint:

bash

CopyEdit

```
GET /users/test_online
```

Description:

- Health check endpoint; verifies the backend is running.

Response 200 OK:

json

CopyEdit

```
"foobar"
```



Common Response Fields

Field	Type	Description
jwtAuthKey	string	JWT token (null if not yet logged in)
sucessful	boolean	Indicates operation success
message	string	Detailed message for the client



Example Login Sequence

1 Call:

```
sql
CopyEdit
GET /users/login?email=aakgur@gmail.com
```

→ Server emails a verification code.

2 Call:

```
sql
CopyEdit
GET /users/login?email=aakgur@gmail.com&code=1234
```

→ If correct, you get your JWT in the response.

3 Include the JWT in future requests as:

```
makefile
CopyEdit
Authorization: Bearer <jwtAuthKey>
```



Status Codes

- **200 OK** — Success (codes sent, validated, or test).

- **400 Bad Request** — Missing parameters.
 - **401 Unauthorized** — Invalid verification code.
 - **500 Internal Server Error** — Unexpected server issue.
-

Security

- ✓ **HTTPS** is enforced via Railway's default SSL certificates.
 - ✓ **JWTs** are signed server-side and expire based on your AuthService settings.
-

Contact

For support with ArcCorp API, email arccorpinfo@gmail.com.