

Document Number: DXXX

Date: 2014-10-08

Revises: [N4040](#)

Editor: Andrew Sutton
University of Akron
asutton@uakron.edu

Working Draft, C++ Extensions for Concepts

Note: this is an early draft. It's known to be incomplet and incorrekt, and it has lots of bad formatting.

Contents

1	General	4
1.1	Scope	4
1.2	Normative references	4
1.3	Implementation compliance	4
1.4	Acknowledgments	4
2	Lexical conventions	5
2.1	Keywords	5
5	Expressions	6
5.1	Primary expressions	6
5.1.2	Lambda expressions	6
5.1.3	Requires expressions	6
5.1.3.1	Simple requirements	7
5.1.3.2	Type requirements	8
5.1.3.3	Compound requirements	8
5.1.3.4	Nested requirements	9
7	Declarations	10
7.1	Specifiers	10
7.1.6	Type specifiers	10
7.1.6.2	Simple type specifiers	10
7.1.6.4	auto specifier	10
7.1.6.5	Constrained type specifiers	12
7.1.7	concept specifier	15
8	Declarators	17
8.3	Meaning of declarators	17
8.3.5	Functions	17
8.4	Function definitions	19
8.4.1	In general	19
9	Classes	20
9.2	Class members	20
10	Derived classes	21
10.3	Virtual functions	21
13	Overloading	22
13.2	Declaration matching	22
13.3	Overload resolution	22
13.3.1	Viable functions	22
13.3.2	Best viable function	22
13.4	Address of overloaded function	23
14	Templates	24
14.1	Template parameters	26
14.2	Introduction of template parameters	28
14.3	Names of template specializations	29
14.4	Template arguments	30
14.4.1	Template template arguments	30
14.5	Template declarations	30
14.5.1	Class templates	30
14.5.1.1	Member functions of class templates	31
14.5.2	Member templates	31
14.5.4	Friends	32
14.5.5	Class template partial specialization	32
14.5.5.1	Matching of class template partial specializations	33
14.5.5.2	Partial ordering of class template specializations	33
14.5.6	Function templates	34
14.5.6.1	Function template overloading	34
14.5.6.2	Partial ordering of function templates	34

14.5.7	Alias templates	34
14.7	Template instantiation and specialization	35
14.7.1	Implicit instantiation	35
14.7.2	Explicit instantiation	35
14.7.3	Explicit specialization	36
14.8	Function template specializations	36
14.8.2	Template argument deduction	36
14.9	Template constraints	37
14.9.1	Constraint expressions	37
14.9.2	Constraint language	38
14.9.2.1	Conjunction	38
14.9.2.2	Disjunction	39
14.9.2.3	Atomic constraints	39
14.9.2.4	Predicate constraints	39
14.9.2.5	Expression constraints	37
14.9.2.6	Type constraints	39
14.9.2.7	Implicit conversion constraints	40
14.9.2.8	Argument deduction constraints	40
14.9.2.9	Constant expression constraints	40
14.9.2.10	Exception constraints	41
14.9.3	Partial ordering of constraints	41

1 General

[\[intro\]](#)

1.1 Scope

[\[general.scope\]](#)

- ¹ This technical specification describes extensions to the C++ Programming language (1.2) that enable the specification and checking of constraints on template arguments, and the ability to overload functions and specialize templates based on those constraints. These extensions include new syntactic forms and modifications to existing language semantics.
- ² International Standard, ISO/IEC 14882, provides important context and specification for this Technical Specification. This document is written as a set of changes against that specification. Instructions to modify or add paragraphs are written as explicit instructions. Modifications made directly to existing text from the International Standard use underlining to represent added text and ~~strikethrough~~ to represent deleted text.

1.2 Normative references

[\[intro.refs\]](#)

- ¹ The following referenced document is indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.
 - ISO/IEC 14882:2014, *Programming Languages - C++*
- ² ISO/IEC 14882:2014 is herein after called the *C++ Standard*. References to clauses within the C++ Standard are written as "C++ §3.2".

1.3 Implementation compliance

[\[intro.compliance\]](#)

- ¹ Conformance requirements for this specification are the same as those defined in C++ §1.4. [*Note*: Conformance is defined in terms of the behavior of programs. — *end note*]

1.4 Acknowledgments

[\[intro.ack\]](#)

- ¹ The design of this specification is based, in part, on a concept specification of the algorithms part of the C++ standard library, known as ``The Palo Alto" TR (WG21 N3351), which was developed by a large group of experts as a test of the expressive power of the idea of concepts. Despite syntactic differences between the notation of the Palo Alto TR and this TS, the TR can be seen as a large-scale test of the expressiveness of this TS.
- ² This work was funded by NSF grant ACI-1148461.

2 Lexical conventions

[lex]

2.1 Keywords

[lex.key]

In C++ §2.12, Table 4, add the keywords concept and requires.

5 Expressions

[expr]

5.1 Primary expressions

[expr.prim]

- ¹ In C++ §5.1.1, add *requires-expression* to the rule, *primary-expression*.

primary-expression:
requires-expression

5.1.2 Lambda expressions

[expr.prim.lambda]

Insert the following paragraph after paragraph 4 to define the term "generic lambda".

- ⁵ A *generic lambda* is a *lambda-expression* where either the *auto type-specifier* (7.1.6.4) or a *constrained-type-specifier* (7.1.6.5) appears in a parameter type of the *lambda-declarator*.

Modify paragraph 5 so that the meaning of a generic lambda is defined in terms of its abbreviated member function call operator.

- ⁶ The closure type for a non-generic *lambda-expression* has a public inline function call operator (C++ §13.5.4) whose parameters and return type are described by the *lambda-expression's* *parameter-declaration-clause* and *trailing-return-type* respectively. ~~For a generic lambda, the closure type has a public inline function call operator member template (14.5.2) whose template-parameter-list consists of one invented type template-parameter for each occurrence of *auto* in the lambda's parameter-declaration-clause, in order of appearance. The invented type template-parameter is a parameter pack if the corresponding parameter-declaration declares a function parameter pack (8.3.5). The return type and function parameters of the function call operator template are derived from the lambda-expression's trailing-return-type and parameter-declaration-clause by replacing each occurrence of *auto* in the decl-specifiers of the parameter-declaration-clause with the name of the corresponding invented template-parameter. For a~~ *generic lambda, the function call operator is an abbreviated member function, whose parameters and return type are derived according to the rules in 8.3.5.*

Add the following example after those in C++ §5.1.2/5. Note that the existing examples in the original document are omitted in this document.

- ⁵ [*Example*:

```
template<typename T> concept bool C = true;

auto gl = [] (C& a, C* b) { a = *b }; // OK: denotes a generic lambda

struct Fun {
    auto operator()(C& a, C* b) const { a = *b; }
} fun;
```

C is a *constrained-type-specifier*, signifying that the lambda is generic. The generic lambda, *gl*, and the function object, *fun*, have equivalent behavior when called with the same arguments. — *end example*]

5.1.3 Requires expressions

[expr.prim.req]

- ¹ A *requires-expression* provides a concise way to express syntactic requirements on template arguments. A syntactic requirement is one that can be checked by name lookup (C++ §3.4) or the checking of static properties of types and expressions. A *requires-expression* defines a conjunction of constraints (14.9), which are introduced by its *requirements*.

requires-expression:
requires *requirement-parameter-list* *requirement-body*
requirement-parameter-list:

```

        ( parameter-declaration-clauseopt )
requirement-body:
    { requirement-list }
requirement-list:
    requirement ;
    requirement-list requirement
requirement:
    simple-requirement
    compound-requirement
    type-requirement
    nested-requirement

```

- ² A *requires-expression* has type `bool`.
- ³ A *requires-expression* evaluates to `true` when all of its introduced constraints are satisfied (14.9), and `false` otherwise.
- ⁴ A *requires-expression* shall not appear outside of a concept definition (7.1.7) or a *requires-clause*. [*Example*: The most common use of *requires-expressions* is to define syntactic requirements in concepts such as the one below:

```

template<typename T>
concept bool R() {
    return requires (T i) {
        typename A<T>;
        { *i } -> const A<T>&;
    };
}

```

A *requires-expression* can also be used in a *requires-clause* templates as a way of writing ad hoc constraints on template arguments such as the one below:

```

template<typename T>
requires requires (T x) { x + x; }
T add(T a, T b) { return a + b; }

```

The first *requires* introduces the *requires-clause*, and the second introduces the *requires-expression*. — *end example*]

- ⁵ The *requires-expression* may introduce local parameters using a *parameter-declaration-clause* (8.3.5). Each name introduced by a local parameter is in scope from the point of its declaration until the closing brace of the *requirement-body*. These parameters have no linkage, storage, or lifetime; they are only used as notation for the purpose of defining requirements.
- ⁶ A local parameter shall not have a default argument.
- ⁷ The *requirement-parameter-list* shall not include an ellipsis.
- ⁸ The *requirement-body* defines a block scope, and is comprised of a sequence of *requirements*. These *requirements* may refer to local parameters, template parameters, and any other declarations visible from the enclosing context. Each *requirement* appends one or more atomic constraints (14.9) to the conjunction of constraints defined by the *requires-expressions*.

5.1.3.1 Simple requirements

[[expr.prim.req.simple](#)]

```

simple-requirement:
    expression

```

- ¹ A *simple-requirement* introduces an expression constraint for its *expression* (14.9). [*Example*:

```

template<typename T> concept bool C =
    requires (T a, T b) {
        a + b; // a simple requirement
    };

```

— end example]

- ² If the expression would always result in a substitution failure, the program is ill-formed. [Example:

```
template<typename T> concept bool C =
    requires () {
        new T[-1]; // error: the expression will never be well-formed
    };
```

— end example]

5.1.3.2 Type requirements

[[expr.prim.req.type](#)]

type-requirement:
typename-specifier

- ¹ A *type-requirement* introduces type constraint for the type named by its *typename-specifier*. [Note: A type requirement asserts the validity of an associated type, either as a member type, a class template specialization, or an alias template. It is not used to specify requirements for arbitrary *type-specifiers*. — end note] [Example:

```
template<typename T> struct S { };
template<typename T> using Ref = T&;

template<typename T> concept bool C =
    requires () {
        typename T::inner; // required nested type name
        template S<T>; // required class template specialization
        typename Ref<T>; // required alias template substitution
    };
```

— end example]

- ² If the required type will always result in a substitution failure, then the program is ill-formed. [Example:

```
template<typename T> concept bool C =
    requires () {
        typename int::X; // error: int does not have class type
    };
```

— end example]

- ³ A *type-requirement* declares its *typename-specifier* to be a *type-name*. That *type-name* is in scope from the point of its declaration to the closing brace of the *requirement-body*. [Example:

```
template<typename T> concept bool C = sizeof(T) == 1;

template<typename T> concept bool D =
    requires (T x) {
        typename Assoc<T>; // declares Assoc<T> as a type-name
        typename T::nested; // declares T::nested as a type-name
        { Assoc<T>{} }; // OK: expression constraint for Assoc<T>{}
        { ++x } -> T::nested; // OK: conversion constraint from ++x to T::nested
        requires D<Assoc<T>>; // OK: additional constraints on D
    };
```

— end example]

5.1.3.3 Compound requirements

[[expr.prim.req.compound](#)]

compound-requirement:
 constexpr_{opt} { *expression* } noexcept_{opt} *trailing-return-type*_{opt} ;

¹ A *compound-requirement* introduces a conjunction of one or more atomic constraints related to its *expression*. A *compound-requirement* introduces an expression constraint for its *expression*, *E*). If the *constexpr* specifier is present, a constant expression constraint (14.9

² [*Example*:

```
template<typename I> concept bool C() { return true; }

template<typename D> concept bool D = s
requires(T x) {
    {x++}; // #1
    {*x} -> typename T::inner; // #2
    {f(x)} -> const C&; // #3
    {g(x)} noexcept; // #4
    constexpr {T::value}; // #5
};
```

Each of these requirements introduces a valid expression constraint on the expression in its enclosing braces. Requirement #1 only an expression constraint on *x++*. It is equivalent to a *simple-requirement* with the same *expression*. Requirement #2 **x* introduces three constraints: an expression constraint for **x*, a type constraint for *typename T::inner*, and a conversion constraint requiring **x* to be implicitly convertible to *typename T::inner*. Requirement #3 also introduces two constraints: an expression constraint for *f(x)*, and a deduction constraint requiring that overload resolution succeeds for the call *i(f(x))* where *g* is the following invented function template.

```
template<typename T> requires C<T>() void i(const T&);
```

Requirement #4 introduces two constraints: an expression constraint for *g(x)* and an exception constraint on *g(x)*. Requirement #5 also introduces two constraints: An expression constraint on *T::value* and a constant expression constraint that *T::value*. — *end example*]

5.1.3.4 Nested requirements

[[expr.prim.req.nested](#)]

nested-requirement:
requires-clause ;

¹ A *nested-requirement* can be used to specify additional constraints on a type declared by a *type-requirement* (5.1.3.2). It appends a normalization of the *constraint-expression* of its *requires-clause* to the conjunction of constraints.

[*Example*:

```
template<typename T> concept bool C() { return sizeof(T) == 1; }

template<typename T> concept bool D =
requires () {
    typename X<T>;
    requires C<X<T>>();
};
```

The *nested-requirement* appends the predicate constraint *sizeof(T) == 1 ()*. — *end example*]

7 Declarations

[dcl.dcl]

7.1 Specifiers

[dcl.spec]

Extend the *decl-specifier* production to include the concept specifier.

```
1 decl-specifier:
    concept
```

7.1.6 Type specifiers

[dcl.type]

7.1.6.2 Simple type specifiers

[dcl.type.simple]

Add *constrained-type-specifier* to the grammar for *simple-type-specifiers*.

```
1 simple-type-specifier:
    constrained-type-specifier
```

7.1.6.4 auto specifier

[dcl.spec.auto]

Modify C++ §7.1.6.4/1 as follows:

¹ The *auto* and *decltype(auto)* *type-specifiers* designate a placeholder type that will be replaced later, either by deduction from an initializer or by explicit specification with a *trailing-return-type*. The *auto type-specifier* is also used to signify that a lambda is a generic lambda or that a function declaration is an abbreviated function. [*Note*: The use of the *auto type-specifier* in a non-deduced context () will cause the deduction of a value for that placeholder type to fail, resulting in an ill-formed program. — *end note*] [*Example*:

```
struct N {
    template<typename T> struct Wrap;
    template<typename T> static Wrap make_wrap(T);
};
template<typename T, typename U> struct Pair;
template<typename T, typename U> Pair<T, U> make_pair(T, U);

template<int N> struct Size { void f(int) { } };
Size<0> s;
bool g(char, double);

void (auto::*)(auto) p = &Size<0>::f;    // OK
N::Wrap<auto> a = N::make_wrap(0.0);    // OK
Pair<auto, auto> p = make_pair(0, 'a'); // OK
auto::Wrap<int> x = N::make_wrap(0);    // error: failed to deduce value for auto
Size<sizeof(auto)> y = s;                // error: failed to deduce value for auto
```

— *end example*]

Modify C++ §7.1.6.4/2 to read:

² **The** placeholder type can appear with a function declarator in the *decl-specifier-seq*, *type-specifier-seq*, *conversion-function-id*, or *trailing-return-type*, in any context where such a declarator is valid. If the function declarator includes a *trailing-return-type* (8.3.5), that specifies the declared return type of the function. The *auto type-specifier* can also appear in the *decl-specifier-seq* of a *parameter-declaration* of a function declarator. If the declared return type of the

function contains a placeholder type, the return type of the function is deduced from return statements in the body of the function, if any.

Modify C++ §7.1.6.4/3 as follows:

- ³ If the *auto type-specifier* appears ~~as one of the decl-specifiers in the decl-specifier-seq of a parameter-declaration in a parameter type~~ of a *lambda-expression*, the lambda is a generic lambda (5.1.2). [*Example:*

```
auto glambda = [](int i, auto a) { return i; }; // OK: a generic lambda
```

— *end example*] Similarly, if the *auto type-specifier* appears in a parameter type of a function declarator, that is an abbreviated function (8.3.5). [*Example:*

```
void f(const auto&, int); // OK: an abbreviated function
```

— *end example*]

Add the following paragraph after C++ §7.1.6.4/3.

- ⁴ If the *auto type-specifier* appears in the *trailing-return-type* of a *compound-requirement* in a *requires-expression*, that return type introduces a deduction constraint (). [*Example:*

```
template<typename T> concept bool C() {
    return requires (T i) {
        {*i} -> const auto&; // OK
    };
}
```

— *end example*]

Modify C++ §7.1.6.4/4. The examples in the original text are unchanged and therefore omitted.

- ⁴ The type of a variable declared using *auto* or *decltype(auto)* is deduced from its initializer. This use is allowed when declaring variables in a block (C++ §6.3), in namespace scope (C++ §3.3.6), and in a *for-init-statement* (C++ §6.5.3). ~~auto or decltype(auto) shall appear as one of the decl-specifiers in the decl-specifier-seq. Either auto shall appear in the decl-specifier-seq, or decltype(auto) shall appear as one of the decl-specifiers of the decl-specifier-seq, and the~~ The *decl-specifier-seq* shall be followed by one or more *init-declarators*, each of which shall have a non-empty initializer. In an initializer of the form

```
( expression-list )
```

the *expression-list* shall be a single *assignment-expression*.

Modify C++ §7.1.6.4/7.

- ⁵ When a variable declared using a placeholder type is initialized, or a return statement occurs in a function declared with a return type that contains a placeholder type, the deduced return type or variable type is determined from the type of its initializer. In the case of a return with no operand, the initializer is considered to be *void()*. Let τ be the declared type of the variable or return type of the function. ~~If the placeholder is the auto type-specifier, If τ contains any occurrences of the auto type-specifier, the deduced type is determined using the rules for template argument deduction. If the deduction is for a return statement and the initializer is a braced-init-list (C++ §8.5.4), the program is ill-formed. Otherwise, obtain P from τ by replacing the occurrences of auto with either a new invented type template parameter U or, if the initializer is a braced-init-list, with `std::initializer_list<U>`. Otherwise, obtain P from τ as follows:~~

- replace each occurrence of *auto* in the variable type with a new invented type template parameter, or
- when the initializer is a *braced-init-list* and *auto* is a *decl-specifier* of the *decl-specifier-seq* of the variable declaration, replace that occurrence of *auto* with `std::initializer_list<U>` where U is an invented template type parameter.

Deduce a value for U each invented template type parameter in P using the rules of template argument deduction from a function call (C++ §14.8.2.1), where P is a function template parameter type and the initializer is the corresponding argument. If the deduction fails, the declaration is ill-formed. Otherwise, the type deduced for the variable or return type is obtained by substituting the deduced U values for each invented template parameter into P . [*Example:*

```
template<typename T> struct Vec { };
template<typename T> Vec<T> make_vec(std::initializer_list<T>) { return Vec<T>{}; }

auto x1 = { 1, 2 }; // OK: decltype(x1) is std::initializer_list<int>
auto x2 = { 1, 2.0 }; // error: cannot deduce element type
auto& x3 = *x1.begin(); // OK: decltype(x3) is int&
const auto* p = &x3; // OK: decltype(p) is const int*
Vec<auto> v1 = make_vec({1, 2, 3}); // OK: decltype(v1) is Vec<int>
Vec<auto> v2 = {1, 2, 3}; // error: cannot deduce element type
```

— end example] [Example:

```
const auto& i = expr;
```

The type of *i* is the deduced type of the parameter *u* in the call *f*(*expr*) of the following invented function template:

```
template <class U> void f(const U& u);
```

— end example] [Example: Similarly, the type of *p* in the following program

```
template<typename F, typename S> struct Pair;
template<typename T, typename U> Pair<T, U> make_pair(T, U);
```

```
struct S { void mfn(bool); } s;
int fn(char, double);
```

```
Pair<auto (*)>(auto, auto), auto (auto::*)(auto)> p = make_pair(fn, &S::mfn);
```

is the deduced type of the parameter *x* in the call of *g*(*make_pair*(*fn*, &*S*::*mfn*)) of the following invented function template:

```
template<class T1, class T2, class T2, class T3, class T4, class T5, class T6>
void g(Pair< T1(*)>(T2, T3), T4 (T5::*)(T6));
```

— end example]

7.1.6.5 Constrained type specifiers

[[dcl.spec.constr](#)]

Add this section to C++ §7.1.6.

- ¹ Like the *auto* *type-specifier* (7.1.6.4), a *constrained-type-specifier* designates a placeholder that will be replaced later by deduction from the *expression* in a *compound-requirement* or a function argument. *constrained-type-specifiers* have the form

```
constrained-type-specifier:
    nested-name-specifieropt constrained-type-name
constrained-type-name:
    concept-name
    partial-concept-id
concept-name:
    identifier
partial-concept-id:
    concept-name < template-argument-listopt >
```

A *constrained-type-specifier* may also designate placeholders for deduced non-type and template template arguments. Deduction of a placeholder from a template argument succeeds only when the deduced value satisfies the constraints associated by the *constrained-type-specifier*. [Example:

```
template<typename T> concept bool C1 = false;
template<int N> concept bool C2 = false;
template<template<typename> class X> C3 = false;

template<typename T, int N> class Array { };
template<typename T, template<typename> class A> class Stack { };
template<typename T> class Alloc { };
```

```

void f1(C1 c);           // C1 designates a placeholder type
void f2(Array<auto, C2>); // C2 designates a placeholder for an integer value
void f3(Stack<auto, C3>); // C3 designates a placeholder for a class template

f1(0);                  // error
f2(Array<int, 3>{});     // error
f3(Stack<char, Alloc>{}); // error

```

In each of these function calls, the deduction of the placeholder designated by the *constrained-type-specifier* fails because the associated constraints are not satisfied. — *end example*]

- ² A *constrained-type-specifier* can appear in many of the same places as the *auto type-specifier*, is subject to the same rules, and has equivalent meaning in those contexts. In particular, a *constrained-type-specifier* can appear in the following contexts with the given meaning:

- a parameter type of a function declaration, signifying an abbreviated function (8.3.5);
- a parameter of a lambda, signifying a generic lambda (5.1.2);
- the parameter type of a template parameter, signifying a constrained template parameter (14.1);
- the *trailing-return-type* of a *compound-requirement*, signifying a deduction constraint ().

A program that includes a *constrained-type-specifier* in any other contexts is ill-formed. [*Example*:

```

template<typename T> concept bool C1 = true;
template<typename T, int N> concept bool C2 = true;
template<bool (*) (int)> concept bool C3 = true;

template<typename T> class Vec;

struct N {
    template<typename T> struct Wrap;
}
template<typename T, typename U> struct Pair;
template<bool (*) (int)> struct Pred;

auto gl = [] (C1& a, C1* b) { a = *b; }; // OK: a generic lambda
void af(const Vec<C1>& x);                // OK: an abbreviated function

void f1(N::Wrap<C1>);                    // OK
void f2(Pair<C1, C2<0>>);                 // OK
void f3(Pred<C3>);                       // OK
void f4(C1::Wrap<C2<1>>);                 // OK: but deduction of C1 will always fail

template<typename T> concept bool Iter() {
    return requires(T i) {
        {*i} -> const C1&; // OK: a deduction constraint
    };
}

```

The declaration of `f4` is valid, but a value can never be deduced for the placeholder designated by `C1` since it appears in a non-deduced context (C++ §14.8.2.5). However, a value may be explicitly given as a template argument in a *template-id*. — *end example*]

- ³ [*Example*: Unlike *auto*, a *constrained-type-specifier* cannot be used in the type of a variable declaration or the return type of a function.

```

template<typename T> concept bool C = true;
template<typename T, int N> concept bool D = true;

const C* x = 0; // error: C used in a variable type
D<0> fn(int x); // error: D<0> used as a return type

```

— *end example*]

- ⁴ A *concept-name* refers to a set of concept definitions (7.1.7) called the *candidate concept set*. If that set is empty, the program is ill-formed. [*Note*: The candidate concept set has multiple members only when referring to a set of overloaded function concepts. There is at most one member of this set when a *concept-name* refers to a variable concept. — *end note*] [*Example*:

```
template<typename T> concept bool C() { return true; }           // #1
template<typename T, typename U> concept bool C() { return true; } // #2
template<typename T> concept bool D = true;                     // #3

void f(C); // OK: the concept-name C may refer to both #1 and #2
void g(D); // OK: the concept-name D refers only to #3
```

— *end example*]

- ⁵ A *partial-concept-id* is a *concept-name* followed by a sequence of *template-arguments*. [*Example*:

```
template<typename T, typename U> concept bool C() { return true; }
template<typename T, int N = 0> concept bool Seq = true;

void f(C<int>);
void f(Seq<3>);
void f(Seq<>);
```

— *end example*]

- ⁶ The concept designated by a *constrained-type-specifier* is resolved by determining the viability of each concept in the candidate concept set. For each candidate concept in that set, Π is a *template-id* formed as follows: let c be the *concept-name* for the candidate concept set, and let x be a template argument that matches the type and form (14.4) of the prototype parameter (7.1.7) of the candidate concept. The template x is called the *deduced concept argument*. If the *constrained-type-name* in the *constrained-type-specifier* is a *concept-name*, Π is formed as $C<x>$. Otherwise, the *constrained-type-name* is a *partial-concept-id* whose *template-argument-list* is A_1, A_2, \dots, A_n , and Π is formed as $C<x, A_1, A_2, \dots, A_n>$. The candidate concept is a *viable candidate concept* when all *template-arguments* of Π match the template parameters of that candidate (14.4). If, after determining the viability of each concept, there is a single viable candidate concept, that is the concept designated by the *constrained-type-specifier*. Otherwise, the program is ill-formed. [*Example*:

```
template<typename T> concept bool C() { return true; }           // #1
template<typename T, typename U> concept bool C() { return true; } // #2
template<typename T> concept bool P() { return true; }
template<int T> concept bool P() { return true; }

void f1(const C*); // OK: C designates #1
void f2(C<char>); // OK: C<char> designates #2
void f3(C<3>);    // error: no matching concept for C<3> (mismatched template arguments)
void g1(P);       // error: resolution of P is ambiguous (P refers to two concepts)
```

— *end example*]

- ⁷ The use of a *constrained-type-specifier* in the type of a *parameter-declaration* associates a constraint (14) with the entity for which that parameter is declared. In the case of a generic lambda, the constraint is associated with the member function call operator of the closure type (5.1.2). For an abbreviated function declaration, the constraint is associated with that function (8.3.5). The use of a *constrained-type-specifier* in the *trailing-return-type* of a *compound-requirement* includes an associated constraint in the conjunction of constraints introduced by that requirement (). When a *constrained-type-specifier* is used in a *template-parameter*, the constrained it associated with the template-declaration in which the *template-parameter* is declared.
- ⁸ The constraint associated by a *constrained-type-specifier* is derived from the *template-id* (called Π above) used to determine the viability of the designated concept (call it D). The constraint is formed by replacing the deduced concept argument x in Π with a template argument, A . That template argument is defined as follows:

- when the *constrained-type-specifier* appears in the type of a *parameter-declaration* of a function declaration, *A* is the name of the invented template parameter corresponding to the *constrained-type-specifier* (8.3.5);
- when the *constrained-type-specifier* appears in the *trailing-return-type* of a *compound-requirement*, *A* is the type deduced for that *constrained-type-specifier* from the expression *expression* in the requirement (5.1.3);
- when the *constrained-type-specifier* appears in a *template-parameter* declaration, *A* is the name of the declared parameter (14.1).

Let π_2 be a *template-id* formed as follows. If *A* is a template parameter (possibly invented) that declares a template parameter pack, and *D* is a variadic concept (7.1.7), π_2 is formed by replacing *x* in π with the pack expansion *A...* Otherwise π_2 is formed by replacing *x* with *A*. Let *E* be the *id-expression* π_2 when the *D* is a variable concept, and the function call $\pi_2()$ when the *D* is a function concept. If *A* is a template parameter that declares a template parameter pack, and *D* is not a variadic concept, then the associated constraint is the fold expression ($\dots \&\& E$) (C++ §5.1.4). Otherwise, the associated constraint is the expression *E*.

[*Example*:

```
template<typename T> concept bool C = true;
template<typename T, typename U> concept bool D() { return true; }
template<int N> concept bool Num = true;

template<int> struct X { };

void f(C&);           // associates C<T1> with f
void g(D<int>);       // associates D<T2, int>() with g
void h(X<Num>);       // associates Num<M> with h
template<C T> struct s1; // associates C<T> with s1
```

In the associated constraints, *T*₁ and *T*₂ are invented type template parameters corresponding to the prototype parameter of their respective designated concepts. Likewise, *M* is a non-type template parameter corresponding to the prototype parameter of *Num*.

```
template<typename T>
concept bool Req =
    requires (T t) {
        { *t } -> const C&; // adds the constraint C<A> to Req
    };

```

In the constraint introduced by the *constrained-type-specifier* `const C&`, *A* is the deduced type of the parameter *a* in the the call `f(*t)` of the following invented function template:

```
template<typename A>
void f(const A& a);
```

— *end example*]

9

7.1.7 concept specifier

[[dcl.spec.concept](#)]

- ¹ The concept specifier shall be applied only to the definition of a function template or variable template, declared in namespace scope (C++ §3.3.6). A function template definition having the concept specifier is called a *function concept*. A function concept is a non-throwing function (C++ §15.4). A variable template definition having the concept specifier is called a *variable concept*. A *concept definition* refers to either a function concept and its definition or a variable concept and its initializer. [*Example*:

```
template<typename T>
concept bool F1() { return true; } // OK: declares a function concept
template<typename T>
concept bool F2();                // error: function concept is not a definition
template<typename T>
concept bool V1 = true;           // OK: declares a variable concept
template<typename T>
concept bool V2;                 // error: variable concept with no initializer
```

```
struct S {
    template<typename T>
        static concept bool C = true;    // error: concept declared in class scope
};
```

— end example]

- ² No storage specifiers shall appear in a declaration with the concept specifier. Additionally, a concept definition shall not include the friend or constexpr specifiers.
- ³ Every concept definition is also a constexpr declaration (C++ §7.1.5).
- ⁴ A concept definition shall be unconstrained. [*Note*: A concept defines a total mapping from its template arguments to the values true and false. — end note]
- ⁵ The first declared template parameter of a concept definition is its *prototype parameter*. A *variadic concept* is a concept whose prototype parameter is a template parameter pack.
- ⁶ A function concept has the following restrictions:
 - No *function-specifiers* shall appear in the declaration.
 - The return type shall be bool.
 - The declaration shall have a *parameter-declaration-clause* equivalent to ().
 - The function shall not be recursive.
 - The function body shall consist of a single return statement whose *expression* shall be a *constraint-expression* (14.9).

[*Example*:

```
template<typename T>
    concept int F1() { return 0; }    // error: return type is not bool
template<typename T>
    concept bool F2(T) { return true; } // error: must have no parameters
```

— end example]

- ⁷ A variable concept has the following restrictions:
 - The declared type shall be bool.
 - The declaration shall have an initializer.
 - The initializer shall be a *constraint-expression*.

[*Example*:

```
template<typename T>
    concept bool V2 = 3 + 4; // error: initializer is not a constraint-expression
template<Integral T>
    concept bool V3 = true;  // error: constrained template declared as a concept
concept bool V4 = 0;        // error: not a template
```

— end example]

- ⁸ A program that declares an explicit instantiation, an explicit specialization, or a partial specialization of a concept definition is ill-formed. [*Example*:

```
template<typename T> concept bool C = false;

template concept bool C<char>; // error: explicit instantiation of a concept
template<>
    concept bool C<int> = true; // error: explicit specialization of a concept
template<typename T>
    concept bool C<T*> = true;  // error: partial specialization of a concept
```

— end example]

- ⁹ [*Note*: The prohibitions against overloading and specialization prevent users from subverting the constraint system by providing a meaning for a concept that differs from the one computed by evaluating its constraints. — end note]

8 Declarators

[dcl.decl]

Modify the definition of the *init-declarator* production in C++ §8/1 as follows:

- ¹ A declarator declares a single variable, function, or type within a declaration. The *init-declarator-list* appearing in a declaration is a comma-separated sequence of declarators, each of which may **have an initializer have constraints, an initializer, or both.**

init-declarator:

declarator requires-clause_{opt} initializer_{opt}

Insert the following paragraphs.

- ² A *requires-clause* in an *init-declarator* shall only appear with a function declarator (8.3.5). If present, the *requires-clause* associates its *constraint-expression* with the declared function (14).
[*Example:*

```
template<typename T> concept bool C = true;
```

```
void f1(int x) requires C<int>;           // OK
```

```
auto n requires C<decltype(n)> = 'a'; // error: constrained variable declaration
```

— *end example*]

- ³ The names of parameters in a function declarator are visible in the *constraint-expression* of the *requires-clause*. [*Example:*

```
template<typename T> concept bool C = true;
```

```
void f(auto x) requires C<decltype(x)>;
```

```
void g(int n) requires sizeof(n) == 4;
```

— *end example*]

8.3 Meaning of declarators

[dcl.meaning]

8.3.5 Functions

[dcl.fct]

Refactor the grammar for *parameter-declarations* in paragraph 3 in order to support the definition of *template-parameters* in Clause 14.

- ³ *parameter-declaration:*
 basic-parameter-declaration
 basic-parameter-declaration = *initializer*
basic-parameter-declaration:
 attribute-specifier-seq_{opt} decl-specifier-seq declarator
 attribute-specifier-seq_{opt} decl-specifier-seq abstract-declarator_{opt}

Modify the second sentence of paragraph 5. The remainder of this paragraph has been omitted.

- ⁵ A single name can be used for several different functions in a single scope; this is function overloading (13). All declarations for a function shall agree exactly in **both** the return type, **and** the parameter-type-list, **and associated constraints, if any** (14).

Modify paragraph 15. Note that the footnote reference has been omitted.

- ¹⁵ There is a syntactic ambiguity when an ellipsis occurs at the end of a *parameter-declaration-clause* without a preceding comma. In this case, the ellipsis is parsed as part of the *abstract-declarator* if the type of the parameter either names a template parameter pack that has not been expanded or contains **either** *auto* **or a constrained-type-specifier**; otherwise, it is parsed as part of the *parameter-declaration-clause*.

Add the following paragraphs after C++ §8.3.5/15.

- ¹⁶ An *abbreviated function* is a function whose parameter-type-list includes one or more placeholders (7.1.6.4, 7.1.6.5). An abbreviated function is equivalent to a function template (14.5.6) whose *template-parameter-list* includes one invented *template-parameter* for each occurrence of a placeholder in the *parameter-declaration-clause*, in order of appearance. If the placeholder is designated by the *auto type-specifier*, then the corresponding invented template parameter is a type *template-parameter*. Otherwise, the placeholder is designated by a *constrained-type-specifier*, and the corresponding invented parameter matches the type and form of the prototype parameter (7.1.7) of the concept designated by the *constrained-type-specifier*. The invented *template-parameter* is a parameter pack if the corresponding *parameter-declaration* declares a function parameter pack and the type of the parameter contains only one placeholder. If the type of the function parameter that declares a function parameter pack containing more than one placeholder, the program is ill-formed. The adjusted function parameters of an abbreviated function are derived from the *parameter-declaration-clause* by replacing each occurrence of a placeholder with the name of the corresponding invented *template-parameter*. If the replacement of a placeholder with the name of a template parameter results in an invalid parameter declaration, the program is ill-formed. [*Example*:

```
template<typename T> class Vec { };
template<typename T, typename U> class Pair { };

void f1(const auto&, auto);
void f2(Vec<auto*>...);
void f3(auto (auto::*)(auto));

template<typename T, typename U>
    void f1(const T&, U);           // redeclaration of f1(const auto&, auto)
template<typename... T>
    void f2(Vec<T*>...);           // redeclaration of f2(Vec<auto*>...)
template<typename T, typename U, typename V>
    void f3(T (U::*)(V));          // redeclaration of f3(auto (auto::*)(auto))

void foo(Pair<auto, auto>...); // error: multiple placeholder types in a parameter pack

template<typename T> concept bool C1 = true;
template<typename T> concept bool C2 = true;
template<typename T, typename U> concept bool D = true;

void g1(const C1*, C2&);
void g2(Vec<C1>&);
void g3(C1&...);
void g4(Vec<D<int>>);

template<C1 T, C2 U> void g1(const T*, U&); // redeclaration of g1(const C1*, C2&)
template<C1 T> void g2(Vec<T>&);           // redeclaration of g2(Vec<C1>&)
template<C1... Ts> void g3(Ts&...);        // redeclaration of g3(C1&...)
template<D<int> T> void g4(Vec<T>);        // redeclaration of g4(Vec<D<int>>)
```

— *end example*] [*Example*:

```
template<int N> concept bool Num = true;

void h(Num*); // error: invalid type in parameter declaration
```

The equivalent and erroneous declaration would have this form:

```
template<int N> void h(N*); // error: invalid type
```

— *end example*]

- ¹⁷ All placeholders introduced using the same *constrained-type-specifier* have the same invented template parameter. [*Example*:

```
namespace N {
    template<typename T> concept bool C = true;
}
template<typename T> concept bool C = true;
template<typename T, int> concept bool D = true;
template<typename, int = 0> concept bool E = true;
```

```
void f0(C a, C b);
```

The types of *a* and *b* are the same invented template type parameter.

```
void f1(C& a, C* b);
```

The type of *a* is a reference to an invented template type parameter (call it *τ*), and the type of *b* is a pointer to *τ*.

```
void f2(N::C a, C b);
void f3(D<0> a, D<1> b);
```

In both functions, the parameters *a* and *b* have different invented template type parameters.

```
void f4(E a, E<> b, E<0> c);
```

The types of *a*, *b*, and *c* are distinct invented template type parameters even though the constraints associated by the each of the *constrained-type-specifiers* (7.1.6.5) are equivalent. — *end example*]

- ¹⁸ A function template can be an abbreviated function. The invented *template-parameters* are added to the *template-parameter-list* after the explicitly declared *template-parameters*. [*Example*:

```
template<typename T, int N> class Array { };

template<int N> void f(Array<auto, N>*>);
template<int N, typename T> void f(Array<T, N>*>); // OK: equivalent to f(Array<auto, N>*)
```

— *end example*]

8.4 Function definitions

[dcl.fct.def]

8.4.1 In general

[dcl.fct.def.general]

Modify the *function-definition* syntax in C++ §8.4.1 to include a *requires-clause*.

```
1      function-definition:
           attribute-specifier-seqopt decl-specifier-seqopt declarator virt-specifier-
           seqopt requires-clauseopt function-body
```

Add the following paragraph.

- ⁹ *If present, the *requires-clause* associates its *constraint-expression* with the function (14).*

9 Classes

[class]

9.2 Class members

[class.mem]

In C++ §9.2, modify the *member-declarator* syntax.

```
1      member-declarator:
      declarator virt-specifier-seqopt requires-clauseopt pure-specifier-seqopt
```

Insert the following paragraphs after C++ §9.2/8.

- ⁹ A *requires-clause* shall only appear in a *member-declarator* if its *declarator* is a function declarator. The *requires-clause* associates its *constraint-expression* with the member function.
[*Example*:

```
struct A {
    A(int*) requires true; // OK: constrained constructor
    ~A() requires true;    // OK: constrained destructor
    void f() requires true; // OK: constrained member function
    int x requires true;   // error: constrained member variable
};
```

— *end example*]

- ¹⁰ The names of parameters in a function declarator are visible in the *constraint-expression* of the *requires-clause*.

10 Derived classes

[class.derived]

10.3 Virtual functions

[class.virtual]

Insert the following paragraph after paragraph 5 in order to prohibit the declaration of constrained virtual functions and the overriding of a virtual function by a constrained member function.

- ⁶ If a virtual function has associated constraints (14), the program is ill-formed. If a constrained member function overrides a virtual function in any base class, the program is ill-formed.

[*Example:*

```
struct A {  
    virtual void f() requires true; // error: constrained virtual function  
};
```

```
struct B {  
    virtual void f();  
};
```

```
struct D : B {  
    void f() requires true; // error: constrained override  
}
```

— *end example*]

13 Overloading

[over]

Modify paragraph 1 to allow overloading based on constraints.

- ¹ When two or more different declarations are specified for a single name in the same scope, that name is said to be overloaded. By extension, two declarations in the same scope that declare the same name but with different types or different associated constraints (14) are called *overloaded declarations*. Only function and function template declarations can be overloaded; variable and type declarations cannot be overloaded.

Update paragraph 3 to mention a function's overloaded constraints. Note that the itemized list in the original text is omitted in this document.

- ³ [*Note:* As specified in 8.3.5, function declarations that have equivalent parameter declarations and associated constraints, if any (14), declare the same function and therefore cannot be overloaded: ... — *end note*]

13.2 Declaration matching

[over.dcl]

Modify paragraph 1 to extend the notion of declaration matching to also include a function's associated constraints. Note that the example in the original text is omitted in this document.

- ¹ Two function declarations of the same name refer to the same function if they are in the same scope and have equivalent parameter declarations (C++ §13.1) and equivalent associated constraints, if any (14).

13.3 Overload resolution

[over.match]

13.3.1 Viable functions

[over.match.viable]

Update paragraph 1 to require the checking of a candidate's associated constraints when determining if that candidate is a viable candidate for a function call.

- ¹ From the set of candidate functions constructed for a given context (C++ §13.3.1), a set of viable functions is chosen, from which the best function will be selected by comparing argument conversion sequences and associated constraints for the best fit (13.3.2). The selection of viable functions considers their associated constraints, if any (14), and their relationships between arguments and function parameters other than the ranking of conversion sequences.

Insert the following paragraph after paragraph 1; this introduces new a criterion for determining if a candidate is viable. Also, update the beginning of the subsequent paragraphs to account for the insertion.

- ² First, for F to be a viable function, if F has associated constraints (14), those constraints shall be satisfied (14.9).
- ³ ~~First~~Second, to be a viable function ...
- ⁴ ~~Second~~Third, for F to be a viable function ...

13.3.2 Best viable function

[over.match.best]

Modify the last item in the list in paragraph 1 and extend it with a final comparison based on the associated constraints of those functions. This applies to both normal functions and specializations of function templates. Note that the preceding (unmodified) items in the original document are elided in this document.

- ¹ Define ICSi(F) as follows:

— ...

- F1 and F2 are function template specializations, and the function template for F1 is more specialized than the template for F2 according to the partial ordering rules described in 14.5.6.2, or, if not that,
- F1 is more constrained than F2 according to the partial ordering of constraints described in 14.9.

13.4 Address of overloaded function

[over.over]

The introduction of constraints modifies the rules for determining which function is selected when taking the address of an overloaded function. Insert a new paragraph before paragraph 4.

- ⁴ If a single constrained function is selected, and the constraints are not satisfied (14.9), the program is ill-formed.

Modify paragraph 4 (paragraph 5 in this document) to incorporate constraints in the selection of an overloaded function when its address is taken. Also add the following example after that in the original document (not shown here).

- ⁵ If more than one function is selected, any function template specializations in the set are eliminated if the set also contains a function that is not a function template specialization, and, Any given non-template function F0 is eliminated if the set contains a second non-template function that is more constrained than F0 according to the partial ordering rules of 14.9.3. Furthermore, any given function template specialization F1 is eliminated if the set contains a second function template specialization whose function template is more specialized than the function template of F1 according to the partial ordering rules of 14.5.6.2. After such eliminations, if any, there shall remain exactly one selected function.

[Example:

```
void f() { }           // #1
void f() requires true { }; // #2
void g() requires false;

void (*pf)() = &f;      // selects #2
void (*pg)() = &g;      // error: g() cannot be selected
```

— end example]

14 Templates

[temp]

Modify the *template-declaration* grammar in paragraph 1 to allow a template declaration introduced by a concept.

```

1      template-declaration:
          template < template-parameter-list > requires-clauseopt declaration
          introduction-clause declaration
      requires-clause:
          requires constraint-expression

```

Add the following paragraphs after paragraph 6.

⁷ A *template-declaration* is written in terms of its template parameters. These parameters are declared explicitly in a *template-parameter-list* (14.1), or they are introduced by a template introduction (14.2).

The *associated constraints* of a *template-declaration* are the conjunction of all constraints introduced by:

- a concept introduction, and
- a *requires-clause* following a *template-parameter-list*, and
- any constrained template parameters (14.1) in the declaration's *template-parameter-list*, and
- any *constrained-type-specifiers* in the *decl-specifier-seq* of a *parameter-declaration* in a function declaration or definition (7.1.6.5), and
- a *requires-clause* appearing after the *declarator* of an *init-declarator* (8), *function-definition* (8.4.1), or *member-declarator* (9.2).

Let τ be a *template-declaration* with associated constraints. τ is equivalent to another *template-declaration* (call it ϵ) whose template parameters are declared explicitly as unconstrained template parameters, and ϵ has a single *requires-clause* whose *constraint-expression* is equivalent to the associated constraints of τ (14.9.1). [*Note*: The following paragraphs describes how constrained template declarations can be equivalently written using alternative syntax in order to generate a canonical spelling of a template's associated constraints.] *Example*:

```

template<typename T> concept bool C = true;

// all of the following declare the same function:
void g(C);
template<C T> void g(T);
C{T} void g(T);
template<typename T> requires C<T> void g(T);

```

The last declaration includes the canonical spelling of the associated constraints for all declarations of $g(T)$ as the *constraint-expression* of its *requires-clause*. — *end example*] The paragraphs below define the rules that make these declarations equivalent. — *end note*]

⁸ When a *template-declaration* is declared by a template introduction (14.2), it is equivalent to a *template-declaration* whose *template-parameter-list* is defined according to the rules for introducing template parameters in 14.2, and the equivalent declaration has a *requires-clause* whose *constraint-expression* is formed as follows. Let $\tau\tau$ be a *template-id* formed as $C<I_1, I_2, \dots, I_n, D_1, D_2, \dots, D_n>$ where C is the name of the designated concept, I_1, I_2, \dots, I_n is the sequence of introduced template parameters, and D_1, D_2, \dots, D_n is the (possibly empty) sequence of instantiated default template arguments needed to form the *template-id* that refers to C . If an introduced parameter declares a template parameter pack, the corresponding template argument in the $\tau\tau$ is a pack expansion $()$. If C is a variable concept, then the *constraint-expression* is the *id-expression* $\tau\tau$. If C is a function concept, then the *constraint-expression* is the function call $\tau\tau()$. [*Example*:

```

template<typename T, typename U> concept bool C1 = true;
template<typename T, typename U> concept bool C2() { return true; }

```



```

template<typename T, typename U = char> concept bool C3 = true;
template<typename... Ts> concept bool C4 = true;

C1{A, B} struct X;
C2{A, B} struct Y;
C3{P} void f(P);
C4{...Qs} void g(Qs&&...);

template<typename A, typename B>
  requires C1<A, B> // constraint associated by C1{A, B}
  struct X;        // OK: redeclaration of X

template<typename A, typename B>
  requires C2<A, B>() // constraint associated by C2{A, B}
  struct Y;          // OK: redeclaration of Y

template<class P>
  requires C3<P> // constraint associated by C3{P}
  void f(P);    // OK: redeclaration of f(P)

template<typename... Qs>
  requires C4<Qs...> // constraint associated by C4{...Qs}
  void void g(Qs&&...); // OK: redeclaration of g(Qs&&...)

```

— end example]

- ⁹ When a *template-declaration* (call it τ) is explicitly declared with *template-parameter-list* that has constrained template parameters (14.1), it is equivalent to a *template-declaration* (call it ϵ) with the same template parameters, except that all constrained parameters are replaced by unconstrained parameters matching the corresponding prototype parameter designated by the *constrained-type-specifier* (7.1.6.5). The declaration, ϵ , has a *requires-clause* whose *constraint-expression* is the conjunction of the constraints associated by the constrained template parameters in τ . The order in which the introduced constraints are evaluated is the same as the order in which the constrained template parameters are declared. If the original declaration τ includes a *requires-clause*, its *constraint-expression* is evaluated after the constraints associated by the constrained template parameters in ϵ . [Example:

```

template<typename> concept bool C1 = true;
template<int> concept bool C2 = true;

template<C1 A, C2 B> struct S;
template<C1 T> requires C2<sizeof(T)> void f(T);

template<typename X, int Y>
  requires C1<X> && C2<Y>
  struct S; // OK: redeclaration of S

template<typename T>
  requires C1<T> && C2<sizeof(T)>
  void f(T); // OK: redeclaration of f(T)

```

— end example]

- ¹⁰ When the declaration is an abbreviated function, it is equivalent to a *template-declaration* whose template parameters are declared according to the rules in 8.3.5. The associated constraints of the abbreviated function are evaluated in the order in which they appear. [Example:

```

template<typename T> concept bool C = true;
template<typename T> concept bool D() { return true; }

void f(C, C, D);

```

```
template<C T, D U>
void f(T, T, U); // OK: redeclaration of f(C, C, D)

template<typename T, typename U>
requires C<T> && D<U>()
void f(T, T, U); // OK: also a redeclaration of f(C, C, D)
```

— end example]

- ¹¹ An abbreviated function can also be declared as a *template-declaration*. The constraints associated by *constrained-type-specifiers* in the *parameter-declaration-clause* of the function declaration are evaluated after those introduced by *constrained-type-specifiers* in the *template-parameter-list* and the following *requires-clause*, if present. This is also the case for an abbreviated function that is declared is declared with a concept introduction. [Example:

```
template<typename T> concept bool C = true;
template<typename T> concept bool D() { return true; }
template<typename T> concept bool P = true;

template<C T> requires P<T> void g1(T, D);
template<C T> void g2(T, D);

template<typename T, typename U>
requires C<T> && P<T> && D<U>()
void g1(T, U); // OK: redeclaration of g1(T, D)

C{ T } void g2(T, D); // OK: redeclaration of g2(T, D)
```

— end example]

- ¹² A *trailing requires-clause* is a *requires-clause* that appears after the *declarator* in an *init-declarator* (8), *function-definition* (8.4.1), or *member-declarator* (9.2). When a constrained function template or member function template is declared with a trailing *requires-clause* it is equivalent to a declaration in which the *constraint-expression* of the trailing *requires-clause* is evaluated after all other associated constraints. [Example:

```
template<C T> struct S {
    template<D U> void f(U) requires D<T>;
};

template<C T> template<typename U>
requires D<U> && D<T>
void S<T>::f(U) { } // OK: definition of S<T>::f(U)

template<C T> template<typename U>
void S<T>::f(U) requires D<U> && D<T> { } // error: redefinition of S<T>::f(U)
```

The second definition if `S<T>::f(U)` is an error because its declaration is equivalent to the first. — end example]

14.1 Template parameters

[temp.param]

Modify the *template-parameter* grammar in C++ §14.1/1 in order to allow constrained template parameters.

```
1      template-parameter:
           parameter-declaration
           non-type-or-constrained-parameter
non-type-or-constrained-parameter:
           basic-parameter-declaration
           basic-parameter-declaration = initializer
           basic-parameter-declaration = type-id
```

basic-parameter-declaration = *id-expression*

Update the wording in C++ §14.1/2 as follows.

- ² There is no semantic difference between *class* and *typename* in a *template-parameter*. *typename* followed by an *unqualified-id* names a template type parameter. *typename* followed by a *qualified-id* denotes the type in a non-type *parameter-declaration* *non-type-or-constrained-parameter*.

Insert the following paragraphs after paragraph 3 in order to distinguish between a template parameter that declares a non-type parameter and a template-parameter that declares a constrained parameter, which may declare a type parameter.

- ³ When a *non-type-or-constrained-parameter* has the following form:
- constrained-type-specifier* ...*opt identifier*_{opt}
- it declares a *constrained template parameter*. Otherwise the parameter is a non-type *template-parameter*.
- ⁴ If the *auto type-specifier* appears in the the parameter type of a *non-type-or-constrained-parameter*, the program is ill-formed. The program is also ill-formed if a *constrained-type-specifier* appears anywhere in the *basic-parameter-declaration* and the form of that declaration does not match the form above.

[*Example*:

```
template<typename T> concept bool C = true;
template<typename T> concept bool D = true;

template<C T> struct S1;      // OK: T is a constrained template parameter
template<int N> struct S2;   // OK: N is a non-type template parameter
template<auto X> struct S2;  // error: auto in template parameter
template<const D N> void f1(); // error: D is used with a const-qualifier
template<D* N> void f2();    // error: N declares a pointer-to-D
```

— *end example*]

Insert the following paragraphs after paragraph 8. These paragraphs define the meaning of a constrained template parameter.

- ⁹ A constrained template parameter declares a template parameter whose type and form match that of the prototype parameter of the concept designated by its *constrained-type-specifier*. The designated concept is found using the rules in 7.1.6.5. Let *I* be the *declarator-id* of the *basic-parameter-declaration*, and let *P* be the prototype parameter of the designated concept. The declared template parameter is determined by the type and form of *P* and the *identifier* and optional ellipsis in *I*.
- If *P* is a type *template-parameter* declared with the *class* or *typename*, the declared parameter is a type *template-parameter*.
 - If *P* is a non-type *template-parameter*, the declared parameter is a non-type *template-parameter* having the same type as *P*.
 - If *P* is a template *template-parameter*, the declared parameter is a template *template-parameter* having the same *template-parameter-list* as *P*.
 - If *P* declares a template parameter pack, *I* shall include an ellipsis, and the declared parameter is a template parameter pack.

[*Example*:

```
template<typename T> concept bool C1 = true;
template<template<typename> class X> concept bool C2 = true;
template<int N> concept bool C3 = true;
template<typename... Ts> concept bool C4 = true;
template<char... Cs> concept bool C5 = true;

template<C1 T> void f1();      // OK: T is a type template-parameter
template<C2 X> void f2();     // OK: X is a template with one type-parameter
template<C3 N> void f3();     // OK: N has type int
template<C4... Ts> void f4(); // OK: Ts is a template parameter pack of types
```

```
template<C4 Ts> void f5();    // error: Ts must be preceded by an ellipsis
template<C5... Cx> f6();    // OK: Cs is a template parameter pack of chars
— end example ]
```

14.2 Introduction of template parameters

[\[temp.intro\]](#)

Add this section after [14.1](#).

- ¹ A *template introduction* provides a convenient way of declaring different templates that have the same template parameters and constraints.

```
introduction-clause:
    nested-name-specifieropt concept-name introduction-list
introduction-list:
    introduced-parameter
    introduction-list, introduced-parameter
introduced-parameter:
    ...opt identifier
```

A template introduction declares a sequence of *template-parameters*, which are derived from a *concept-name* and the sequence of *identifiers* in its *introduction-list*.

- ² The concept designated by the *concept-name* (call it *c*) is determined by the *introduction-list*. The set of concept definitions named by *c* is called the candidate concept set. A concept *cc* is viable if *cc* declares at least as many template parameters as there are *identifiers* in the *introduction-list*, and all excess template parameters are declared with default template arguments. If only one concept in that set is viable, that is the concept designated by *c*. Otherwise, the program is ill-formed. [*Example*: It is possible to overload function concepts in such a way that a *concept-name* can designate multiple concepts.

```
template<typename T> concept bool Eq() { return true; }           // #1
template<typename T, typename U> concept bool Eq() { return true; } // #2

Eq{T} void f1(T, T);    // OK: Eq{T} designates #1
Eq{A, B} void f2(A, B); // OK: Eq{A, B} designates #2

template<typename T> concept bool C() { return true; }
template<int N> concept bool C() { return true; }

C{X} void f(); // error: resolution of C{X} is ambiguous
```

— end example]

- ³ For each *introduced-parameter* *I* in an *introduction-list*, and for its corresponding template parameter in the *template-parameter-list* of the designated concept (call it *P*), declare a new template parameter using the rules for declaring a constrained parameter ([14.1](#)) by using *I* as a *declarator-id* and *P* as the prototype parameter. However, if *I* contains an ellipsis, *P* shall declare a template parameter pack. [*Example*:

```
template<typename T, int N, typename... Xs> concept bool C1 = true;
template<template<typename> class X> concept bool C2 = true;

C1{A, B, ...C} // OK: A is declared as typename A
    struct s;  // B is declared as int B
               // C is declared as typename... C

C1{X, Y, Z} // error: Z must be preceded by an ellipsis
    struct t;

C2{T} // OK: T is declared as template<typename> class T
    void foo();

C2{...X} // error: the corresponding parameter is not a
    void bar(); // template parameter pack
```

— end example]

- ⁴ [*Note*: A concept referred to by a *concept-name* may have template parameters with default template arguments. An *introduction-list* may omit *identifiers* for a corresponding template parameter if it has a default argument. However, only the *introduced-parameters* are declared as template parameters. [*Example*:

```
template<typename A, typename B = bool>
    concept bool C() { return true; }

C{T} void f(T); // OK: f(T) is a function template with
                // a single template type parameter T
```

There is no *introduced-parameter* that corresponds to the template parameter B in the C concept, so f(T) is declared with only one template parameter. — end example] — end note]

- ⁵ An introduced template parameter does not have a default template argument, even if its corresponding template parameter does. [*Example*:

```
template<typename T, int N = -1> concept bool P() { return true; }

P{T, N} struct Array { };

Array<double, 0> s1; // OK
Array<double> s2;    // error: Array takes two template arguments
```

— end example]

- ⁶ [*Note*: The introduction of a sequence of template parameters by a *concept-name* associates a constraint with the *template-declaration* according to the rules describe in 14. — end note]

14.3 Names of template specializations

[temp.names]

Add the following paragraph to require the implicit instantiation of default template arguments for non-function templates.

- ⁸ When a *simple-template-id* does not name a function, a default *template-argument* is implicitly instantiated (14.7.1) in a context that requires the value of that default argument. [*Example*:

```
template<typename T, typename U = int> struct S { };

S<bool>* p; // the type of p is S<bool, int>*
```

The default argument for U is instantiated to form the type S<bool, int>*, but the definition of that class template specialization is not implicitly instantiated (C++ §14.7.1); it is not used in a context that requires a complete type. — end example]

Add this paragraph to require the satisfaction of associated constraints on the formation of the *simple-template-id*.

- ⁹ When a *simple-template-id* names a constrained class template, variable template or alias template, and all *template-arguments* in the *template-id* are non-dependent, (), the associated constraints are checked against those *template-arguments* (14.9). If, as a result of checking, the associated constraints are not satisfied, the program is ill-formed. [*Example*:

```
template<typename T> requires false struct S { };

S<int>* p; // error: constraints not satisfied.
```

— end example]

14.4 Template arguments

[temp.arg]

14.4.1 Template template arguments

[temp.arg.template]

Modify paragraph 3 to include rules for matching constrained template template parameters. Note that the examples following this paragraph in the original document are omitted.

- ³ A *template-argument* matches a template *template-parameter* (call it *P*) when each of the template parameters in the *template-parameter-list* of the *template-argument*'s corresponding class template or alias template (call it *A*) matches the corresponding template parameter in the *template-parameter-list* of *P*, and the associated constraints of *P* subsume the associated constraints of *A* (14.9). Two template parameters match if they are of the same kind (type, non-type, template), for non-type *template-parameters*, their types are equivalent (14.5.6.1), and for template *template-parameters*, each of their corresponding *template-parameters* matches, recursively. When *P*'s *template-parameter-list* contains a template parameter pack (C++ §14.5.3), the template parameter pack will match zero or more template parameters or template parameter packs in the *template-parameter-list* of *A* with the same type and form as the template parameter pack in *P* (ignoring whether those template parameters are template parameter packs).

Add the following example to the end of paragraph 3, after the examples given in the original document.

- ³ [*Example*:
- ```
template<typename T> concept bool C = requires (T t) { t.f(); };
template<typename T> concept bool D = C<T> && requires (T t) { t.g(); };

template<template<C> class P>
 struct S { };

template<C> struct X { };
template<D> struct Y { };
template<typename T> struct Z { };

S<X> s1; // OK: X has the same constraints as P
S<Y> s2; // error: the constraints of P do not subsume those of Y
S<Z> s3; // OK: the constraints of P subsume those of Z
```
- *end example* ]

## 14.5 Template declarations

[temp.decls]

### 14.5.1 Class templates

[temp.class]

Modify paragraph 3 to require template constraints for out-of-class definitions of members of constrained templates. Note that the example in the original document is omitted. The example in this paragraph is to be added after the omitted example.

- <sup>3</sup> When a member function, a member class, a member enumeration, a static data member or a member template of a class template is defined outside of the class template definition, the member definition is defined as a template definition in which the *template-parameters* and associated constraints are those of the class template. The names of the template parameters used in the definition of the member may be different from the template parameter names used in the class template definition. The template argument list following the class template name in the member definition shall name the parameters in the same order as the one used in the template parameter list of the member. Each template parameter pack shall be expanded with an ellipsis in the template argument list. [ *Example*:

```
template<typename T> concept bool C = true;
template<typename T> concept bool D = true;
```

```

template<C T> struct S {
 void f();
 void g();
 template<D U> struct Inner;
}

template<C T> void S<T>::f() { } // OK: parameters and constraints match
template<typename T> void S<T>::g() { } // error: no matching declaration for S<T>

template<C T>
 template<D U> struct S<T>::Inner { }; // OK

```

The declaration of `S<T>::g()` does not match because it does not have the associated constraints of `s`. — *end example* ]

#### 14.5.1.1 Member functions of class templates

[temp.mem.func]

Add the following example to the end of paragraph 1.

<sup>1</sup> [ *Example*:

```

template<typename T> struct S {
 void f() requires true;
 void g() requires true;
};

template<typename T>
 void S<T>::f() requires true { } // OK
template<typename T>
 void S<T>::g() // error: no matching function in S<T>

```

— *end example* ]

#### 14.5.2 Member templates

[temp.mem]

Modify paragraph 1 in order to account for constrained member templates of (possibly) constrained class templates. Add the example in this document after the example in the original document, which is omitted here.

<sup>1</sup> A template can be declared within a class or class template; such a template is called a member template. A member template can be defined within or outside its class definition or class template definition. A member template of a class template that is defined outside of its class template definition shall be specified with the *template-parameters and associated constraints* of the class template followed by the *template-parameters and associated constraints* of the member template. [ *Example*:

```

template<typename T> concept bool C1 = true;
template<typename T> concept bool C2 = sizeof(T) <= 4;

template<C1 T>
 struct S {
 template<C2 U> void f(U);
 template<C2 U> void g(U);
 };

template<C1 T> template<C2 U>
 void S<T>::f(U); // OK
template<C1 T> template<typename U>
 void S<T>::g(U); // error: definition does not match

```

The associated constraints in the definition of `g()` do not match those in of its declaration. — *end example* ]

#### 14.5.4 Friends

[temp.friend]

- <sup>1</sup> Add the following paragraphs after C++ §14.5.4/9.
- <sup>2</sup> A *constrained friend* of a class or class template is a constrained class template, constrained function template, a constrained ordinary or generic (non-member) function definition. [ *Example*: When *c* is a type concept, all of the following are valid constrained friend declarations.

```
template<typename T>
struct X {
 template<C U>
 friend void f(X x, U u) { } // Constrained function template

 template<C W>
 friend struct Z { }; // Constrained class template

 friend bool operator==(X a, X b) // Constrained ordinary function
 requires C<T>() { return true; }

 friend void g(X a, C b) { } // Constrained generic function
};
```

Note that *g* is a generic function because the parameter *b* has a *constrained-type-specifier*. — *end example* ]

- <sup>3</sup> A non-template friend function shall not be constrained unless the function's parameter or result type depends on a template parameter. [ *Example*:

```
template<typename T>
struct S {
 friend void f(int n) requires C<T>(); // Error: cannot be constrained
};
```

— *end example* ]

- <sup>4</sup> A constrained non-template friend function shall not declare a specialization. [ *Example*:

```
template<typename T>
struct S {
 friend void f<>(T x) requires C<T>(); // Error: declares a specialization

 friend void g(T x) requires C<T>() { } // OK: does not declare a specialization
};
```

— *end example* ]

- <sup>5</sup> As with constrained member functions, constraints on non-template friend functions are not instantiated during class template instantiation.

#### 14.5.5 Class template partial specialization

[temp.class.spec]

After paragraph 3, insert the following, which explains constrained partial specializations.

- <sup>4</sup> A class template partial specialization may be constrained (14). [ *Example*:

```
template<typename T> concept bool C = requires (T t) { t.f(); };
template<typename T> concept bool N = N > 0;

template<C T1, C T2, N I> class A<T1, T2, I>; // #6
template<C T, N I> class A<int, T*, I>; // #7
```

— *end example* ]

Modify the 3rd item in the list of paragraph 8 to allow constrained class template partial specializations like #6. Note that all other items in that list are elided.



<sup>8</sup> Within the argument list of a class template partial specialization, the following restrictions apply:

- ...
- In an unconstrained class template partial specialization, the argument list of the specialization shall not be identical to the implicit argument list of the primary template.
- ...

9

#### 14.5.5.1 Matching of class template partial specializations

[temp.class.spec.match]

Modify paragraph 2; constraints must be satisfied in order to match a partial specialization. Add the example given here to the (omitted) example in the original document.

<sup>2</sup> A partial specialization matches a given actual template argument list if the template arguments of the partial specialization can be deduced from the actual template argument list (C++ §14.8.2) and the deduced template arguments satisfy the constraints of the partial specialization, if any (14.9). [ Example:

```
struct S { void f(); };
```

```
A<S, S, 1> a6; // uses #6
```

```
A<S, int, 2> a7; // error: constraints not satisfied
```

```
A<int, S*, 3> a8; // uses #7
```

— end example ]

#### 14.5.5.2 Partial ordering of class template specializations

[temp.class.order]

Modify paragraph 1 so that constraints are considered in the partial ordering of class template specializations. Add the example at the end of this paragraph to the (omitted) example in the original document.

<sup>1</sup> For two class template partial specializations, the first is at least as specialized as the second if, given the following rewrite to two function templates, the first function template is at least as specialized as the second according to the ordering rules for function templates (C++ §14.5.6.2):

- the first function template has the same template parameters and associated constraints as the first partial specialization and has a single function parameter whose type is a class template specialization with the template arguments of the first partial specialization, and
- the second function template has the same template parameters and associated constraints as the second partial specialization and has a single function parameter whose type is a class template specialization with the template arguments of the second partial specialization.

[ Example:

```
template<l;typename T> concept bool C = requires (T t) { t.f(); };
template<l;typename T> concept bool D = C<l;T> && requires (T t) { t.f(); };
```

```
template<typename T> class S { };
template<C T> class S<T> { }; // #1
template<D T> class S<T> { }; // #2
```

```
template<C T> void f(S<T>); // A
template<D T> void f(S<T>); // B
```

The partial specialization #2 is be more specialized than #1 for template arguments that satisfy both constraints because B is more specialized than A. — end example ]

## 14.5.6 Function templates

[temp.fct]

### 14.5.6.1 Function template overloading

[temp.over.link]

Modify paragraph 6 to account for constraints on function templates.

- <sup>6</sup> ~~Two function templates are *equivalent* if they are declared in the same scope, have the same name, have identical template parameter lists, and have return types and parameter lists that are equivalent using the rules described above to compare expressions involving template parameters.~~

Two function templates are *equivalent* if they are:

- declared in the same scope,
- have the same name,
- have identical template parameter lists,
- have return types and parameter lists that are equivalent using the rules described above to compare expressions involving template parameters, and
- have associated constraints that are equivalent using the rules described in to compare constraints.

Two function templates are *functionally equivalent* if they are equivalent except that ~~one or more expressions that involve template parameters in the return types and parameter lists are functionally equivalent using the rules described above to compare expressions involving template parameters~~

- one or more expressions that involve template parameters in the return types and parameter lists are functionally equivalent using the rules described above to compare expressions involving template parameters, or if not that,
- the two function templates have constraints that are functionally equivalent but not equivalent, using the rules described in to describe the comparison of constraints.

If a program contains declarations of function templates that are functionally equivalent but not equivalent, the program is ill-formed; no diagnostic is required.

### 14.5.6.2 Partial ordering of function templates

[temp.func.order]

Modify paragraph 2 to include constraints in the partial ordering of function templates.

- <sup>2</sup> Partial ordering selects which of two function templates is more specialized than the other by transforming each template in turn (see next paragraph) and performing template argument deduction using the function type. The deduction process determines whether one of the templates is more specialized than the other. If so, the more specialized template is the one chosen by the partial ordering process. If both deductions succeed, the partial ordering selects the more constrained template as described by the rules in 14.9.3.

## 14.5.7 Alias templates

[temp.alias]

Insert the following after paragraph 2.

- <sup>3</sup> If the alias template is constrained, and all template arguments are non-dependent, the *template-arguments* shall satisfy the template's associated constraints (14.9). [ *Example:*

```
template = false;
```

```
template using Ptr = T*;
```

```
Ptr p; // error: constraints not satisfied.
```

— *end example* ]

## 14.7 Template instantiation and specialization

[temp.spec]

### 14.7.1 Implicit instantiation

[temp.inst]

Add the following paragraph after paragraph 1 in order to explain the how constrained members are instantiated.

- <sup>2</sup> When a constrained member of a class is instantiated, new constraints for the instantiated declaration are formed by substituting the template arguments into the associated constraints of that member. The resulting expression is not evaluated after this substitution. If the substitution fails, the program is ill-formed. [ *Note*: The evaluation of constraints happens during lookup or overload resolution (13). Preserving the spelling of the substituted constraint also allows constrained member function to be partially ordered by those constraints according to the rules in 14.9. — *end note* ] [ *Example*:

```
template<typename T> concept bool C = sizeof(T) > 2;
template<typename T> concept bool D = C && sizeof(T) > 4;

template<typename T> struct S {
 S() requires C<T> { } // #1
 S() requires D<T> { } // #2
};

S<char> s1; // error: no matching constructor
S<char[8]> s2; // OK: calls #2
```

The instantiation of `S<char>` produces a class template specialization having the constructors, `S<char>::S()` requires `C<char>` and `S<char>::S()` requires `D<char>`. Even though neither constructor will be selected by overload resolution, they remain a part of the class template specialization. This also has the effect of suppressing the implicit generation of a default constructor (C++ §12.1). The default constructor invoked by the declaration of `s2` is the more constrained because the constraint `D<char[8]>` subsumes `C<char[8]>`. — *end example* ]

### 14.7.2 Explicit instantiation

[temp.explicit]

Add the following paragraphs to this section. These require an explicit instantiation of a constrained template to satisfy the template's associated constraints.

- <sup>14</sup> If the explicit instantiation names a class template specialization or variable template specialization of a constrained template, then the *template-arguments* in the *template-id* of the explicit instantiation shall satisfy the template's associated constraints (14.9). [ *Example*:

```
template<typename T> concept bool C = sizeof(T) == 1;

template<C T> struct S { };

template S<char>; // OK
template S<char[2]>; // error: constraints not satisfied
```

— *end example* ]

- <sup>15</sup> An explicit instantiation whose *template-name* names a set of overloaded function template refers to exactly one in that set. Remove from that set all function templates for which the template arguments of the explicit instantiation do not match (14.4), cannot be deduced (), have different parameter-type-lists, and whose constraints are not satisfied by the template arguments. The partial ordering of the remaining function templates determines the template to which the specialization refers (14.5.6.2). If no function template is found, or if multiple function templates are found, the program is ill-formed. [ *Example*:

```
template<typename T> concept bool C = requires (T t) { -t; };
```

```
template<C T> void f(T) { } // #1
template<typename T> void g(T) { } // #2
template<C T> void g(T) { } // #3
```

```
template void f(int); // OK: refers to #1
template void f(void*); // error: no matching template
template void g(int); // OK: refers to #3
template void g(void*); // OK: refers to #2
```

— end example ]

### 14.7.3 Explicit specialization

[temp.expl.spec]

Insert the following paragraphs after paragraph 12. These require an explicit specialization to satisfy the constraints of the primary template.

- <sup>12</sup> The *template-arguments* in the *template-id* of an explicit specialization of a constrained class template or constrained variable template shall satisfy the associated constraints of that template (14.9). [ Example:

```
template<typename T> concept bool C = sizeof(T) == 1;

template<C T> struct S { };

template<> S<char> { }; // OK
template<> S<char[2]> { }; // error: constraints not satisfied
```

— end example ]

- <sup>13</sup> An explicit specialization whose *template-name* names a set of overloaded function template refers to exactly one in that set. The function template referred to by an explicit specialization is the same function template as an explicit instantiation with the same *template-name template-arguments* (14.7.2). [ Note: An explicit specialization cannot refer to a constrained function template whose associated constraints are not satisfied (14.9). — end note ] [ Example:

```
template void f(T); // #1
template void g(T); // #2
template void g(T); // #3

template<> void f(int); // OK: refers to #1
template<> void f(void*); // error: no matching template
template<> void g(int); // OK: refers to #3
template<> void g(void*); // OK: refers to #2
```

— end example ]

## 14.8 Function template specializations

[temp.fct.spec]

### 14.8.2 Template argument deduction

[temp.deduct]

Add the following sentences to the end of paragraph 5. This defines the substitution of template arguments into a function template's associated constraints. Note that the last part of paragraph 5 has been duplicated in order to provide context for the addition.

- <sup>5</sup> When all template arguments have been deduced or obtained from default template arguments, all uses of template parameters in the template parameter list of the template and the function type are replaced with the corresponding deduced or default argument values. If the substitution results in an invalid type, as described above, type deduction fails. Additionally, if the function template has associated constraints (14), substitute the template arguments into the constraints

without evaluating the result. If this substitution results in an invalid type, then the resulting expression is defined to be false. The resulting constraints are associated with the function template specialization. [ Note: The constraints associated with the function template specialization are evaluated in order to determine if the specialization is a viable candidate (13.3.1). — end note ]

Add the following section after 14.8. This section defines *constraint-expressions*, their normalization and composition, the equivalence of constraints, and their partial ordering.

## 14.9 Template constraints

[temp.constr]

### 14.9.1 Constraint expressions

[temp.constr.expr]

- <sup>1</sup> Certain contexts require expressions that can be transformed into constraints through the process of normalization.

*constraint-expression:*  
*logical-or-expression*

- <sup>2</sup> A *constraint-expression*  $E$  is *normalized* by forming a constraint (14.9) that is composed of a combination of only logical operators and atomic constraints. That transformation is defined as follows:

- The normalization of an expression of the form  $(P)$  is the normalization of  $P$ .
- The normalization of an expression of the form  $P \ || \ Q$  is the disjunction of the normalization of  $P$  and the normalization of  $Q$ . If, in the expression  $P \ || \ Q$ , lookup of operator  $||$  finds a user-defined function, the program is ill-formed.
- The normalization of an expression of the form  $P \ \&\& \ Q$  is the conjunction of the normalization of  $P$  and the normalization of  $Q$ . If, in the expression  $P \ \&\& \ Q$ , lookup of operator  $\&\&$  finds a user-defined function, the program is ill-formed.
- The normalization of a function call of the form  $C\langle A_1, A_2, \dots, A_n \rangle()$  where  $A_1, A_2, \dots, A_n$  is a sequence of template arguments and  $c$  names a function concept (7.1.7) is defined as follows: Let  $E$  be the expression returned by the function concept  $c$ , and let  $s$  be the result of substituting the template arguments into that expression. The resulting constraint is the normalization of  $s$ .
- The normalization of a *id-expression* of the form  $C\langle A_1, A_2, \dots, A_n \rangle$  where  $A_1, A_2, \dots, A_n$  is a sequence of template arguments and  $c$  names a variable concept (7.1.7) is defined as follows: Let  $E$  be the initializer of the variable concept  $c$ , and let  $s$  be the result of substituting the template arguments into that expression. The resulting constraint is the normalization of  $s$ .
- The normalization of a *requires-expression* is defined to be the conjunction of constraints introduced by the body of that expression (5.1.3).
- Otherwise, the expression shall be an predicate constraint  $()$ .

[ Note: A *constraint-expression* defines a subset of constant expressions over which certain logical implications can be deduced during translation. The prohibition against user-defined logical operators is intended to prevent the subversion of the underlying logic necessary partially order constraints (14.9.3). — end note ]

[ Example:

```
template<typename T> concept bool C1() { return sizeof(T) == 1; }
template<typename T> concept bool C2 = C1<T>() && 1 == 2; }
template<typename T> concept bool C3 = requires () { typename T::type; };

// Expression // Constraint
C2<char> sizeof(char) == 1 && 1 == 2
C3<int> /* valid-type for int::type */
3 + 4 // error: not a constraint
```

In the normalized constraints, the expressions `sizeof(char) == 1`, and `1 == 2` are predicate constraints. The concept `c4` is normalized to a single valid type constraint for the (ill-formed) type `int::type`. — end example ]

- <sup>3</sup> Two *constraint-expressions* are considered equivalent if two function definitions containing the expressions would satisfy the one definition rule  $()$ , except that the tokens used to name template parameters may differ as long as a token used to name a template parameter in one expression is replaced by another token that

names the same template parameter in the other expression, and the tokens used to name names of other entities may differ only if those names refer to the same set of declarations. [ *Example*:

```
template<typename T> concept bool C = sizeof(T) == 1;

template<typename T> requires C<T> void f(); // #1
template<typename U> requires C<U> void f(); // OK: redeclaration of #1

namespace N1 { template<typename T> concept bool C1 = true; }
namespace N2 { template<typename T> concept bool C2 = true; }

template<typename T> requires N1::C1<T> void g(); // #2
template<typename T> requires N1::C1<T> void h(); // #3
using N1::C1;
template<typename T> requires C1<T> void g(); // OK: redeclaration of #2
using namespace N2;
template<typename T> requires C2<T> void h(); // OK: redeclaration of #3
```

— *end example* ] Two *constraint-expressions* that are not equivalent are functionally equivalent if, for any given set of template arguments, the evaluation of the expression results in the same value. A *constraint-expression* or subexpression thereof of the form (E) is not equivalent to E, but the two expressions are functionally equivalent.

[ *Example*:

```
void f() requires true || 1 == 2; // #1
void f() requires true || (1 == 2); // not equivalent but functionally equivalent
```

— *end example* ]

## 14.9.2 Constraint language

[[temp.constr.lang](#)]

- <sup>1</sup> The *constraint language* defines the abstract syntax, evaluation, and subsumption of constraints introduced by *constraint-expressions* and *requires-expressions*.
- <sup>2</sup> A *constraint* is a sequence of logical operators and operands that specify requirements on template arguments.
- <sup>3</sup> *Constraint checking* is the processing of substituting non-dependent template arguments (C++ §14.6.2) into a constraint for the purpose of determining if the constraint is satisfied. After substitution, a constraint is *satisfied* if and only if all of its sub-constraints are satisfied according to the evaluation rules described in this section. If the substitution of template arguments into a constraint fails, that constraint is not satisfied. [ *Note*: Substitution into a constraint may yield a well-formed constraint that contains ill-formed expressions or types. This may happen, for example, in the implicit instantiation of a class template specialization (14.7.1). — *end note* ]
- <sup>4</sup> A constraint P is said to *subsume* another constraint Q if, informally, it can be determine that P implies Q, up to the equivalence of expressions and types in P and Q. [ *Note*: Subsumption does not determine, for example, if the predicate constraint () N % 2 == 1 subsumes N & 1 for some integral template argument, N. — *end note* ]
- <sup>5</sup> [ *Note*: The following sections describe the logical operators and operands of the constraint language, including the their evaluation and subsumption rules. — *end note* ]

### 14.9.2.1 Conjunction

[[temp.constr.conj](#)]

- <sup>1</sup> A *conjunction* is a logical operator taking two operands. A conjunction of constraints is satisfied if and only if both operands are satisfied.
- <sup>2</sup> A conjunction of the constraints P and Q subsumes another constraint R if and only if P subsumes R, Q subsumes R, or both subsume R.

### 14.9.2.2 Disjunction

[temp.constr.disj]

- <sup>1</sup> A *disjunction* is a logical operator taking two operands. A disjunction of constraints is satisfied if and only if either operand is satisfied or both operands are satisfied.
- <sup>2</sup> A disjunction of the constraints P and Q subsumes another constraint R if and only if P subsumes R and Q subsumes R.

### 14.9.2.3 Atomic constraints

[temp.constr.atom]

- <sup>1</sup> Any constraint that is not a conjunction or disjunction is an *atomic constraint*.
- <sup>2</sup> An atomic constraint P subsumes a disjunction of the constraints Q and R if and only if P subsumes Q, P subsumes R, or both.
- <sup>3</sup> An atomic constraint P subsumes a conjunction of the constraints Q and R if and only if P subsumes Q and P subsumes R.

### 14.9.2.4 Predicate constraints

[temp.constr.pred]

- <sup>1</sup> A *predicate constraint* is an atomic constraint that evaluates a prvalue constant expression of type bool (C++ §5.19). The constraint is satisfied if and only if the expression evaluates to true. [ *Note:* Predicate constraints allow the definition of template requirements in terms of constant expressions. This enables constraints on non-type arguments, template template arguments, and also the definition of constraints as metaprograms on type arguments and template argument packs. — *end note* ] [ *Example:*

```
template<typename T> concept bool C = sizeof(T) == 4 && !true;
```

Here, `sizeof(T) == 4` and `!true` are predicate constraints required by the concept, C. — *end example* ]

- <sup>2</sup> A predicate constraint P subsumes another predicate constraint Q if and only if P and Q are equivalent *constraint-expressions* (14.9.1).  
[ *Example:* The predicate `M >= 0` does not subsume the predicate `M > 0` because they are not equivalent *constraint-expressions*. — *end example* ]

### 14.9.2.5 Expression constraints

[temp.constr.expr]

- <sup>1</sup> An *expression constraint* is an atomic constraint that specifies a requirement the formation of a an *expression*, E. It is satisfied if E is non-dependent, meaning that the substitution yielding E did not fail. Within an expression constraint, E is an unevaluated operand (5). [ *Note:* An expression constraint is introduced by the *expression* in either a *simple-requirement* (5.1.3.1) or *compound-requirement* (5.1.3.3) of a *requires-expression*. — *end note* ]  
[ *Example:* The concept C introduces a expression constraint for the expression `++t`.

```
template<typename T> concept bool C = requires (T t) { ++t; };
```

The type argument `int` satisfies this constraint because the the expression `++t` is valid after substituting `int` for `T`. — *end example* ]

- <sup>2</sup> An expression constraint P subsumes another expression constraint Q if and only if The *expressions* of P and Q are equivalent (14.5.6.1).

### 14.9.2.6 Type constraints

[temp.constr.type]

- <sup>1</sup> A *type constraint* is an atomic constraint that specifies a requirement on the formation of a type, T. It is satisfied if and only T is non-dependent, meaning that the substitution yielding T did not fail. [ *Note:* A type constraint is introduced by the *type-id* in a *type-requirement* of a *requires-expression* (5.1.3.2). — *end note* ]  
[ *Example:* The concept C introduces a type constraint for the type name `T::type`.

```
template<typename T> concept bool C =
requires (T t) {
```



```
typename T::type;
};
```

The type `int` does not satisfies this constraint because substitution of that type into the constraint results in a substitution failure because `int::type` is ill-formed. — *end example* ]

- <sup>2</sup> A type requirement that names a class template specialization does not require the completeness of that type; class templates are not instantiated when the constraint is checked (14.7.1).
- <sup>3</sup> A type requirement *P* subsumes another type requirement *Q* if and only if the types in *P* and *Q* are equivalent (C++ §14.4).

#### 14.9.2.7 Implicit conversion constraints

[temp.constr.conv]

- <sup>1</sup> A *implicit conversion constraint* is an atomic constraint that specifies a requirement on the implicit conversion of an *expression* (call it *E*) to a type (call it *T*). The constraint is satisfied if and only if *E* is implicitly convertible to *T* (C++ §4). [ *Note*: A conversion constraint is introduced by a *trailing-return-type* in a *compound-requirement* when the *trailing-type-specifier-seq* contains no placeholders (5.1.3.3). — *end note* ]

[ *Example*:

```
template<typename T> concept bool C =
requires (T a, T b) {
 { a == b } -> bool;
};
```

The *compound-requirement* in the *requires-expression* of *C* introduces two atomic constraints: an expression constraint for `a == b` and the conversion constraint that the expression `a == b` is implicitly convertible to `bool`. — *end example* ]

- <sup>2</sup> An implicit conversion constraint *P* subsumes another conversion constraint *Q* if and only if the *expressions* of *P* and *Q* are equivalent (14.5.6.1) and the types of *P* and *Q* are equivalent (C++ §14.4).

#### 14.9.2.8 Argument deduction constraints

[temp.constr.deduct]

- <sup>1</sup> An *argument deduction constraint* is an atomic constraint that specifies a requirement on the usability of an *expression* (call it *E*) as an argument to an invented function template (call it *F*) that has a single parameter whose type (call it *T*) is written in terms of the function's template parameters. The constraint is satisfied if and only if *F* is selected by overload resolution for the call *F*(*E*) (13.3). [ *Note*: Overload resolution selects *F* only when template argument deduction succeeds and *F*'s associated constraints are satisfied. — *end note* ] [ *Note*: An argument deduction constraint is introduced by a *trailing-return-type* in a *compound-requirement* when the *trailing-type-specifier-seq* contains at least one placeholder (5.1.3.3). — *end note* ] [ *Example*: The concept *D* introduces an argument deduction constraint for the expression `*t`.

```
template<typename T> concept bool C = requires (T t) { ++t; }
template<typename T> concept bool D = requires (T t) { *t -> const C&; }
```

When determining if *D* is satisfied, overload resolution is performed for the call `g(*t)` against the following invented function:

```
template<typename T> requires C<T> void g(const T&);
```

— *end example* ]

- <sup>2</sup> An argument deduction constraint *P* subsumes another argument deduction constraint *Q* if and only if the *expressions* of *P* and *Q* are equivalent (14.5.6.1), and the types of *P* and *Q* are equivalent (C++ §14.4).

#### 14.9.2.9 Constant expression constraints

[temp.constr.constexpr]

- <sup>1</sup> A *constant expression constraint* is an atomic constraint that specifies a requirement that an *expression* (call it *E*) can be evaluated during translation. The constraint is satisfied if and only if *E* is a prvalue constant expression (C++ §5.19). [ *Note*: A constant expression constraint determines if an expression can be



evaluated during translation for specific `constexpr` arguments. It cannot be used to determine if an expression is evaluated during translation for all possible arguments. — *end note* ] [ *Note*: Constant expression constraints are introduced by a *compound-requirement* that includes the `constexpr` specifier (5.1.3.3). — *end note* ] [ *Example*:

```
template<typename T, int N> concept bool C =
requires() {
 constexpr { T(N) }; // determines if T(N) is a constant expression
};
```

— *end example* ]

- <sup>2</sup> A constant expression constraint *P* subsumes another constant expression constraint *Q* if and only if the expressions of *P* and *Q* are equivalent (14.5.6.1).

#### 14.9.2.10 Exception constraints

[[temp.constr.noexcept](#)]

- <sup>1</sup> An *exception constraint* is an atomic constraint that specifies a requirement that an *expression* (call it *E*) does not throw an exception. It is satisfied if and only if the expression `noexcept(E)` is true (C++ §5.3.7). [ *Note*: Constant expression constraints are introduced by a *compound-requirement* that includes the `noexcept` specifier (5.1.3.3). — *end note* ]
- <sup>2</sup> An exception constraint *P* subsumes another exception constraint *Q* if and only if the *expressions* of *P* and *Q* are equivalent (14.5.6.1).

#### 14.9.3 Partial ordering of constraints

[[temp.constr.order](#)]

- <sup>1</sup> The subsumption relation defines a partial ordering on constraints. This partial ordering is used to determine
  - the best viable candidate of non-template functions (13.3.2),
  - the address of a non-template function (13.4),
  - to determine which of a set of non-template functions are defined (8.3.5),
  - the partial ordering of class template specializations (14.5.5.2),
  - the partial ordering of function templates (14.5.6.2), and
  - the matching of template template arguments (14.4.1).

With the exception of matching template template arguments, the partial ordering applies to declarations. In each case, several declarations may have equivalent conversion sequences, signatures, or types. These declarations can be partially ordered by their constraints.

- <sup>2</sup> A constrained declaration *D1* is *more constrained* than another constrained declaration *D2* if *D1*'s associated constraints subsume, but are not subsumed by those of *D2*. A constrained declaration is more constrained than an unconstrained declaration.
- <sup>3</sup> [ *Example*:

```
template<typename T> concept bool C1 = requires(T t) { ++t; };
template<typename T> concept bool C2 = C1<T> && requires(T t) { *t; };

template<C1 T> void f(T); // #1
template<C2 T> void f(T); // #2

f(0); // selects #1
f((int*)0); // selects #2
```

When both candidates are viable, overload resolution will select #1 because the constraints of *C2* subsumes those of *C1*, — *end example* ]