torch.quantized_max_pool1d#

https://pytorch.org/docs/stable/generated/torch.quantized_max_pool1d.html#to

Description:

Applies a 1D max pooling over an input quantized tensor composed of several input planes. input (Tensor) – quantized tensor kernel_size (list of int) – the size of the sliding window stride (list of int, optional) – the stride of the sliding window padding (list of int, optional) – padding to be added on both sides, must be >= 0 and <= kernel_size / 2

Function Signature

```
torch.quantized_max_pool1d(input, kernel_size, stride=[],
padding=0, dilation=1, ceil_mode=False) → Tensor#

Parameters

Returns

Return type
```

Returns:

Tensor

Code Examples

```
>>> qx = torch.quantize_per_tensor(torch.rand(2, 2), 1.5, 3,
torch.quint8)
>>> torch.quantized_max_pool1d(qx, [2])
tensor([[0.0000],
        [1.5000]], size=(2, 1), dtype=torch.quint8,
    quantization_scheme=torch.per_tensor_affine, scale=1.5,
zero_point=3)
```

Detailed Documentation

Documentation

Applies a 1D max pooling over an input quantized tensor composed of several input planes.

input (Tensor) – quantized tensor

kernel_size (list of int) – the size of the sliding window

stride (list of int, optional) – the stride of the sliding window

padding (list of int, optional) – padding to be added on both sides, must be >= 0 and <= kernel_size / 2

dilation (list of int, optional) – The stride between elements within a sliding window, must be > 0. Default 1

ceil_mode (bool, optional) – If True, will use ceil instead of floor to compute the output shape. Defaults to False.

A quantized tensor with max_pool1d applied.

Generated on 10/26/2025 | **PyTorch** Documentation Scraper