LazyConv2d#

https://pytorch.org/docs/stable/generated/torch.nn.LazyConv2d.html#torch.nn.

Description:

A torch.nn.Conv2d module with lazy initialization of the in_channels argument. The in_channels argument of the Conv2d that is inferred from the input.size(1). The attributes that will be lazily initialized are weight and bias. Check the torch.nn.modules.lazy.LazyModuleMixin for further documentation on lazy modules and their limitations. out_channels (int) – Number of channels produced by the convolution kernel_size (int or tuple) – Size of the convolving kernel

Function Signature

```
class torch.nn.LazyConv2d(out_channels, kernel_size,
stride=1, padding=0, dilation=1, groups=1, bias=True,
padding_mode='zeros', device=None, dtype=None)[source]#

Parameters

cls_to_become[source]#
```

Notes & Warnings

NOTE See also torch.nn.Conv2d and torch.nn.modules.lazy.LazyModuleMixin

Detailed Documentation

Documentation

A torch.nn.Conv2d module with lazy initialization of the in_channels argument.

The in_channels argument of the Conv2d that is inferred from the input.size(1). The attributes that will be lazily initialized are weight and bias.

Check the torch.nn.modules.lazy.LazyModuleMixin for further documentation on lazy modules and their limitations.

out_channels (int) – Number of channels produced by the convolution

kernel_size (int or tuple) – Size of the convolving kernel

stride (int or tuple, optional) – Stride of the convolution. Default: 1

padding (int or tuple, optional) – Zero-padding added to both sides of the input. Default: 0

dilation (int or tuple, optional) – Spacing between kernel elements. Default: 1

groups (int, optional) – Number of blocked connections from input channels to output channels. Default: 1

bias (bool, optional) – If True, adds a learnable bias to the output. Default: True

padding_mode (str, optional) – 'zeros', 'reflect', 'replicate' or 'circular'. Default: 'zeros'

torch.nn.Conv2d and torch.nn.modules.lazy.LazyModuleMixin