tf.nondifferentiable_batch_function Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/nondifferentiable_batch_function

> *Batches the computation done by the decorated function.*

Function Signatures

```
tf.nondifferentiable_batch_function( num_batch_threads,
max_batch_size, batch_timeout_micros,
allowed_batch_sizes=None, max_enqueued_batches=10,
autograph=True, enable_large_batch_splitting=True )
@batch_function(1, 2, 3) def layer(a): return tf.matmul(a, a)
b = layer(w)
```

Code Examples

```
tf.nondifferentiable_batch_function(
num_batch_threads,
max_batch_size,
batch_timeout_micros,
allowed_batch_sizes=None,
max_enqueued_batches=10,
autograph=True,
enable_large_batch_splitting=True
)
```


```
tf.nondifferentiable_batch_function(
num_batch_threads,
max_batch_size,
batch_timeout_micros,
allowed_batch_sizes=None,
max_enqueued_batches=10,
autograph=True,
enable_large_batch_splitting=True
)
```


```
@batch_function(1, 2, 3)
def layer(a):
return tf.matmul(a, a)
b = layer(w)
```


```
@batch_function(1, 2, 3)
def layer(a):
return tf.matmul(a, a)
b = layer(w)
```

Documentation

Batches the computation done by the decorated function.

View aliases

Compat aliases for migration

See
Migration guide for
more details.

tf.compat.v1.nondifferentiable_batch_function

So, for example, in the following code

if more than one session.run call is simultaneously trying to compute b
the values of w will be gathered, non-deterministically concatenated
along the first axis, and only one thread will run the computation. See the
documentation of the Batch op for more details.

Assumes that all arguments of the decorated function are Tensors which will
be batched along their first dimension.

SparseTensor is not supported. The return value of the decorated function
must be a Tensor or a list/tuple of Tensors.

Returns