

AutoTokenizer

https://huggingface.co/docs/transformers/main/en/model_doc/auto#transformers

Detailed Documentation

```
class <span class="code-  
inline">transformers.AutoConfigtransformers.AutoConfighttps</s
```

class

`transformers.AutoConfigtransformers.AutoConfighttps` ://github.com/huggir

This is a generic configuration class that will be instantiated as one of the configuration classes of the library

when created with the `[ from_pretrained ()]`
(/docs/transformers/main/en/model_doc/auto# `transformers.AutoConfig.from_`
class method.

This class cannot be instantiated directly using `__init__ ()` (throws an error).

`from_pretrainedtransformers.AutoConfig.from_pretrainedhttps://github.com/hugg`
`"pretrained_model_name_or_path", "val": ": typing.Union[str, os.PathLike[str]]",`
`{"name": "**kwargs", "val": ""}- **pretrained_model_name_or_path** ( str or`

`os.PathLike`) --

- A string, the **model id** of a pretrained model configuration hosted inside a model repo on
- A path to a **directory** containing a configuration file saved using the

`[ save_pretrained ()]`

(/docs/transformers/main/en/main_classes/configuration# `transformers.PreTrai`

method, or the `[ save_pretrained ()]`

(/docs/transformers/main/en/main_classes/model# `transformers.PreTrainedMoc`

method,

e.g., `./my_model_directory/`.

- A path or url to a saved configuration JSON **file**, e.g.,

`from_pretrainedtransformers.AutoConfig.from_pretrainedhttps://g`

`from_pretrainedtransformers.AutoConfig.from_pretrainedhttps://github.com/hugg`

`"pretrained_model_name_or_path", "val": ": typing.Union[str, os.PathLike[str]]"},`

`{"name": "**kwargs", "val": ""}- **pretrained_model_name_or_path** ( str or`

`os.PathLike`) --

- A string, the **model id** of a pretrained model configuration hosted inside a model repo on
- A path to a **directory** containing a configuration file saved using the

`[ save_pretrained ()]`

(/docs/transformers/main/en/main_classes/configuration# `transformers.PreTrai`

method, or the `[ save_pretrained ()]`

(/docs/transformers/main/en/main_classes/model# transformers.PreTrainedModel) method,

e.g., `./my_model_directory/`.

- A path or url to a saved configuration JSON *file*, e.g.,

`./my_model_directory/configuration.json`.

- `**cache_dir**` (`str` or `os.PathLike`, *optional*) --

Path to a directory in which a downloaded pretrained model configuration should be cached if the

standard cache should not be used.

`transformers.AutoConfig.register`https://github.com/huggingface/transformers/blob/main/src/transformers/configuration_utils.py

`transformers.AutoConfig.register`https://github.com/huggingface/transformers/blob/main/src/transformers/configuration_utils.py
"model_type", "val": ""}, {"name": "config", "val": ""}, {"name": "exist_ok", "val": " = False"}]- `**model_type**` (`str`) -- The model type like "bert" or "gpt".

- `**config**` (`PreTrainedConfig`)
(/docs/transformers/main/en/main_classes/configuration# transformers.PreTrainedConfig)
-- The config to register.

Register a new configuration for this class.

class <span class="code-

inline">transformers.AutoTokenizertransformers.AutoTokenizerht

class

`transformers.AutoTokenizertransformers.AutoTokenizerhttps://github.com,`

This is a generic tokenizer class that will be instantiated as one of the tokenizer classes of the library when

created with the `[AutoTokenizer.from_pretrained()]` (`/docs/transformers/main/en/model_doc/auto#transformers.AutoTokenizer.from_pretrained()`) class method.

This class cannot be instantiated directly using `__init__()` (throws an error).

`from_pretrainedtransformers.AutoTokenizer.from_pretrainedhttps://github.com/huggingface/transformers/blob/main/src/transformers/models/auto/tokenization_auto.py#L111-L112`
"pretrained_model_name_or_path", "val": ""}, {"name": "inputs", "val": ""}, {"name": "kwargs", "val": ""}- **pretrained_model_name_or_path** (`str` or `os.PathLike`) --

- A string, the *model id* of a predefined tokenizer hosted inside a model repo on huggingface.co.
- A path to a *directory* containing vocabulary files required by the tokenizer, for instance saved

using the `[save_pretrained()]` (`/docs/transformers/main/en/internal/tokenization_utils#transformers.PreTrainedTokenizer.save_pretrained()`) method, e.g., `./my_model_directory/`.

- A path or url to a single saved vocabulary file if and only if the tokenizer only requires a

single vocabulary `file` (like Bert or XLNet), e.g.:
`./my_model_directory/vocab.txt`. (Not

from_pretrained transformers.AutoTokenizer.from_pretrainedhttps

from_pretrained transformers.AutoTokenizer.from_pretrainedhttps://github.com/hu
 "pretrained_model_name_or_path", "val": ""}, {"name": "inputs", "val": ""},
 {"name": "kwargs", "val": ""}] - **pretrained_model_name_or_path** (`str` or
`os.PathLike`) --

- A string, the *model id* of a predefined tokenizer hosted inside a model repo on huggingface.co.
- A path to a *directory* containing vocabulary files required by the tokenizer, for instance saved

using the `[ save_pretrained ()]`
 (/docs/transformers/main/en/internal/tokenization_utils# transformers.PreTrain
 method, e.g., `./my_model_directory/`.

- A path or url to a single saved vocabulary file if and only if the tokenizer only requires a

single vocabulary `file` (like Bert or XLNet), e.g.:
`./my_model_directory/vocab.txt`. (Not

applicable to all derived classes)

- **inputs** (additional positional arguments, *optional*) --

Will be passed along to the Tokenizer `__init__()` method.

- **config** ([PreTrainedConfig]
(/docs/transformers/main/en/main_classes/configuration# `transformers.PreTrainedConfig`)
optional) --

register transformers.AutoTokenizer.register(<https://github.com/huggingface/transformers>)

```
register(transformers.AutoTokenizer.register(https://github.com/huggingface/transformers),  
        {"config_class": "", {"name": "slow_tokenizer_class", "val": ""}, {"name": "fast_tokenizer_class", "val": ""}, {"name": "exist_ok", "val": False}},  
        config_class=[PreTrainedConfig]  
(/docs/transformers/main/en/main_classes/configuration# transformers.PreTrainedConfig)  
--
```

The configuration corresponding to the model to register.

- **slow_tokenizer_class** (`PretrainedTokenizer`, *optional*) --

The slow tokenizer to register.

- **fast_tokenizer_class** (`PretrainedTokenizerFast`, *optional*) --

The fast tokenizer to register.

Register a new tokenizer in this mapping.

`class`

`transformers.AutoFeatureExtractor`

class

```
transformers.AutoFeatureExtractor
```

This is a generic feature extractor class that will be instantiated as one of the feature extractor classes of the

library when created with the `[AutoFeatureExtractor.from_pretrained()]` (/docs/transformers/main/en/model_doc/auto#transformers.AutoFeatureExtra class method.

This class cannot be instantiated directly using `__init__()` (throws an error).

`from_pretrained`
`transformers.AutoFeatureExtractor.from_pretrained`
<https://github.com>
"pretrained_model_name_or_path", "val": ""}, {"name": "**kwargs", "val": ""}]-
pretrained_model_name_or_path (`str` or `os.PathLike`) --

This can be either:

- a string, the *model id* of a pretrained feature_extractor hosted inside a model repo on
- a path to a *directory* containing a feature extractor file saved using the

```
[ save_pretrained ()]
```

(/docs/transformers/main/en/main_classes/feature_extractor#transformers.Fea method, e.g.,

```
./my_model_directory/
```

`from_pretrainedtransformers.AutoFeatureExtractor.from_pretrain`

```
from_pretrainedtransformers.AutoFeatureExtractor.from_pretrainedhttps://github.
str or os.PathLike ) --
```

This can be either:

- a string, the *model id* of a pretrained feature_extractor hosted inside a model repo on
- a path to a *directory* containing a feature extractor file saved using the

```
[ save_pretrained ()]
```

(/docs/transformers/main/en/main_classes/feature_extractor# `transformers.Fea`
method, e.g.,

```
./my_model_directory/
```

- a path or url to a saved feature extractor JSON *file*, e.g.,

```
./my_model_directory/preprocessor_config.json
```

- *cache_dir* (`str` or `os.PathLike` , *optional*) --

Path to a directory in which a downloaded pretrained model feature extractor should be cached if the

`registertransformers.AutoFeatureExtractor.registerhttps://github.`

```
registertransformers.AutoFeatureExtractor.registerhttps://github.com/huggingface
"config_class", "val": ""}, {"name": "feature_extractor_class", "val": ""}, {"name":
"exist_ok", "val": " = False"]}- **config_class** ([PreTrainedConfig]
(/docs/transformers/main/en/main_classes/configuration# transformers.PreTrai
--
```

The configuration corresponding to the model to register.

- `**feature_extractor_class**` (`FeatureExtractorMixin`) -- The feature extractor to register.0

Register a new feature extractor for this class.

`class` `<span class="code-`

`inline">transformers.AutoImageProcessortransformers.AutoImag`

`class`

```
transformers.AutoImageProcessortransformers.AutoImageProcessorhttps ://
```

This is a generic image processor class that will be instantiated as one of the image processor classes of the

library when created with the `[AutoImageProcessor.from_pretrained ()]`
(/docs/transformers/main/en/model_doc/auto# transformers.AutoImageProcess
class method.

This class cannot be instantiated directly using `__init__()` (throws an error).

```
from_pretrained transformers.AutoImageProcessor.from_pretrained https://github.c
str or
os.PathLike ) --
```

This can be either:

- a string, the *model id* of a pretrained image_processor hosted inside a model repo on
- a path to a *directory* containing a image processor file saved using the

```
[ save_pretrained ()]
```

(/docs/transformers/main/en/internal/image_processing_utils# `transformers.Ima`
method, e.g.,

```
./my_model_directory/.
```

`from_pretrained transformers.AutoImageProcessor.from_pretrained`

`from_pretrained transformers.AutoImageProcessor.from_pretrained https://github.c`
