

tf.autograph.set_verbosity Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/autograph/set_verbosity

Sets the AutoGraph verbosity level.

Function Signatures

```
tf.autograph.set_verbosity( level, alsologtostdout=False )
```

Code Examples

```
tf.autograph.set_verbosity(  
level, alsologtostdout=False  
)
```

```
tf.autograph.set_verbosity(  
level, alsologtostdout=False  
)
```

```
import os  
import tensorflow as tf  
os.environ['AUTOGRAPH_VERBOSITY'] = '5'  
# Verbosity is now 5  
tf.autograph.set_verbosity(0)  
# Verbosity is now 0  
os.environ['AUTOGRAPH_VERBOSITY'] = '1'  
# No effect, because set_verbosity was already called.
```

```
import os  
import tensorflow as tf  
os.environ['AUTOGRAPH_VERBOSITY'] = '5'  
# Verbosity is now 5  
tf.autograph.set_verbosity(0)  
# Verbosity is now 0  
os.environ['AUTOGRAPH_VERBOSITY'] = '1'  
# No effect, because set_verbosity was already called.
```

Documentation

Sets the AutoGraph verbosity level.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.autograph.set_verbosity`

Debug logging in AutoGraph

More verbose logging is useful to enable when filing bug reports or doing more in-depth debugging.

There are two means to control the logging verbosity:

- The `set_verbosity` function
- The `AUTOGRAPH_VERBOSITY` environment variable

The `set_verbosity` function

The `AUTOGRAPH_VERBOSITY` environment variable

`set_verbosity` takes precedence over the environment variable.

For example:

Logs entries are output to absl's
default output,
with INFO level.

Logs can be mirrored to stdout by using the `alsologtostdout` argument.
Mirroring is enabled by default when Python runs in interactive mode.

