

tf.broadcast_dynamic_shape Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/broadcast_dynamic_shape

Computes the shape of a broadcast given symbolic shapes.

Function Signatures

```
tf.broadcast_dynamic_shape( shape_x, shape_y )
```

Code Examples

```
tf.broadcast_dynamic_shape(  
    shape_x, shape_y  
)
```

```
tf.broadcast_dynamic_shape(  
    shape_x, shape_y  
)
```

```
shape_x = (1, 2, 3)  
shape_y = (5, 1, 3)  
tf.broadcast_dynamic_shape(shape_x, shape_y)
```

```
shape_x = (1, 2, 3)
```

```
shape_y = (5, 1, 3)
```

```
tf.broadcast_dynamic_shape(shape_x, shape_y)
```

Documentation

Computes the shape of a broadcast given symbolic shapes.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.broadcast_dynamic_shape`

When `shape_x` and `shape_y` are Tensors representing shapes (i.e. the result of calling `tf.shape` on another Tensor) this computes a Tensor which is the shape of the result of a broadcasting op applied in tensors of shapes `shape_x` and `shape_y`.

This is useful when validating the result of a broadcasting operation when the tensors do not have statically known shapes.

Example:

`## Returns`

`## Raises`