

tf.compat.v1.LMDBReader Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/LMDBReader

A Reader that outputs the records from a LMDB file.

Function Signatures

```
tf.compat.v1.LMDBReader( name=None, options=None )
```

Code Examples

```
tf.compat.v1.LMDBReader(  
    name=None, options=None  
)
```

```
tf.compat.v1.LMDBReader(  
    name=None, options=None  
)
```

```
num_records_produced(  
    name=None  
)
```

```
num_records_produced(  
    name=None  
)
```

```
num_work_units_completed(  
    name=None  
)
```

```
num_work_units_completed(  
    name=None  
)
```

```
read(  
    queue, name=None  
)
```

```
read(  
    queue, name=None  
)
```

Documentation

A Reader that outputs the records from a LMDB file.

Inherits From: ReaderBase

See ReaderBase for supported methods.

Attributes

Methods

num_records_produced

[View source](#)

Returns the number of records this reader has produced.

This is the same as the number of Read executions that have succeeded.

num_work_units_completed

[View source](#)

Returns the number of work units this reader has finished processing.

[View source](#)

Returns the next record (key, value) pair produced by a reader.

Will dequeue a work unit from queue if necessary (e.g. when the Reader needs to start reading from a new file since it has finished with the previous file).

read_up_to

[View source](#)

Returns up to num_records (key, value) pairs produced by a reader.

Will dequeue a work unit from queue if necessary (e.g., when the

Reader needs to start reading from a new file since it has finished with the previous file).

It may return less than num_records even before the last batch.

[View source](#)

Restore a reader to its initial clean state.

restore_state

[View source](#)

Restore a reader to a previously saved state.

Not all Readers support being restored, so this can produce an Unimplemented error.

serialize_state

[View source](#)

Produce a string tensor that encodes the state of a reader.

Not all Readers support being serialized, so this can produce an Unimplemented error.

eager compatibility

Readers are not compatible with eager execution. Instead, please use tf.data to get data into your model.
