

tf.compat.v1.ReaderBase Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/ReaderBase

Base class for different Reader types, that produce a record every step.

Function Signatures

```
tf.compat.v1.ReaderBase( reader_ref, supports_serialize=False
)
```

Code Examples

```
tf.compat.v1.ReaderBase(
reader_ref, supports_serialize=False
)
```

```
tf.compat.v1.ReaderBase(
reader_ref, supports_serialize=False
)
```

```
num_records_produced(
name=None
)
```

```
num_records_produced(  
    name=None  
)
```

```
num_work_units_completed(  
    name=None  
)
```

```
num_work_units_completed(  
    name=None  
)
```

```
read(  
    queue, name=None  
)
```

```
read(  
    queue, name=None  
)
```

Documentation

Base class for different Reader types, that produce a record every step.

Conceptually, Readers convert string 'work units' into records (key, value pairs). Typically the 'work units' are filenames and the records are extracted from the contents of those files. We want a single record produced per step, but a work unit can correspond to many records.

Therefore we introduce some decoupling using a queue. The queue

contains the work units and the Reader dequeues from the queue when it is asked to produce a record (via `Read()`) but it has finished the last work unit.

Raises

Attributes

Methods

`num_records_produced`

[View source](#)

Returns the number of records this reader has produced.

This is the same as the number of `Read` executions that have succeeded.

`num_work_units_completed`

[View source](#)

Returns the number of work units this reader has finished processing.

[View source](#)

Returns the next record (key, value) pair produced by a reader.

Will dequeue a work unit from queue if necessary (e.g. when the Reader needs to start reading from a new file since it has finished with the previous file).

read_up_to

[View source](#)

Returns up to num_records (key, value) pairs produced by a reader.

Will dequeue a work unit from queue if necessary (e.g., when the Reader needs to start reading from a new file since it has finished with the previous file).

It may return less than num_records even before the last batch.

[View source](#)

Restore a reader to its initial clean state.

restore_state

[View source](#)

Restore a reader to a previously saved state.

Not all Readers support being restored, so this can produce an Unimplemented error.

serialize_state

[View source](#)

Produce a string tensor that encodes the state of a reader.

Not all Readers support being serialized, so this can produce an Unimplemented error.

eager compatibility

Readers are not compatible with eager execution. Instead, please use `tf.data` to get data into your model.