

tf.compat.v1.arg_min Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/arg_min

*Returns the index with the smallest value across dimensions of a tensor.
(deprecated)*

Function Signatures

```
tf.compat.v1.arg_min( input: Annotated[Any, tf.raw_ops.Any],  
dimension: Annotated[Any, tf.raw_ops.Any], output_type:  
TV_ArgMin_output_type = tf.dtypes.int64, name=None ) ->  
Annotated[Any, tf.raw_ops.Any]
```

Code Examples

```
tf.compat.v1.arg_min(  
input: Annotated[Any, tf.raw_ops.Any],  
dimension: Annotated[Any, tf.raw_ops.Any],  
output_type: TV_ArgMin_output_type = tf.dtypes.int64,  
name=None  
) -> Annotated[Any, tf.raw_ops.Any]
```

```
tf.compat.v1.arg_min(  
input: Annotated[Any, tf.raw_ops.Any],  
dimension: Annotated[Any, tf.raw_ops.Any],  
output_type: TV_ArgMin_output_type = tf.dtypes.int64,  
name=None  
) -> Annotated[Any, tf.raw_ops.Any]
```

```
tf.raw_ops.Any
```

```
tf.raw_ops.Any
```

```
tf.dtypes.int64
```

```
tf.raw_ops.Any
```

```
import tensorflow as tf  
a = [1, 10, 26.9, 2.8, 166.32, 62.3]  
b = tf.math.argmin(input = a)  
c = tf.keras.backend.eval(b)  
# c = 0  
# here a[0] = 1 which is the smallest element of a across axis 0
```

```
import tensorflow as tf  
a = [1, 10, 26.9, 2.8, 166.32, 62.3]  
b = tf.math.argmin(input = a)  
c = tf.keras.backend.eval(b)  
# c = 0  
# here a[0] = 1 which is the smallest element of a across axis 0
```

Documentation

Returns the index with the smallest value across dimensions of a tensor.
(deprecated)

Note that in case of ties the identity of the return value is not guaranteed.

Returns
