

tf.compat.v1.assign Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/assign

Update ref by assigning value to it.

Function Signatures

```
tf.compat.v1.assign( ref, value, validate_shape=None,  
use_locking=None, name=None )
```

Code Examples

```
tf.compat.v1.assign(  
    ref, value, validate_shape=None, use_locking=None, name=None  
)
```

```
tf.compat.v1.assign(  
    ref, value, validate_shape=None, use_locking=None, name=None  
)
```

```
import tensorflow as tf  
a = tf.Variable([1], shape=tf.TensorShape(None))  
tf.compat.v1.assign(a, [2,3])
```

```
import tensorflow as tf
```

```
a = tf.Variable([1], shape=tf.TensorShape(None))
```

```
tf.compat.v1.assign(a, [2,3])
```

```
with tf.Graph().as_default():  
    with tf.compat.v1.Session() as sess:  
        a = tf.compat.v1.Variable(0, dtype=tf.int64)  
        sess.run(a.initializer)  
        update_op = tf.compat.v1.assign(a, 2)  
        res_a = sess.run(update_op)  
        res_a  
2
```

```
with tf.Graph().as_default():
```

Documentation

Update ref by assigning value to it.

Migrate to TF2

`tf.compat.v1.assign` is mostly compatible with eager execution and `tf.function`. However, argument `'validate_shape'` will be ignored. To avoid shape validation, set `'shape'` to `tf.TensorShape(None)` when constructing the variable:

To switch to the native TF2 style, one could use method `'assign'` of `tf.Variable`:

How to Map Arguments

Description

Used in the notebooks

- Tutorial on Multi Armed Bandits in TF-Agents

This operation outputs a Tensor that holds the new value of `ref` after the value has been assigned. This makes it easier to chain operations that need to use the reset value.

Returns

Before & After Usage Example

Before:

After:

