

tf.compat.v1.count_nonzero Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/count_nonzero

*Computes number of nonzero elements across dimensions of a tensor.
(deprecated arguments) (deprecated arguments)*

Function Signatures

```
tf.compat.v1.count_nonzero( input_tensor=None, axis=None,  
keepdims=None, dtype=tf.dtypes.int64, name=None,  
reduction_indices=None, keep_dims=None, input=None )  
(keep_dims)  
(reduction_indices)
```

Code Examples

```
tf.compat.v1.count_nonzero(  
input_tensor=None,  
axis=None,  
keepdims=None,  
dtype=tf.dtypes.int64,  
name=None,  
reduction_indices=None,  
keep_dims=None,  
input=None  
)
```

```
tf.compat.v1.count_nonzero(  
input_tensor=None,  
axis=None,  
keepdims=None,  
dtype=tf.dtypes.int64,  
name=None,  
reduction_indices=None,  
keep_dims=None,  
input=None  
)
```

```
tf.dtypes.int64
```

```
x = tf.constant([[0, 1, 0], [1, 1, 0]])  
tf.math.count_nonzero(x) # 3  
tf.math.count_nonzero(x, 0) # [1, 2, 0]  
tf.math.count_nonzero(x, 1) # [1, 2]  
tf.math.count_nonzero(x, 1, keepdims=True) # [[1], [2]]  
tf.math.count_nonzero(x, [0, 1]) # 3
```

```
x = tf.constant([[0, 1, 0], [1, 1, 0]])
tf.math.count_nonzero(x) # 3
tf.math.count_nonzero(x, 0) # [1, 2, 0]
tf.math.count_nonzero(x, 1) # [1, 2]
tf.math.count_nonzero(x, 1, keepdims=True) # [[1], [2]]
tf.math.count_nonzero(x, [0, 1]) # 3
```

```
x = tf.constant(["", "a", " ", "b", ""])
tf.math.count_nonzero(x) # 3, with "a", " ", and "b" as nonzero
strings.
```

```
x = tf.constant(["", "a", " ", "b", ""])
tf.math.count_nonzero(x) # 3, with "a", " ", and "b" as nonzero
strings.
```

Documentation

Computes number of nonzero elements across dimensions of a tensor.
(deprecated arguments) (deprecated arguments)

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.math.count_nonzero`

Reduces `input_tensor` along the dimensions given in `axis`.

Unless `keepdims` is true, the rank of the tensor is reduced by 1 for each entry in `axis`. If `keepdims` is true, the reduced dimensions are retained with length 1.

If `axis` has no entries, all dimensions are reduced, and a tensor with a single element is returned.

For example:

`## For example:`

`## Returns`

