

tf.compat.v1.create_partitioned_variables

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/create_partitioned_variables

*Create a list of partitioned variables according to the given slicing.
(deprecated)*

Function Signatures

```
tf.compat.v1.create_partitioned_variables( shape, slicing,  
initializer, dtype=tf.dtypes.float32, trainable=True,  
collections=None, name=None, reuse=None )
```

Code Examples

```
tf.compat.v1.create_partitioned_variables(  
    shape,  
    slicing,  
    initializer,  
    dtype=tf.dtypes.float32,  
    trainable=True,  
    collections=None,  
    name=None,  
    reuse=None  
)
```

```
tf.compat.v1.create_partitioned_variables(  
    shape,  
    slicing,  
    initializer,  
    dtype=tf.dtypes.float32,  
    trainable=True,  
    collections=None,  
    name=None,  
    reuse=None  
)
```

```
tf.dtypes.float32
```

Documentation

Create a list of partitioned variables according to the given slicing. (deprecated)

Currently only one dimension of the full variable can be sliced, and the full variable can be reconstructed by the concatenation of the returned list along that dimension.

For convenience, The requested number of partitions does not have to divide the corresponding dimension evenly. If it does not, the shapes of the partitions are incremented by 1 starting from partition 0 until all slack is absorbed. The adjustment rules may change in the future, but as you can save/restore these variables with different slicing specifications this should not be a problem.

Returns

Raises