

tf.compat.v1.distributions.kl_divergence

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/distributions/kl_divergence

Get the KL-divergence $KL(\text{distribution_a} \parallel \text{distribution_b})$. (deprecated)

Function Signatures

```
tf.compat.v1.distributions.kl_divergence( distribution_a,  
distribution_b, allow_nan_stats=True, name=None )  
type(distribution_a)  
type(distribution_b)
```

Code Examples

```
tf.compat.v1.distributions.kl_divergence(  
distribution_a, distribution_b, allow_nan_stats=True, name=None  
)
```

```
tf.compat.v1.distributions.kl_divergence(  
distribution_a, distribution_b, allow_nan_stats=True, name=None  
)
```

Documentation

Get the KL-divergence `KL(distribution_a || distribution_b)`. (deprecated)

If there is no KL method registered specifically for `type(distribution_a)` and `type(distribution_b)`, then the class hierarchies of these types are searched.

If one KL method is registered between any pairs of classes in these two parent hierarchies, it is used.

If more than one such registered method exists, the method whose registered classes have the shortest sum MRO paths to the input types is used.

If more than one such shortest path exists, the first method identified in the search is used (favoring a shorter MRO distance to `type(distribution_a)`).

Returns

Raises