

tf.compat.v1.enable_eager_execution

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/enable_eager_execution

Enables eager execution for the lifetime of this program.

Function Signatures

```
tf.compat.v1.enable_eager_execution( config=None,
device_policy=None, execution_mode=None ) -> None
tf.compat.v1.enable_eager_execution() # After eager execution
is enabled, operations are executed as they are # defined and
Tensor objects hold concrete values, which can be accessed as
# numpy.ndarray's through the numpy() method. assert
tf.multiply(6, 7).numpy() == 42
```

Code Examples

```
tf.compat.v1.enable_eager_execution(  
    config=None, device_policy=None, execution_mode=None  
) -> None
```

```
tf.compat.v1.enable_eager_execution(  
    config=None, device_policy=None, execution_mode=None  
) -> None
```

```
tf.compat.v1.enable_eager_execution()  
# After eager execution is enabled, operations are executed as they  
# are  
# defined and Tensor objects hold concrete values, which can be  
# accessed as  
# numpy.ndarray's through the numpy() method.  
assert tf.multiply(6, 7).numpy() == 42
```

```
tf.compat.v1.enable_eager_execution()  
# After eager execution is enabled, operations are executed as they  
# are  
# defined and Tensor objects hold concrete values, which can be  
# accessed as  
# numpy.ndarray's through the numpy() method.  
assert tf.multiply(6, 7).numpy() == 42
```

Documentation

Enables eager execution for the lifetime of this program.

Migrate to TF2

This function is not necessary if you are using TF2. Eager execution is

enabled by default.

Description

Used in the notebooks

- TensorFlow Constrained Optimization Example Using CelebA Dataset
- TensorFlow Distributions: A Gentle Introduction

Eager execution provides an imperative interface to TensorFlow. With eager execution enabled, TensorFlow functions execute operations immediately (as opposed to adding to a graph to be executed later in a `tf.compat.v1.Session`) and

return concrete values (as opposed to symbolic references to a node in a computational graph).

For example:

Eager execution cannot be enabled after TensorFlow APIs have been used to create or execute graphs. It is typically recommended to invoke this function at program startup and not in a library (as most libraries should be usable both with and without eager execution).

- `DEVICE_PLACEMENT_EXPLICIT`: raises an error if the

placement is not correct.

- `DEVICE_PLACEMENT_WARN`: copies the tensors which are not

on the right device but logs a warning.

- `DEVICE_PLACEMENT_SILENT`: silently copies the tensors.

Note that this may hide performance problems as there is no notification provided when operations are blocked on the tensor being copied between devices.

- `DEVICE_PLACEMENT_SILENT_FOR_INT32`: silently copies

int32 tensors, raising errors on the other ones.

`## Raises`