

tf.compat.v1.executing_eagerly_outside_functions

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/executing_eagerly_outside_functions

Returns True if executing eagerly, even if inside a graph function.

Function Signatures

```
tf.compat.v1.executing_eagerly_outside_functions() -> bool  
tf.executing_eagerly()  
tf.compat.v1.enable_eager_execution()
```

Code Examples

```
tf.compat.v1.executing_eagerly_outside_functions() -> bool
```

```
tf.compat.v1.executing_eagerly_outside_functions() -> bool
```

```
tf.compat.v1.enable_eager_execution()
@tf.function
def func():
    # A function constructs TensorFlow graphs, it does not execute
    eagerly,
    # but the outer most context is still eager.
    assert not tf.executing_eagerly()
    return tf.compat.v1.executing_eagerly_outside_functions()
func()
```

```
tf.compat.v1.enable_eager_execution()
```

```
@tf.function
```

```
def func():
```

```
# A function constructs TensorFlow graphs, it does not execute
eagerly,
```

```
# but the outer most context is still eager.
```

Documentation

Returns True if executing eagerly, even if inside a graph function.

This function will check the outermost context for the program and see if it is in eager mode. It is useful comparing to `tf.executing_eagerly()`, which checks the current context and will return False within a `tf.function` body. It can be used to build library that behave differently in eager runtime and v1 session runtime (deprecated).

Example:

Returns