

tf.compat.v1.feature_column.make_parse_example_spec

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/feature_column/make_parse_example_spec

Creates parsing spec dictionary from input feature_columns. (deprecated)

Function Signatures

```
tf.compat.v1.feature_column.make_parse_example_spec(  
    feature_columns )
```

Code Examples

```
tf.compat.v1.feature_column.make_parse_example_spec(  
    feature_columns  
)
```

```
tf.compat.v1.feature_column.make_parse_example_spec(  
    feature_columns  
)
```

```
# Define features and transformations
feature_a = categorical_column_with_vocabulary_file(...)
feature_b = numeric_column(...)
feature_c_bucketized =
bucketized_column(numeric_column("feature_c"), ...)
feature_a_x_feature_c = crossed_column(
columns=["feature_a", feature_c_bucketized], ...)
feature_columns = set(
[feature_b, feature_c_bucketized, feature_a_x_feature_c])
features = tf.io.parse_example(
serialized=serialized_examples,
features=make_parse_example_spec(feature_columns))
```

```
# Define features and transformations
feature_a = categorical_column_with_vocabulary_file(...)
feature_b = numeric_column(...)
feature_c_bucketized =
bucketized_column(numeric_column("feature_c"), ...)
feature_a_x_feature_c = crossed_column(
columns=["feature_a", feature_c_bucketized], ...)
feature_columns = set(
[feature_b, feature_c_bucketized, feature_a_x_feature_c])
features = tf.io.parse_example(
serialized=serialized_examples,
features=make_parse_example_spec(feature_columns))
```

```
{
"feature_a": parsing_ops.VarLenFeature(tf.string),
"feature_b": parsing_ops.FixedLenFeature([1], dtype=tf.float32),
"feature_c": parsing_ops.FixedLenFeature([1], dtype=tf.float32)
}
```

```
{
"feature_a": parsing_ops.VarLenFeature(tf.string),
"feature_b": parsing_ops.FixedLenFeature([1], dtype=tf.float32),
"feature_c": parsing_ops.FixedLenFeature([1], dtype=tf.float32)
}
```

Documentation

Creates parsing spec dictionary from input `feature_columns`. (deprecated)

The returned dictionary can be used as arg 'features' in `tf.io.parse_example`.

Typical usage example:

For the above example, `make_parse_example_spec` would return the dict:

Returns

Raises