

tf.compat.v1.flags.BaseListParser Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/BaseListParser

Base class for a parser of lists of strings.

Function Signatures

```
tf.compat.v1.flags.BaseListParser( token: Optional[Text] =  
None, name: Optional[Text] = None ) -> None  
super().__init__(token, name)
```

Code Examples

```
tf.compat.v1.flags.BaseListParser(  
token: Optional[Text] = None, name: Optional[Text] = None  
) -> None
```

```
tf.compat.v1.flags.BaseListParser(  
token: Optional[Text] = None, name: Optional[Text] = None  
) -> None
```

```
super().__init__(token, name)
```

```
super().__init__(token, name)
```

```
flag_type() -> Text
```

```
flag_type() -> Text
```

```
parse(  
argument: Text  
) -> List[Text]
```

```
parse(  
argument: Text  
) -> List[Text]
```

Documentation

Base class for a parser of lists of strings.

Inherits From: `ArgumentParser`

To extend, inherit from this class; from the subclass `__init__`, call::

where `token` is a character used to tokenize, and `name` is a description of the separator.

Methods

`## flag_type`

See base class.

See base class.

`## Class Variables`