

tf.compat.v1.flags.EnumFlag Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/EnumFlag

Basic enum flag; its value can be any string from list of enum_values.

Function Signatures

```
tf.compat.v1.flags.EnumFlag( name: Text, default:
Optional[Text], help: Optional[Text], enum_values:
Iterable[Text], short_name: Optional[Text] = None,
case_sensitive: bool = True, **args )
flag_type() -> Text
```

Code Examples

```
tf.compat.v1.flags.EnumFlag(
name: Text,
default: Optional[Text],
help: Optional[Text],
enum_values: Iterable[Text],
short_name: Optional[Text] = None,
case_sensitive: bool = True,
**args
)
```

```
tf.compat.v1.flags.EnumFlag(  
    name: Text,  
    default: Optional[Text],  
    help: Optional[Text],  
    enum_values: Iterable[Text],  
    short_name: Optional[Text] = None,  
    case_sensitive: bool = True,  
    **args  
)
```

```
flag_type() -> Text
```

```
flag_type() -> Text
```

```
parse(  
    argument: Union[Text, Optional[_T]]  
) -> None
```

```
parse(  
    argument: Union[Text, Optional[_T]]  
) -> None
```

```
serialize() -> Text
```

```
serialize() -> Text
```

Documentation

Basic enum flag; its value can be any string from list of `enum_values`.

Inherits From: `Flag`

Attributes

Methods

flag_type

Returns a str that describes the type of the flag.

Parses string and sets flag value.

serialize

Serializes the flag.

unparse

__bool__

__eq__

Return self==value.

__ge__

Return a >= b. Computed by @total_ordering from (not a < b).

__gt__

Return a > b. Computed by @total_ordering from (not a < b) and (a != b).

__le__

Return a <= b. Computed by @total_ordering from (a < b) or (a == b).

__lt__

Return self