

tf.compat.v1.flags.FlagHolder Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/FlagHolder

Holds a defined flag.

Function Signatures

```
tf.compat.v1.flags.FlagHolder( flag_values:
tf.compat.v1.flags.FlagValues, flag: Flag[_T],
ensure_non_none_value: bool = False )

flags.DEFINE_integer('foo', ...) flags.DEFINE_integer('bar',
...) def method(): # prints parsed value of 'bar' flag
print(flags.FLAGS.foo) # runtime error due to typo or
possibly bad coding style. print(flags.FLAGS.baz)

_FOO_FLAG = flags.DEFINE_integer('foo', ...) _BAR_FLAG =
flags.DEFINE_integer('bar', ...) def method():
print(_FOO_FLAG.value) print(_BAR_FLAG.value)
```

Code Examples

```
tf.compat.v1.flags.FlagHolder(  
    flag_values: tf.compat.v1.flags.FlagValues,  
    flag: Flag[_T],  
    ensure_non_none_value: bool = False  
)
```

```
tf.compat.v1.flags.FlagHolder(  
    flag_values: tf.compat.v1.flags.FlagValues,  
    flag: Flag[_T],  
    ensure_non_none_value: bool = False  
)
```

```
tf.compat.v1.flags.FlagValues
```

```
flags.DEFINE_integer('foo', ...)  
flags.DEFINE_integer('bar', ...)  
def method():  
    # prints parsed value of 'bar' flag  
    print(flags.FLAGS.foo)  
    # runtime error due to typo or possibly bad coding style.  
    print(flags.FLAGS.baz)
```

```
flags.DEFINE_integer('foo', ...)  
flags.DEFINE_integer('bar', ...)  
def method():  
    # prints parsed value of 'bar' flag  
    print(flags.FLAGS.foo)  
    # runtime error due to typo or possibly bad coding style.  
    print(flags.FLAGS.baz)
```

```
_FOO_FLAG = flags.DEFINE_integer('foo', ...)  
_BAR_FLAG = flags.DEFINE_integer('bar', ...)  
def method():  
    print(_FOO_FLAG.value)  
    print(_BAR_FLAG.value)
```

```
_FOO_FLAG = flags.DEFINE_integer('foo', ...)
_BAR_FLAG = flags.DEFINE_integer('bar', ...)
def method():
    print(_FOO_FLAG.value)
    print(_BAR_FLAG.value)
```

```
serialize() -> Text
```

Documentation

Holds a defined flag.

This facilitates a cleaner api around global state. Instead of::

it encourages code like::

since the name of the flag appears only once in the source code.

Attributes

If `_ensure_non_none_value` is True, then return value is not None.

Methods

`## serialize`

Returns a serialized representation of the flag.

`__bool__`

`## __eq__`

Return `self==value`.

`## __nonzero__`