

tf.compat.v1.flags.FloatParser Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/FloatParser

Parser of floating point values.

Function Signatures

```
tf.compat.v1.flags.FloatParser( lower_bound: Optional[float]
= None, upper_bound: Optional[float] = None ) -> None
convert( argument: Union[int, float, str] ) -> float
```

Code Examples

```
tf.compat.v1.flags.FloatParser(  
  lower_bound: Optional[float] = None, upper_bound: Optional[float] =  
  None  
) -> None
```

```
tf.compat.v1.flags.FloatParser(  
  lower_bound: Optional[float] = None, upper_bound: Optional[float] =  
  None  
) -> None
```

```
convert(  
  argument: Union[int, float, str]  
) -> float
```

```
convert(  
  argument: Union[int, float, str]  
) -> float
```

```
flag_type() -> Text
```

```
flag_type() -> Text
```

```
is_outside_bounds(  
  val: _N  
) -> bool
```

```
is_outside_bounds(  
  val: _N  
) -> bool
```

Documentation

Parser of floating point values.

Inherits From: `ArgumentParser`

Parsed value may be bounded to a given upper and lower bound.

Methods

`## convert`

Returns the float value of argument.

`flag_type`

See base class.

`is_outside_bounds`

Returns whether the value is outside the bounds or not.

See base class.

`## Class Variables`