

tf.compat.v1.gather_nd Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/gather_nd

Gather slices from params into a Tensor with shape specified by indices.

Function Signatures

```
tf.compat.v1.gather_nd( params, indices, name=None,  
batch_dims=0 )
```

Code Examples

```
tf.compat.v1.gather_nd(  
    params, indices, name=None, batch_dims=0  
)
```

```
tf.compat.v1.gather_nd(  
    params, indices, name=None, batch_dims=0  
)
```

```
tf.gather_nd(  
    indices=[[0, 0],  
            [1, 1]],  
    params = [['a', 'b'],  
              ['c', 'd']]).numpy()  
array([b'a', b'd'], dtype=object)
```

```
tf.gather_nd(  

```

```
indices=[[0, 0],
```

```
params = [['a', 'b'],
```

```
['c', 'd']]).numpy()
```

Documentation

Gather slices from params into a Tensor with shape specified by indices.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.manip.gather_nd`

`indices` is a Tensor of indices into `params`. The index vectors are arranged along the last axis of `indices`.

This is similar to `tf.gather`, in which `indices` defines slices into the first dimension of `params`. In `tf.gather_nd`, `indices` defines slices into the first N dimensions of `params`, where $N = \text{indices.shape}[-1]$.

Gathering scalars

In the simplest case the vectors in `indices` index the full rank of `params`:

In this case the result has 1-axis fewer than `indices`, and each index vector is replaced by the scalar indexed from `params`.

In this case the shape relationship is:

If `indices` has a rank of K , it is helpful to think `indices` as a $(K-1)$ -dimensional tensor of indices into `params`.

Gathering slices

If the index vectors do not index the full rank of `params` then each location

in the result contains a slice of params. This example collects rows from a matrix:

Here indices contains [2] index vectors, each with a length of 1. The index vectors each refer to rows of the params matrix. Each row has a shape of [3] so the output shape is [2, 3].

In this case, the relationship between the shapes is:

It is helpful to think of the results in this case as tensors-of-tensors. The shape of the outer tensor is set by the leading dimensions of indices. While the shape of the inner tensors is the shape of a single slice.

Batches

Additionally, both params and indices can have M leading batch dimensions that exactly match. In this case batch_dims must be set to M.

For example, to collect one row from each of a batch of matrices you could set the leading elements of the index vectors to be their location in the batch:

The batch_dims argument lets you omit those leading location dimensions from the index:

This is equivalent to calling a separate gather_nd for each location in the batch dimensions.

More examples

Indexing into a 3-tensor:

The examples below are for the case when only indices have leading extra dimensions. If both 'params' and 'indices' have leading batch dimensions, use the 'batch_dims' parameter to run `gather_nd` in batch mode.

Batched indexing into a matrix:

Batched slice indexing into a matrix:

Batched indexing into a 3-tensor:

Examples with batched 'params' and 'indices':

See also `tf.gather`.

Returns