

tf.compat.v1.gfile.FastGFile Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/gfile/FastGFile

File I/O wrappers without thread locking.

Function Signatures

```
tf.compat.v1.gfile.FastGFile( name, mode='r' )  
close()
```

Code Examples

```
tf.compat.v1.gfile.FastGFile(  
    name, mode='r'  
)
```

```
tf.compat.v1.gfile.FastGFile(  
    name, mode='r'  
)
```

```
with tf.io.gfile.GFile("/tmp/x", "w") as f:  
    f.write("asdf\n")  
    f.write("qwer\n")  
# implicit f.close() at the end of the block
```

```
with tf.io.gfile.GFile("/tmp/x", "w") as f:
```

```
    f.write("asdf\n")
```

```
    f.write("qwer\n")
```

Documentation

File I/O wrappers without thread locking.

Note, that this is somewhat like builtin Python file I/O, but there are semantic differences to make it more efficient for some backing filesystems. For example, a write mode file will not be opened until the first write call (to minimize RPC

invocations in network filesystems).

Attributes

Methods

[View source](#)

Closes the file.

Should be called for the WritableFile to be flushed.

In general, if you use the context manager pattern, you don't need to call this directly.

For cloud filesystems, forgetting to call `close()` might result in data loss as last write might not have been replicated.

[View source](#)

Flushes the Writable file.

This only ensures that the data has made its way out of the process without any guarantees on whether it's written to disk. This means that the data would survive an application crash but not necessarily an OS crash.

[View source](#)

[View source](#)

Returns the contents of a file as a string.

Starts reading from current position in file.

readline

[View source](#)

Reads the next line, keeping `\n`. At EOF, returns `"`.

readlines

[View source](#)

Returns all lines from the file in a list.

[View source](#)

Seeks to the offset in the file. (deprecated arguments)

seekable

[View source](#)

Returns True as FileIO supports random access ops of `seek()/tell()`

[View source](#)

Returns the size of the file.

[View source](#)

Returns the current position in the file.

[View source](#)

Writes `file_content` to the file. Appends to the end of the file.

__enter__

[View source](#)

Make usable with "with" statement.

`__exit__`

[View source](#)

Make usable with "with" statement.

`__iter__`

[View source](#)