

tf.compat.v1.glorot_uniform_initializer

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/glorot_uniform_initializer

The Glorot uniform initializer, also called Xavier uniform initializer.

Function Signatures

```
tf.compat.v1.glorot_uniform_initializer( seed=None,  
dtype=tf.dtypes.float32 )
```

Code Examples

```
tf.compat.v1.glorot_uniform_initializer(  
seed=None,  
dtype=tf.dtypes.float32  
)
```

```
tf.compat.v1.glorot_uniform_initializer(  
seed=None,  
dtype=tf.dtypes.float32  
)
```

```
tf.dtypes.float32
```

```
@classmethod  
from_config(  
    config  
)
```

```
@classmethod
```

```
from_config(  
    config  
)
```

```
initializer = RandomUniform(-1, 1)  
config = initializer.get_config()  
initializer = RandomUniform.from_config(config)
```

```
initializer = RandomUniform(-1, 1)  
config = initializer.get_config()  
initializer = RandomUniform.from_config(config)
```

Documentation

The Glorot uniform initializer, also called Xavier uniform initializer.

Inherits From: `variance_scaling_initializer`

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.initializers.glorot_uniform`

It draws samples from a uniform distribution within $[-limit, limit]$
where $limit$ is $\sqrt{6 / (fan_in + fan_out)}$
where fan_in is the number of input units in the weight tensor
and fan_out is the number of output units in the weight tensor.

References

Methods

from_config

[View source](#)

Instantiates an initializer from a configuration dictionary.

Example:

get_config

[View source](#)

Returns the configuration of the initializer as a JSON-serializable dict.

__call__

[View source](#)

Returns a tensor object initialized as specified by the initializer.