

tf.compat.v1.image.sample_distorted_bounding_box

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/image/sample_distorted_bounding_box

*Generate a single randomly distorted bounding box for an image.
(deprecated)*

Function Signatures

```
tf.compat.v1.image.sample_distorted_bounding_box( image_size,
bounding_boxes, seed=None, seed2=None,
min_object_covered=0.1, aspect_ratio_range=None,
area_range=None, max_attempts=None,
use_image_if_no_bounding_boxes=None, name=None )
```

Code Examples

```
tf.compat.v1.image.sample_distorted_bounding_box(  
    image_size,  
    bounding_boxes,  
    seed=None,  
    seed2=None,  
    min_object_covered=0.1,  
    aspect_ratio_range=None,  
    area_range=None,  
    max_attempts=None,  
    use_image_if_no_bounding_boxes=None,  
    name=None  
)
```

```
tf.compat.v1.image.sample_distorted_bounding_box(  
    image_size,  
    bounding_boxes,  
    seed=None,  
    seed2=None,  
    min_object_covered=0.1,  
    aspect_ratio_range=None,  
    area_range=None,  
    max_attempts=None,  
    use_image_if_no_bounding_boxes=None,  
    name=None  
)
```

```
# Generate a single distorted bounding box.
begin, size, bbox_for_draw =
tf.image.sample_distorted_bounding_box(
tf.shape(image),
bounding_boxes=bounding_boxes,
min_object_covered=0.1)
# Draw the bounding box in an image summary.
image_with_box = tf.image.draw_bounding_boxes(tf.expand_dims(image,
0),
bbox_for_draw)
tf.compat.v1.summary.image('images_with_box', image_with_box)
# Employ the bounding box to distort the image.
distorted_image = tf.slice(image, begin, size)
```

```
# Generate a single distorted bounding box.
begin, size, bbox_for_draw =
tf.image.sample_distorted_bounding_box(
tf.shape(image),
bounding_boxes=bounding_boxes,
min_object_covered=0.1)
# Draw the bounding box in an image summary.
image_with_box = tf.image.draw_bounding_boxes(tf.expand_dims(image,
0),
bbox_for_draw)
tf.compat.v1.summary.image('images_with_box', image_with_box)
# Employ the bounding box to distort the image.
distorted_image = tf.slice(image, begin, size)
```

Documentation

Generate a single randomly distorted bounding box for an image. (deprecated)

Bounding box annotations are often supplied in addition to ground-truth labels in image recognition or object localization tasks. A common technique for training such a system is to randomly distort an image while preserving its content, i.e. data augmentation. This Op outputs a randomly distorted

localization of an object, i.e. bounding box, given an `image_size`, `bounding_boxes` and a series of constraints.

The output of this Op is a single bounding box that may be used to crop the original image. The output is returned as 3 tensors: `begin`, `size` and `bboxes`. The first 2 tensors can be fed directly into `tf.slice` to crop the image. The latter may be supplied to `tf.image.draw_bounding_boxes` to visualize what the bounding box looks like.

Bounding boxes are supplied and returned as `[y_min, x_min, y_max, x_max]`.

The

bounding box coordinates are floats in `[0.0, 1.0]` relative to the width and height of the underlying image.

For example,

Note that if no bounding box information is available, setting `use_image_if_no_bounding_boxes = True` will assume there is a single implicit bounding box covering the whole image. If `use_image_if_no_bounding_boxes` is `false` and no bounding boxes are supplied, an error is raised.

Returns

Raises