

tf.compat.v1.initializers.identity Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/initializers/identity

Initializer that generates the identity matrix.

Function Signatures

```
tf.compat.v1.initializers.identity( gain=1.0,  
dtype=tf.dtypes.float32 )
```

Code Examples

```
tf.compat.v1.initializers.identity(  
gain=1.0,  
dtype=tf.dtypes.float32  
)
```

```
tf.compat.v1.initializers.identity(  
gain=1.0,  
dtype=tf.dtypes.float32  
)
```

```
tf.dtypes.float32
```

```
@classmethod  
from_config(  
    config  
)
```

```
@classmethod
```

```
from_config(  
    config  
)
```

```
initializer = RandomUniform(-1, 1)  
config = initializer.get_config()  
initializer = RandomUniform.from_config(config)
```

```
initializer = RandomUniform(-1, 1)  
config = initializer.get_config()  
initializer = RandomUniform.from_config(config)
```

Documentation

Initializer that generates the identity matrix.

Only use for 2D matrices.

Methods

`## from_config`

[View source](#)

Instantiates an initializer from a configuration dictionary.

Example:

`## get_config`

[View source](#)

Returns the configuration of the initializer as a JSON-serializable dict.

`__call__`

[View source](#)

Returns a tensor object initialized as specified by the initializer.