

Module: `tf.compat.v1.io` Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/io

Public API for `tf._api.v2.io` namespace

Documentation

Public API for `tf._api.v2.io` namespace

Modules

gfile module: Public API for `tf._api.v2.io.gfile` namespace

Classes

class `FixedLenFeature`: Configuration for parsing a fixed-length input feature.

class `FixedLenSequenceFeature`: Configuration for parsing a variable-length input feature into a Tensor.

class `PaddingFIFOQueue`: A `FIFOQueue` that supports batching variable-sized tensors by padding.

class `PriorityQueue`: A queue implementation that dequeues elements in prioritized order.

class `QueueBase`: Base class for queue implementations.

class `RaggedFeature`: Configuration for passing a `RaggedTensor` input feature.

class RandomShuffleQueue: A queue implementation that dequeues elements in a random order.

class SparseFeature: Configuration for parsing a sparse input feature from an Example.

class TFRecordCompressionType: The type of compression for the record.

class TFRecordOptions: Options used for manipulating TFRecord files.

class TFRecordWriter: A class to write records to a TFRecords file.

class VarLenFeature: Configuration for parsing a variable-length input feature.

Functions

decode_and_crop_jpeg(...): Decode and Crop a JPEG-encoded image to a uint8 tensor.

decode_base64(...): Decode web-safe base64-encoded strings.

decode_bmp(...): Decode the first frame of a BMP-encoded image to a uint8 tensor.

decode_compressed(...): Decompress strings.

decode_csv(...): Convert CSV records to tensors. Each column maps to one tensor.

decode_gif(...): Decode the frame(s) of a GIF-encoded image to a uint8 tensor.

decode_image(...): Function for decode_bmp, decode_gif, decode_jpeg, and decode_png.

decode_jpeg(...): Decode a JPEG-encoded image to a uint8 tensor.

decode_json_example(...): Convert JSON-encoded Example records to binary protocol buffer strings.

`decode_png(...)`: Decode a PNG-encoded image to a uint8 or uint16 tensor.

`decode_proto(...)`: The op extracts fields from a serialized protocol buffers message into tensors.

`decode_raw(...)`: Convert raw byte strings into tensors. (deprecated arguments)

`deserialize_many_sparse(...)`: Deserialize and concatenate SparseTensors from a serialized minibatch.

`encode_base64(...)`: Encode strings into web-safe base64 format.

`encode_jpeg(...)`: JPEG-encode an image.

`encode_png(...)`: PNG-encode an image.

`encode_proto(...)`: The op serializes protobuf messages provided in the input tensors.

`extract_jpeg_shape(...)`: Extract the shape information of a JPEG-encoded image.

`is_jpeg(...)`: Convenience function to check if the 'contents' encodes a JPEG image.

`match_filenames_once(...)`: Save the list of files matching pattern, so it is only computed once.

`matching_files(...)`: Returns the set of files matching one or more glob patterns.

`parse_example(...)`: Parses Example protos into a dict of tensors.

`parse_sequence_example(...)`: Parses a batch of SequenceExample protos.

`parse_single_example(...)`: Parses a single Example proto.

`parse_single_sequence_example(...)`: Parses a single SequenceExample proto.

`parse_tensor(...)`: Transforms a serialized tensorflow.TensorProto proto into a Tensor.

`read_file(...)`: Reads the contents of file.

`serialize_many_sparse(...)`: Serialize N-minibatch SparseTensor into an [N, 3] Tensor.

`serialize_sparse(...)`: Serialize a SparseTensor into a 3-vector (1-D Tensor) object.

`serialize_tensor(...)`: Transforms a Tensor into a serialized TensorProto proto.

`tf_record_iterator(...)`: An iterator that read the records from a TFRecords file. (deprecated)

`write_file(...)`: Writes contents to the file at input filename.

`write_graph(...)`: Writes a graph proto to a file.