

tf.compat.v1.lite.OpHint Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/lite/OpHint

A class that helps build tflite function invocations. (deprecated)

Function Signatures

```
tf.compat.v1.lite.OpHint( function_name, level=1,  
children_inputs_mappings=None, **kwargs )
```

Code Examples

```
tf.compat.v1.lite.OpHint(  
function_name, level=1, children_inputs_mappings=None, **kwargs  
)
```

```
tf.compat.v1.lite.OpHint(  
function_name, level=1, children_inputs_mappings=None, **kwargs  
)
```

```
add_input(  
*args, **kwargs  
)
```

```
add_input(  
    *args, **kwargs  
)
```

```
add_inputs(  
    *args, **kwargs  
)
```

```
add_inputs(  
    *args, **kwargs  
)
```

```
add_output(  
    *args, **kwargs  
)
```

```
add_output(  
    *args, **kwargs  
)
```

Documentation

A class that helps build tflite function invocations. (deprecated)

It allows you to take a bunch of TensorFlow ops and annotate the construction such that toco knows how to convert it to tflite. This embeds a pseudo function in a TensorFlow graph. This allows embedding high-level API usage information in a lower level TensorFlow implementation so that an alternative implementation can be substituted later.

Essentially, any "input" into this pseudo op is fed into an identity, and

attributes are added to that input before being used by the constituent ops that make up the pseudo op. A similar process is done to any output that is to be exported from the current op.

Child Classes

```
class OpHintArgumentTracker
```

Methods

```
## add_input
```

[View source](#)

Add a wrapped input argument to the hint.

add_inputs

[View source](#)

Add a sequence of inputs to the function invocation.

add_output

[View source](#)

Add a wrapped output argument to the hint.

add_outputs

[View source](#)

Add a sequence of outputs to the function invocation.

```
## Class Variables
```
