

tf.compat.v1.losses.absolute_difference

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/losses/absolute_difference

Adds an Absolute Difference loss to the training procedure.

Function Signatures

```
tf.compat.v1.losses.absolute_difference( labels, predictions,  
weights=1.0, scope=None,  
loss_collection=ops.GraphKeys.LOSSES,  
reduction=Reduction.SUM_BY_NONZERO_WEIGHTS )
```

Code Examples

```
tf.compat.v1.losses.absolute_difference(  
    labels,  
    predictions,  
    weights=1.0,  
    scope=None,  
    loss_collection=ops.GraphKeys.LOSSES,  
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS  
)
```

```
tf.compat.v1.losses.absolute_difference(  
    labels,  
    predictions,  
    weights=1.0,  
    scope=None,  
    loss_collection=ops.GraphKeys.LOSSES,  
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS  
)
```

Documentation

Adds an Absolute Difference loss to the training procedure.

`weights` acts as a coefficient for the loss. If a scalar is provided, then the loss is simply scaled by the given value. If `weights` is a Tensor of shape `[batch_size]`, then the total loss for each sample of the batch is rescaled by the corresponding element in the `weights` vector. If the shape of `weights` matches the shape of predictions, then the loss of each measurable element of predictions is scaled by the corresponding value of `weights`.

Returns

`##` Raises

eager compatibility

The `loss_collection` argument is ignored when executing eagerly. Consider holding on to the return value or collecting losses via a `tf.keras.Model`.