

tf.compat.v1.math.angle Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/math/angle

Returns the element-wise argument of a complex (or real) tensor.

Function Signatures

```
tf.compat.v1.math.angle( input, name=None )
```

Code Examples

```
tf.compat.v1.math.angle(  
input, name=None  
)
```

```
tf.compat.v1.math.angle(  
input, name=None  
)
```

```
input = tf.constant([-2.25 + 4.75j, 3.25 + 5.75j],  
dtype=tf.complex64)  
tf.math.angle(input).numpy()  
# ==> array([2.0131705, 1.056345 ], dtype=float32)
```

```
input = tf.constant([-2.25 + 4.75j, 3.25 + 5.75j],  
dtype=tf.complex64)  
tf.math.angle(input).numpy()  
# ==> array([2.0131705, 1.056345 ], dtype=float32)
```

Documentation

Returns the element-wise argument of a complex (or real) tensor.

Given a tensor input, this operation returns a tensor of type float that is the argument of each element in input considered as a complex number.

The elements in input are considered to be complex numbers of the form $(a + bj)$, where a is the real part and b is the imaginary part.

If input is real then b is zero by definition.

The argument returned by this function is of the form $\text{atan2}(b, a)$.

If input is real, a tensor of all zeros is returned.

For example:

Returns