

tf.compat.v1.metrics.mean_iou Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/mean_iou

Calculate per-step mean Intersection-Over-Union (mIOU).

Function Signatures

```
tf.compat.v1.metrics.mean_iou( labels, predictions,  
    num_classes, weights=None, metrics_collections=None,  
    updates_collections=None, name=None )
```

Code Examples

```
tf.compat.v1.metrics.mean_iou(  
    labels,  
    predictions,  
    num_classes,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.mean_iou(  
    labels,  
    predictions,  
    num_classes,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

Documentation

Calculate per-step mean Intersection-Over-Union (mIOU).

Mean Intersection-Over-Union is a common evaluation metric for semantic image segmentation, which first computes the IOU for each semantic class and then computes the average over classes.

IOU is defined as follows:

$$\text{IOU} = \text{true_positive} / (\text{true_positive} + \text{false_positive} + \text{false_negative}).$$

The predictions are accumulated in a confusion matrix, weighted by weights, and mIOU is then calculated from it.

For estimation of the metric over a stream of data, the function creates an `update_op` operation that updates these variables and returns the `mean_iou`.

If `weights` is `None`, `weights` default to 1. Use weights of 0 to mask values.

Returns

Raises