

tf.compat.v1.metrics.precision_at_threshold

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/precision_at_thresholds

Computes precision values for different thresholds on predictions.

Function Signatures

```
tf.compat.v1.metrics.precision_at_thresholds( labels,  
predictions, thresholds, weights=None,  
metrics_collections=None, updates_collections=None, name=None  
)
```

Code Examples

```
tf.compat.v1.metrics.precision_at_thresholds(  
    labels,  
    predictions,  
    thresholds,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.precision_at_thresholds(  
    labels,  
    predictions,  
    thresholds,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

Documentation

Computes precision values for different thresholds on predictions.

The `precision_at_thresholds` function creates four local variables, `true_positives`, `true_negatives`, `false_positives` and `false_negatives` for various values of thresholds. `precision[i]` is defined as the total weight of values in predictions above `thresholds[i]` whose corresponding entry in labels is `True`, divided by the total weight of values in predictions above `thresholds[i]` ($\text{true_positives}[i] / (\text{true_positives}[i] + \text{false_positives}[i])$).

For estimation of the metric over a stream of data, the function creates an `update_op` operation that updates these variables and returns the precision.

If `weights` is `None`, `weights` default to 1. Use weights of 0 to mask values.

Returns

Raises