

tf.compat.v1.metrics.sensitivity_at_specificity

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/sensitivity_at_specificity

Computes the specificity at a given sensitivity.

Function Signatures

```
tf.compat.v1.metrics.sensitivity_at_specificity( labels,  
predictions, specificity, weights=None, num_thresholds=200,  
metrics_collections=None, updates_collections=None, name=None  
)
```

Code Examples

```
tf.compat.v1.metrics.sensitivity_at_specificity(  
    labels,  
    predictions,  
    specificity,  
    weights=None,  
    num_thresholds=200,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.sensitivity_at_specificity(  
    labels,  
    predictions,  
    specificity,  
    weights=None,  
    num_thresholds=200,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

Documentation

Computes the specificity at a given sensitivity.

The `sensitivity_at_specificity` function creates four local variables, `true_positives`, `true_negatives`, `false_positives` and `false_negatives` that are used to compute the sensitivity at the given specificity value. The threshold for the given specificity value is computed and used to evaluate the corresponding sensitivity.

For estimation of the metric over a stream of data, the function creates an `update_op` operation that updates these variables and returns the sensitivity. `update_op` increments the `true_positives`, `true_negatives`, `false_positives` and `false_negatives` counts with the weight of each case found in the predictions and labels.

If `weights` is `None`, `weights` default to 1. Use weights of 0 to mask values.

For additional information about specificity and sensitivity, see the following: https://en.wikipedia.org/wiki/Sensitivity_and_specificity

Returns

`## Raises`
