

tf.compat.v1.metrics.specificity_at_sensitivity

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/specificity_at_sensitivity

Computes the specificity at a given sensitivity.

Function Signatures

```
tf.compat.v1.metrics.specificity_at_sensitivity( labels,  
predictions, sensitivity, weights=None, num_thresholds=200,  
metrics_collections=None, updates_collections=None, name=None  
)
```

Code Examples

```
tf.compat.v1.metrics.specificity_at_sensitivity(  
    labels,  
    predictions,  
    sensitivity,  
    weights=None,  
    num_thresholds=200,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.specificity_at_sensitivity(  
    labels,  
    predictions,  
    sensitivity,  
    weights=None,  
    num_thresholds=200,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

Documentation

Computes the specificity at a given sensitivity.

The `specificity_at_sensitivity` function creates four local variables, `true_positives`, `true_negatives`, `false_positives` and `false_negatives` that are used to compute the specificity at the given sensitivity value. The threshold for the given sensitivity value is computed and used to evaluate the corresponding specificity.

For estimation of the metric over a stream of data, the function creates an `update_op` operation that updates these variables and returns the specificity. `update_op` increments the `true_positives`, `true_negatives`, `false_positives` and `false_negatives` counts with the weight of each case found in the predictions and labels.

If `weights` is `None`, `weights` default to 1. Use weights of 0 to mask values.

For additional information about specificity and sensitivity, see the following: https://en.wikipedia.org/wiki/Sensitivity_and_specificity

Returns

`## Raises`