

tf.compat.v1.mixed_precision.disable_mixed_precision_graph_rewrite

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/mixed_precision/disable_mixed_precision_graph_rewrite

Disables the mixed precision graph rewrite.

Function Signatures

```
tf.compat.v1.mixed_precision.disable_mixed_precision_graph_rewrite()
```

Code Examples

```
tf.compat.v1.mixed_precision.disable_mixed_precision_graph_rewrite()  
)
```

```
tf.compat.v1.mixed_precision.disable_mixed_precision_graph_rewrite()  
)
```

Documentation

Disables the mixed precision graph rewrite.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.train.experimental.disable_mixed_precision_graph_rewrite`

After this is called, the mixed precision graph rewrite will no longer run for new Sessions, and so float32 operations will no longer be converted to float16 in such Sessions. However, any existing Sessions will continue to have the graph rewrite enabled if they were created after `enable_mixed_precision_graph_rewrite` was called but before `disable_mixed_precision_graph_rewrite` was called.

This does not undo the effects of loss scaling. Any optimizers wrapped with a `LossScaleOptimizer` will continue to do loss scaling, although this loss scaling will no longer be useful if the optimizer is used in new Sessions, as the graph rewrite no longer converts the graph to use float16.

This function is useful for unit testing. A unit tests can test using the mixed precision graph rewrite, then disable it so future unit tests continue using float32. If this is done, unit tests should not share a single session, as `enable_mixed_precision_graph_rewrite` and `disable_mixed_precision_graph_rewrite` have no effect on existing sessions.

