

tf.compat.v1.nn.ctc_loss_v2 Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/ctc_loss_v2

Computes CTC (Connectionist Temporal Classification) loss.

Function Signatures

```
tf.compat.v1.nn.ctc_loss_v2( labels, logits, label_length,  
logit_length, logits_time_major=True, unique=None,  
blank_index=None, name=None )
```

Code Examples

```
tf.compat.v1.nn.ctc_loss_v2(  
    labels,  
    logits,  
    label_length,  
    logit_length,  
    logits_time_major=True,  
    unique=None,  
    blank_index=None,  
    name=None  
)
```

```
tf.compat.v1.nn.ctc_loss_v2(  
    labels,  
    logits,  
    label_length,  
    logit_length,  
    logits_time_major=True,  
    unique=None,  
    blank_index=None,  
    name=None  
)
```

Documentation

Computes CTC (Connectionist Temporal Classification) loss.

This op implements the CTC loss as presented in (Graves et al., 2006).

Notes:

- Same as the "Classic CTC" in TensorFlow 1.x's `tf.compat.v1.nn.ctc_loss` setting of `preprocess_collapse_repeated=False`, `ctc_merge_repeated=True`

- Labels may be supplied as either a dense, zero-padded tensor with a

vector of label sequence lengths OR as a `SparseTensor`.

- On TPU and GPU: Only dense padded labels are supported.
- On CPU: Caller may use `SparseTensor` or dense padded labels but calling with

a `SparseTensor` will be significantly faster.

- Default blank label is 0 rather than `num_classes - 1`, unless overridden by

`blank_index`.

Returns

References