

tf.compat.v1.nn.dropout Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/dropout

Computes dropout. (deprecated arguments)

Function Signatures

```
tf.compat.v1.nn.dropout( x, keep_prob=None, noise_shape=None,
seed=None, name=None, rate=None )
(keep_prob)
```

Code Examples

```
tf.compat.v1.nn.dropout(
x, keep_prob=None, noise_shape=None, seed=None, name=None,
rate=None
)
```

```
tf.compat.v1.nn.dropout(
x, keep_prob=None, noise_shape=None, seed=None, name=None,
rate=None
)
```

Documentation

Computes dropout. (deprecated arguments)

For each element of `x`, with probability `rate`, outputs 0, and otherwise scales up the input by $1 / (1 - \text{rate})$. The scaling is such that the expected sum is unchanged.

By default, each element is kept or dropped independently. If `noise_shape` is specified, it must be

broadcastable

to the shape of `x`, and only dimensions with `noise_shape[i] == shape(x)[i]` will make independent decisions. For example, if `shape(x) = [k, l, m, n]` and `noise_shape = [k, 1, 1, n]`, each batch and channel component will be kept independently and each row and column will be kept or not kept together.

Returns

Raises