

tf.compat.v1.nn.softmax_cross_entropy_with_logits

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/nn/softmax_cross_entropy_with_logits_v2

Computes softmax cross entropy between logits and labels. (deprecated arguments)

Function Signatures

```
tf.compat.v1.nn.softmax_cross_entropy_with_logits_v2( labels,
logits, axis=None, name=None, dim=None )
(dim)
```

Code Examples

```
tf.compat.v1.nn.softmax_cross_entropy_with_logits_v2(
labels, logits, axis=None, name=None, dim=None
)
```

```
tf.compat.v1.nn.softmax_cross_entropy_with_logits_v2(
labels, logits, axis=None, name=None, dim=None
)
```

Documentation

Computes softmax cross entropy between logits and labels. (deprecated arguments)

Used in the notebooks

- Classify Flowers with Transfer Learning

Measures the probability error in discrete classification tasks in which the classes are mutually exclusive (each entry is in exactly one class). For example, each CIFAR-10 image is labeled with one and only one label: an image can be a dog or a truck, but not both.

If using exclusive labels (wherein one and only one class is true at a time), see `sparse_softmax_cross_entropy_with_logits`.

A common use case is to have logits and labels of shape `[batch_size, num_classes]`, but higher dimensions are supported, with the `axis` argument specifying the class dimension.

logits and labels must have the same dtype (either float16, float32, or float64).

Backpropagation will happen into both logits and labels. To disallow backpropagation into labels, pass label tensors through `tf.stop_gradient` before feeding it to this function.

Note that to avoid confusion, it is required to pass only named arguments to this function.

Returns

