

tf.compat.v1.pad Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/pad

Pads a tensor.

Function Signatures

```
tf.compat.v1.pad( tensor, paddings, mode='CONSTANT',  
name=None, constant_values=0 )
```

Code Examples

```
tf.compat.v1.pad(  
tensor, paddings, mode='CONSTANT', name=None, constant_values=0  
)
```

```
tf.compat.v1.pad(  
tensor, paddings, mode='CONSTANT', name=None, constant_values=0  
)
```

```

t = tf.constant([[1, 2, 3], [4, 5, 6]])
paddings = tf.constant([[1, 1,], [2, 2]])
# 'constant_values' is 0.
# rank of 't' is 2.
tf.pad(t, paddings, "CONSTANT") # [[0, 0, 0, 0, 0, 0, 0],
# [0, 0, 1, 2, 3, 0, 0],
# [0, 0, 4, 5, 6, 0, 0],
# [0, 0, 0, 0, 0, 0, 0]]
tf.pad(t, paddings, "REFLECT") # [[6, 5, 4, 5, 6, 5, 4],
# [3, 2, 1, 2, 3, 2, 1],
# [6, 5, 4, 5, 6, 5, 4],
# [3, 2, 1, 2, 3, 2, 1]]
tf.pad(t, paddings, "SYMMETRIC") # [[2, 1, 1, 2, 3, 3, 2],
# [2, 1, 1, 2, 3, 3, 2],
# [5, 4, 4, 5, 6, 6, 5],
# [5, 4, 4, 5, 6, 6, 5]]

```

```

t = tf.constant([[1, 2, 3], [4, 5, 6]])
paddings = tf.constant([[1, 1,], [2, 2]])
# 'constant_values' is 0.
# rank of 't' is 2.
tf.pad(t, paddings, "CONSTANT") # [[0, 0, 0, 0, 0, 0, 0],
# [0, 0, 1, 2, 3, 0, 0],
# [0, 0, 4, 5, 6, 0, 0],
# [0, 0, 0, 0, 0, 0, 0]]
tf.pad(t, paddings, "REFLECT") # [[6, 5, 4, 5, 6, 5, 4],
# [3, 2, 1, 2, 3, 2, 1],
# [6, 5, 4, 5, 6, 5, 4],
# [3, 2, 1, 2, 3, 2, 1]]
tf.pad(t, paddings, "SYMMETRIC") # [[2, 1, 1, 2, 3, 3, 2],
# [2, 1, 1, 2, 3, 3, 2],
# [5, 4, 4, 5, 6, 6, 5],
# [5, 4, 4, 5, 6, 6, 5]]

```

Documentation

Pads a tensor.

This operation pads a tensor according to the paddings you specify.

paddings is an integer tensor with shape $[n, 2]$, where n is the rank of tensor. For each dimension D of input, $\text{paddings}[D, 0]$ indicates how many values to add before the contents of tensor in that dimension, and $\text{paddings}[D, 1]$ indicates how many values to add after the contents of tensor in that dimension. If mode is "REFLECT" then both $\text{paddings}[D, 0]$ and $\text{paddings}[D, 1]$ must be no greater than $\text{tensor.dim_size}(D) - 1$. If mode is "SYMMETRIC" then both $\text{paddings}[D, 0]$ and $\text{paddings}[D, 1]$ must be no greater than $\text{tensor.dim_size}(D)$.

The padded size of each dimension D of the output is:

$\text{paddings}[D, 0] + \text{tensor.dim_size}(D) + \text{paddings}[D, 1]$

For example:

Returns

Raises