

tf.compat.v1.placeholder Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/placeholder

Inserts a placeholder for a tensor that will be always fed.

Function Signatures

```
tf.compat.v1.placeholder( dtype, shape=None, name=None )
```

Code Examples

```
tf.compat.v1.placeholder(  
dtype, shape=None, name=None  
)
```

```
tf.compat.v1.placeholder(  
dtype, shape=None, name=None  
)
```

```
x = tf.compat.v1.placeholder(tf.float32, shape=(1024, 1024))  
y = tf.matmul(x, x)  
with tf.compat.v1.Session() as sess:  
    print(sess.run(y)) # ERROR: will fail because x was not fed.  
    rand_array = np.random.rand(1024, 1024)  
    print(sess.run(y, feed_dict={x: rand_array})) # Will succeed.
```

```
x = tf.compat.v1.placeholder(tf.float32, shape=(1024, 1024))  
y = tf.matmul(x, x)  
with tf.compat.v1.Session() as sess:  
    print(sess.run(y)) # ERROR: will fail because x was not fed.  
    rand_array = np.random.rand(1024, 1024)  
    print(sess.run(y, feed_dict={x: rand_array})) # Will succeed.
```

Documentation

Inserts a placeholder for a tensor that will be always fed.

Migrate to TF2

This API is not compatible with eager execution and `tf.function`. To migrate to TF2, rewrite the code to be compatible with eager execution. Check the

migration

guide

on replacing `Session.run` calls. In TF2, you can just pass tensors directly into ops and layers. If you want to explicitly set up your inputs, also see

Keras functional API on

how to use `tf.keras.Input` to replace `tf.compat.v1.placeholder`.

`tf.function` arguments also do the job of `tf.compat.v1.placeholder`.

For more details please read Better

performance with `tf.function`.

Description

Used in the notebooks

- Debug a TensorFlow 2 migrated training pipeline
- Migrate the SavedModel workflow
- Migrating your TFLite code to TF2
- Generating Images with BigBiGAN
- Classify Flowers with Transfer Learning
- Generating Images with Little Data Using S3GAN
- Generating Images with BigGAN
- Exploring the TF-Hub CORD-19 Swivel Embeddings

For example:

Returns

Raises