

tf.compat.v1.placeholder_with_default

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/placeholder_with_default

A placeholder op that passes through input when its output is not fed.

Function Signatures

```
tf.compat.v1.placeholder_with_default( input, shape,  
name=None )
```

Code Examples

```
tf.compat.v1.placeholder_with_default(  
input, shape, name=None  
)
```

```
tf.compat.v1.placeholder_with_default(  
input, shape, name=None  
)
```

```
@tf.function  
def f():  
x = tf.compat.v1.placeholder_with_default(  
tf.constant([[1., 2., 3.], [4., 5., 6.]]), [None, 3])  
y = tf.constant([[1.],[2.], [3.]])  
z = tf.matmul(x, y)  
assert z.shape[0] == None  
assert z.shape[1] == 1
```

```
@tf.function
```

```
x = tf.compat.v1.placeholder_with_default(  

```

```
tf.constant([[1., 2., 3.], [4., 5., 6.]]), [None, 3])
```

```
y = tf.constant([[1.],[2.], [3.]])
```

Documentation

A placeholder op that passes through input when its output is not fed.

Migrate to TF2

This API is strongly discouraged for use with eager execution and `tf.function`. The primary use of this API is for testing computation wrapped within a `tf.function` where the input tensors might not have statically known fully-defined shapes. The same can be achieved by creating a concrete function from the `tf.function` with a `tf.TensorSpec` input which has partially defined shapes. For example, the code

can easily be replaced by

You can learn more about `tf.function` at [Better performance with tf.function](#).

Description

Returns