

tf.compat.v1.reduce_max Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/reduce_max

*Computes `tf.math.maximum` of elements across dimensions of a tensor.
(deprecated arguments)*

Function Signatures

```
tf.compat.v1.reduce_max( input_tensor, axis=None,
keepdims=None, name=None, reduction_indices=None,
keep_dims=None )
(keep_dims)
```

Code Examples

```
tf.compat.v1.reduce_max(
input_tensor,
axis=None,
keepdims=None,
name=None,
reduction_indices=None,
keep_dims=None
)
```

```
tf.compat.v1.reduce_max(  
    input_tensor,  
    axis=None,  
    keepdims=None,  
    name=None,  
    reduction_indices=None,  
    keep_dims=None  
)
```

```
>>> x = tf.constant([5, 1, 2, 4])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([-5, -1, -2, -4])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([4, float('nan')])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([float('nan'), float('nan')])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([float('-inf'), float('inf')])  
>>> tf.reduce_max(x)
```

```
>>> x = tf.constant([5, 1, 2, 4])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([-5, -1, -2, -4])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([4, float('nan')])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([float('nan'), float('nan')])  
>>> tf.reduce_max(x)  
  
>>> x = tf.constant([float('-inf'), float('inf')])  
>>> tf.reduce_max(x)
```

Documentation

Computes `tf.math.maximum` of elements across dimensions of a tensor.
(deprecated arguments)

This is the reduction operation for the elementwise `tf.math.maximum` op.

Reduces `input_tensor` along the dimensions given in `axis`.

Unless `keepdims` is true, the rank of the tensor is reduced by 1 for each of the entries in `axis`, which must be unique. If `keepdims` is true, the reduced dimensions are retained with length 1.

If `axis` is `None`, all dimensions are reduced, and a tensor with a single element is returned.

Usage example

See the numpy docs for `np.amax` and `np.nanmax` behavior.

Returns