

tf.compat.v1.saved_model.signature_def_u

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/saved_model/signature_def_utils/MethodNameUpdater

Updates the method name(s) of the SavedModel stored in the given path.

Function Signatures

```
tf.compat.v1.saved_model.signature_def_utils.MethodNameUpdater(  
    export_dir )
```

Code Examples

```
tf.compat.v1.saved_model.signature_def_utils.MethodNameUpdater(  
    export_dir  
)
```

```
tf.compat.v1.saved_model.signature_def_utils.MethodNameUpdater(  
    export_dir  
)
```

```

...
updater =
tf.compat.v1.saved_model.signature_def_utils.MethodNameUpdater(
export_dir)
# Update all signature_defs with key "foo" in all meta graph defs.
updater.replace_method_name(signature_key="foo",
method_name="regress")
# Update a single signature_def with key "bar" in the meta graph
def with
# tags ["serve"]
updater.replace_method_name(signature_key="bar",
method_name="classify",
tags="serve")
updater.save(new_export_dir)

```

```

...
updater =
tf.compat.v1.saved_model.signature_def_utils.MethodNameUpdater(
export_dir)
# Update all signature_defs with key "foo" in all meta graph defs.
updater.replace_method_name(signature_key="foo",
method_name="regress")
# Update a single signature_def with key "bar" in the meta graph
def with
# tags ["serve"]
updater.replace_method_name(signature_key="bar",
method_name="classify",
tags="serve")
updater.save(new_export_dir)

```

```

replace_method_name(
signature_key, method_name, tags=None
)

```

```

replace_method_name(
signature_key, method_name, tags=None
)

```

```
save(  
new_export_dir=None  
)
```

```
save(  
new_export_dir=None  
)
```

Documentation

Updates the method name(s) of the SavedModel stored in the given path.

The `MethodNameUpdater` class provides the functionality to update the method name field in the `signature_defs` of the given `SavedModel`. For example, it can be used to replace the `predict` `method_name` to `regress`.

Typical usages of the `MethodNameUpdater`

Raises

Methods

replace_method_name

[View source](#)

Replaces the `method_name` in the specified `signature_def`.

This will match and replace multiple sig defs iff `tags` is `None` (i.e when multiple `MetaGraphs` have a `signature_def` with the same key).

If `tags` is not `None`, this will only replace a single `signature_def` in the `MetaGraph` with matching `tags`.

[View source](#)

Saves the updated `SavedModel`.