

tf.compat.v1.scatter_div Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/scatter_div

Divides a variable reference by sparse updates.

Function Signatures

```
tf.compat.v1.scatter_div( ref, indices, updates,
use_locking=False, name=None )

# Scalar indices ref[indices, ...] /= updates[...] # Vector
indices (for each i) ref[indices[i], ...] /= updates[i, ...]
# High rank indices (for each i, ..., j) ref[indices[i, ...,
j], ...] /= updates[i, ..., j, ...]
```

Code Examples

```
tf.compat.v1.scatter_div(  
    ref, indices, updates, use_locking=False, name=None  
)
```

```
tf.compat.v1.scatter_div(  
    ref, indices, updates, use_locking=False, name=None  
)
```

```
# Scalar indices  
ref[indices, ...] /= updates[...]  
# Vector indices (for each i)  
ref[indices[i], ...] /= updates[i, ...]  
# High rank indices (for each i, ..., j)  
ref[indices[i, ..., j], ...] /= updates[i, ..., j, ...]
```

```
# Scalar indices  
ref[indices, ...] /= updates[...]  
# Vector indices (for each i)  
ref[indices[i], ...] /= updates[i, ...]  
# High rank indices (for each i, ..., j)  
ref[indices[i, ..., j], ...] /= updates[i, ..., j, ...]
```

Documentation

Divides a variable reference by sparse updates.

This operation computes

This operation outputs `ref` after the update is done.

This makes it easier to chain operations that need to use the reset value.

Duplicate entries are handled correctly: if multiple indices reference the same location, their contributions divide.

Requires `updates.shape = indices.shape + ref.shape[1:]` or `updates.shape = []`.

Returns