

tf.compat.v1.scatter_max Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/scatter_max

Reduces sparse updates into a variable reference using the max operation.

Function Signatures

```
tf.compat.v1.scatter_max( ref, indices, updates,
use_locking=False, name=None )

# Scalar indices ref[indices, ...] = max(ref[indices, ...],
updates[...]) # Vector indices (for each i) ref[indices[i],
... ] = max(ref[indices[i], ...], updates[i, ...]) # High rank
indices (for each i, ..., j) ref[indices[i, ..., j], ...] =
max(ref[indices[i, ..., j], ...], updates[i, ..., j, ...])
```

Code Examples

```
tf.compat.v1.scatter_max(  
    ref, indices, updates, use_locking=False, name=None  
)
```

```
tf.compat.v1.scatter_max(  
    ref, indices, updates, use_locking=False, name=None  
)
```

```
# Scalar indices  
ref[indices, ...] = max(ref[indices, ...], updates[...])  
# Vector indices (for each i)  
ref[indices[i], ...] = max(ref[indices[i], ...], updates[i, ...])  
# High rank indices (for each i, ..., j)  
ref[indices[i, ..., j], ...] = max(ref[indices[i, ..., j], ...],  
    updates[i, ..., j, ...])
```

```
# Scalar indices  
ref[indices, ...] = max(ref[indices, ...], updates[...])  
# Vector indices (for each i)  
ref[indices[i], ...] = max(ref[indices[i], ...], updates[i, ...])  
# High rank indices (for each i, ..., j)  
ref[indices[i, ..., j], ...] = max(ref[indices[i, ..., j], ...],  
    updates[i, ..., j, ...])
```

Documentation

Reduces sparse updates into a variable reference using the max operation.

This operation computes

This operation outputs ref after the update is done.

This makes it easier to chain operations that need to use the reset value.

Duplicate entries are handled correctly: if multiple indices reference the same location, their contributions combine.

Requires `updates.shape = indices.shape + ref.shape[1:]` or `updates.shape = []`.

Returns